

C1037 nitrocellulose glossy varnish on the furniture CELOLESK

Creation date	19th October 2016	Version	3.0
Revision date	09th February 2024		

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

C1037 nitrocellulose glossy varnish on the furniture
CELOLESK
mixture
C1037-: A-C0000; Z2C0000
H6DX-92XP-E002-XUHD

Substance / mixture
Number
UFI
Other mixture names
C1037 Nitrocelulózový lesklý lak na nábytek CELOLESK

1.2. Relevant identified uses of the substance or mixture and uses advised against

Mixture's intended use

CELOLESK C1037 is a quick-drying glossy colorless varnish, ideal for finishing wooden and wicker furniture, including sofas, and all other wooden and cork objects in the home.

Main intended use

PC-PNT-2 Paints/coatings - Decorative

Mixture uses advised against

The product should not be used in ways other than those referred in Section 1.

1.3. Details of the supplier of the safety data sheet

Manufacturer

Name or trade name	COLORLAK, a.s.
Address	Tovární 1076, Staré Město, 686 03 Czech Republic
Identification number (CRN)	49444964
VAT Reg No	CZ49444964
Phone	+420 572527111
E-mail	colorlak@colorlak.cz
Web address	www.colorlak.cz

Competent person responsible for the safety data sheet

Name	Ing. Veronika Chytilová
E-mail	chytilova@colorlak.cz

1.4. Emergency telephone number

European emergency number: 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification of the mixture in accordance with Regulation (EC) No 1272/2008

The mixture is classified as dangerous.

Flam. Liq. 2, H225
Skin Irrit. 2, H315
Eye Dam. 1, H318
STOT SE 3, H336, H335
STOT RE 2, H373 (central nervous system)
Aquatic Chronic 3, H412

Most serious adverse physico-chemical effects

Highly flammable liquid and vapour.

Most serious adverse effects on human health and the environment

May cause drowsiness or dizziness. May cause damage to the central nervous system through prolonged or repeated exposure. Causes skin irritation. Causes serious eye damage. May cause respiratory irritation. Harmful to aquatic life with long lasting effects.

 Responsible Care® OUR COMMITMENT TO SUSTAINABILITY	SAFETY DATA SHEET according to Regulation (EC) No 1907/2006 (REACH) as amended			 COLORLAK barvy, které vydrží
C1037 nitrocellulose glossy varnish on the furniture CELOLESK				
Creation date	19th October 2016			
Revision date	09th February 2024	Version	3.0	

2.2. Label elements

Hazard pictogram



Signal word

Danger

Hazardous substances

n-butyl acetate

Technical xylene (mixed with ethylbenzene)

2-methylpropan-1-ol

Hazard statements

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to the central nervous system through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water and soap.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P314	Get medical advice/attention if you feel unwell.
P370+P378	In case of fire: Use foam (alcohol resistant), carbon dioxide, a spray mist, powder to extinguish.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to by handing over to a person authorized to dispose of waste or a site designated by the town.

Supplemental information

EUH208	Contains rosin. May produce an allergic reaction.
EUH066	Repeated exposure may cause skin dryness or cracking.

Requirements for child-resistant fastenings and tactile warning of danger

Container must carry a tactile warning of danger.

2.3. Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended.

 Responsible Care® OUR COMMITMENT TO SUSTAINABILITY	SAFETY DATA SHEET		 COLORLAK barvy, které vydrží
according to Regulation (EC) No 1907/2006 (REACH) as amended			
C1037 nitrocellulose glossy varnish on the furniture CELOLESK			
Creation date	19th October 2016	Version	3.0
Revision date	09th February 2024		

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

CELOLESK C1037 varnish is a colloidal solution of nitrocellulose in organic solvents with the addition of plasticizers, synthetic resins and special additives.

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Index: 607-025-00-1 CAS: 123-86-4 EC: 204-658-1 Registration number: 01-2119485493-29	n-butyl acetate	20-30	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	2
EC: 905-588-0 Registration number: 01-2119539452-40	Technical xylene (mixed with ethylbenzene)	18,5-21,5	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Acute Tox. 4, H312+H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Specific concentration limit: STOT RE 2, H373 (central nervous system): C ≥ 10 % ATE Dermal = 1100 mg/kg bw ATE Inhalation (vapor) = 11 mg/l	2
CAS: 9004-70-0 EC: 682-719-5	Nitrocellulose, nitrogen content ≤ 12,6%	15-22	Desen. Expl. 3, H207	1
Index: 603-108-00-1 CAS: 78-83-1 EC: 201-148-0 Registration number: 01-2119484609-23	2-methylpropan-1-ol	9-12	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335, H336	
Index: 603-002-00-5 CAS: 64-17-5 EC: 200-578-6 Registration number: 01-2119457610-43	ethanol	8-11	Flam. Liq. 2, H225 Eye Irrit. 2, H319	
Index: 650-015-00-7 CAS: 8050-09-7 EC: 232-475-7 Registration number: 01-2119480418-32-xxxx	rosin	≤0,13	Skin Sens. 1, H317	

Notes

- Note T: This substance may be marketed in a form which does not have the physical hazards as indicated by the classification in the entry in Part 3. If the results of the relevant method or methods in accordance with Part 2 of Annex I of this Regulation show that the specific form of substance marketed does not exhibit this physical property or these physical hazards, the substance shall be classified in accordance with the result or results of this test or these tests. Relevant information, including reference to the relevant test method(s) shall be included in the safety data sheet.
- A substance for which exposure limits are set.

Full text of all classifications and hazard statements is given in the section 16.

C1037 nitrocellulose glossy varnish on the furniture CELOLESK

Creation date	19th October 2016	Version	3.0
Revision date	09th February 2024		

SECTION 4: First aid measures

4.1. Description of first aid measures

Take care of your own safety. If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet. If unconscious, put the person in the stabilized (recovery) position on his side with his head slightly bent backwards and make sure that airways are free; never induce vomiting. If the person vomits by himself, make sure that the vomit is not inhaled. In life threatening conditions first of all provide resuscitation of the affected person and ensure medical assistance. Respiratory arrest - provide artificial respiration immediately. Cardiac arrest - provide indirect cardiac massage immediately.

If inhaled

Terminate the exposure immediately; move the affected person to fresh air. Protect the person against growing cold. Provide medical treatment if irritation, dyspnoea or other symptoms persist.

If on skin

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible. Soap, soap solution or shampoo should be used if there is no skin injury. Provide medical treatment if skin irritation persists. Rinse skin with water or shower.

If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. No neutralization should be performed in any case! Rinsing should be continued for 10-30 minutes from the inner to the outer eye corner to make sure that the other eye is not involved. Depending on the situation, call medical rescue service or ensure medical treatment as promptly as possible. Everyone must be referred for treatment even if affected only a little.

If swallowed

Rinse out the mouth with water and provide 2-5 dL of water. Provide medical treatment if the person has any health problems.

4.2. Most important symptoms and effects, both acute and delayed

If inhaled

Inhaling vapours can cause corrosion of the breathing system. May cause respiratory irritation. May cause drowsiness or dizziness.

If on skin

Causes skin irritation.

If in eyes

Causes serious eye damage.

If swallowed

Corrosion of the digestion system can occur.

4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

Unsuitable extinguishing media

Water - full jet.

5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

5.3. Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Closed containers with the product near the fire should be cooled with water. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide sufficient ventilation. Highly flammable liquid and vapour. Remove all ignition sources. Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Do not inhale mist/vapours/spray. Prevent contact with skin and eyes.

C1037 nitrocellulose glossy varnish on the furniture CELOLESK

Creation date 19th October 2016
Revision date 09th February 2024 Version 3.0

6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water.

6.3. Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.

6.4. Reference to other sections

See the Section 7, 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Prevent formation of gases and vapours in flammable or explosive concentrations and concentrations exceeding the occupational exposure limits. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. Use non-sparking tools. Use of antistatic clothes and footwear is recommended. Do not inhale mist/vapours/spray. Prevent contact with skin and eyes. No smoking. Wash hands and exposed parts of the body thoroughly after handling. Use only outdoors or in a well-ventilated area. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Take action to prevent static discharges. Avoid release to the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Do not expose to sunlight. Store locked up. Keep container tightly closed. Keep cool.

Content	Packaging type	Material of package
0,35 l	can / tin	FE
0,75 kg	can / tin	FE
3,5 l	can / tin	FE
9 l	bucket	FE

Storage class 8A - Combustible corrosive substances

Storage temperature +5 to +25 °C

The specific requirements or rules relating to the substance/mixture

Solvent vapours are heavier than air and accumulate especially near the floor where they may form an explosive mixture with the air.

7.3. Specific end use(s)

not available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

The mixture contains substances for which occupational exposure limits are set.

European Union

Commission Directive (EU) 2019/1831

Substance name (component)	Type	Value
n-butyl acetate (CAS: 123-86-4)	OEL 8 hours	241 mg/m ³
	OEL 8 hours	50 ppm
	OEL 15 minutes	723 mg/m ³
	OEL 15 minutes	150 ppm

European Union

Commission Directive 91/322/EEC

Substance name (component)	Type	Value
Technical xylene (mixed with ethylbenzene)	OEL 8 hours	442 mg/m ³
	OEL 8 hours	100 ppm
	OEL 15 minutes	884 mg/m ³
	OEL 15 minutes	200 ppm

 Responsible Care® OUR COMMITMENT TO SUSTAINABILITY	SAFETY DATA SHEET according to Regulation (EC) No 1907/2006 (REACH) as amended	 COLORLAK barvy, které vydrží
C1037 nitrocellulose glossy varnish on the furniture CELOLESK		
Creation date	19th October 2016	
Revision date	09th February 2024	Version 3.0

European Union

Commission Directive 91/322/EEC

Substance name (component)	Type	Value
Technical xylene (mixed with ethylbenzene)	OEL 8 hours	221 mg/m ³
	OEL 8 hours	50 ppm
	OEL 15 minutes	442 mg/m ³
	OEL 15 minutes	100 ppm

DNEL

2-methylpropan-1-ol					
Workers / consumers	Route of exposure	Value	Effect	Value determination	Source
Workers	Inhalation	310 mg/m ³	Chronic effects local		BL dodavatele
Consumers	Inhalation	55 mg/m ³	Chronic effects local		BL dodavatele

ethanol					
Workers / consumers	Route of exposure	Value	Effect	Value determination	Source
Workers	Inhalation	950 mg/m ³	Chronic effects systemic		BL dodavatele
Workers	Dermal	343 mg/kg bw/day	Chronic effects systemic		BL dodavatele
Consumers	Inhalation	114 mg/m ³	Chronic effects systemic		echa
Consumers	Dermal	206 mg/kg bw/day	Chronic effects systemic		echa
Consumers	Oral	87 mg/kg bw/day	Chronic effects systemic		echa

n-butyl acetate					
Workers / consumers	Route of exposure	Value	Effect	Value determination	Source
Workers	Inhalation	600 mg/m ³	Acute effects local		BL dodavatele
Consumers	Inhalation	300 mg/m ³	Acute effects local		BL dodavatele
Workers	Inhalation	300 mg/m ³	Chronic effects local		BL dodavatele
Consumers	Inhalation	35.7 mg/m ³	Chronic effects local		BL dodavatele
Workers	Dermal	11 mg/kg	Chronic effects systemic		BL dodavatele
Workers	Dermal	11 mg/kg	Acute effects systemic		BL dodavatele
Consumers	Dermal	6 mg/kg	Chronic effects systemic		BL dodavatele
Consumers	Dermal	6 mg/kg	Acute effects systemic		BL dodavatele
Consumers	Oral	2 mg/kg	Chronic effects systemic		BL dodavatele
Consumers	Oral	2 mg/kg	Acute effects systemic		BL dodavatele

rosin					
Workers / consumers	Route of exposure	Value	Effect	Value determination	Source
Workers	Dermal	2.131 mg/kg bw/day	Chronic effects systemic		ECHA
Consumers	Dermal	1.065 mg/kg bw/day	Chronic effects systemic		ECHA
Consumers	Oral	1.065 mg/kg bw/day	Chronic effects systemic		ECHA

 Responsible Care® OUR COMMITMENT TO SUSTAINABILITY	SAFETY DATA SHEET according to Regulation (EC) No 1907/2006 (REACH) as amended	 barvy, které vydrží
C1037 nitrocellulose glossy varnish on the furniture CELOLESK		
Creation date	19th October 2016	
Revision date	09th February 2024	Version 3.0

Technical xylene (mixed with ethylbenzene)					
Workers / consumers	Route of exposure	Value	Effect	Value determination	Source
Workers	Inhalation	221 mg/m ³	Chronic effects systemic		BL dodavatele
Workers	Inhalation	442 mg/m ³	Acute effects systemic		BL dodavatele
Workers	Dermal	212 mg/kg bw/day	Chronic effects systemic		BL dodavatele
Consumers	Inhalation	65.3 mg/m ³	Chronic effects local		BL dodavatele
Consumers	Dermal	125 mg/kg bw/day	Chronic effects systemic		BL dodavatele
Consumers	Oral	12.5 mg/kg bw/day	Chronic effects systemic		BL dodavatele
Workers	Inhalation	221 mg/m ³	Chronic effects local		BL dodavatele
Workers	Inhalation	442 mg/m ³	Acute effects local		BL dodavatele
Consumers	Inhalation	260 mg/m ³	Acute effects systemic		BL dodavatele
Consumers	Inhalation	260 mg/m ³	Acute effects local		BL dodavatele

PNEC

2-methylpropan-1-ol			
Route of exposure	Value	Value determination	Source
Freshwater environment	0.4 mg/l		BL dodavatele
Marine water	0.04 mg/l		BL dodavatele
Water (intermittent release)	11 mg/l		BL dodavatele
Microorganisms in sewage treatment	10 mg/l		BL dodavatele
Freshwater sediment	1.52 mg/kg of dry substance of sediment		BL dodavatele
Sea sediments	0.152 mg/kg of dry substance of sediment		BL dodavatele
Soil (agricultural)	0.0699 mg/kg of dry substance of soil		BL dodavatele

ethanol			
Route of exposure	Value	Value determination	Source
Freshwater environment	0.96 mg/l		BL dodavatele
Marine water	0.79 mg/l		BL dodavatele
Water (intermittent release)	2.75 mg/l		echa
Microorganisms in sewage treatment	580 mg/l		BL dodavatele
Freshwater sediment	3.6 mg/kg of dry substance of sediment		echa
Sea sediments	2.9 mg/kg of dry substance of sediment		echa
Soil (agricultural)	0.63 mg/kg		BL dodavatele
Food chain	380-720 mg/kg of food		echa

 Responsible Care® OUR COMMITMENT TO SUSTAINABILITY	SAFETY DATA SHEET according to Regulation (EC) No 1907/2006 (REACH) as amended		 COLORLAK barvy, které vydrží
C1037 nitrocellulose glossy varnish on the furniture CELOLESK			
Creation date Revision date	19th October 2016 09th February 2024	Version	3.0

n-butyl acetate			
Route of exposure	Value	Value determination	Source
Freshwater environment	0.18 mg/l		BL dodavatele
Marine water	0.018 mg/l		BL dodavatele
Water (intermittent release)	0.36 mg/l		BL dodavatele
Microorganisms in sewage treatment	35.6 mg/l		BL dodavatele
Freshwater sediment	0.981 mg/kg		BL dodavatele
Sea sediments	0.0981 mg/kg		BL dodavatele
Soil (agricultural)	0.0903 mg/kg		BL dodavatele

Technical xylene (mixed with ethylbenzene)			
Route of exposure	Value	Value determination	Source
Freshwater environment	0.327 mg/l		BL dodavatele
Marine water	0.327 mg/l		BL dodavatele
Soil (agricultural)	2.31 mg/kg of dry substance of soil		BL dodavatele
Food chain	0.327 mg/l		BL dodavatele
Microorganisms in sewage treatment	6.58 mg/l		BL dodavatele
Sea sediments	12.46 mg/kg of dry substance of sediment		BL dodavatele
Freshwater sediment	12.46 mg/kg of dry substance of sediment		BL dodavatele

8.2. Exposure controls

Take off contaminated clothing and wash before reuse. Follow the usual measures intended for health protection at work and especially for good ventilation. This can be achieved only by local suction or efficient general ventilation. If exposure limits cannot be observed in this mode, suitable protection of airways must be used. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

Eye/face protection

Protective goggles or face shield (based on the nature of the work performed).

Skin protection

Hand protection: Protective gloves resistant to the product (EN 374). Gloves material: Nitrile rubber (EN 374). Penetration time of glove material: ≥ 480 minutes (EN 374). When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. Observe other recommendations of the manufacturer. Other protection: protective workwear. Contaminated skin should be washed thoroughly.

Respiratory protection

Halfmask with a filter against organic vapours or a self-contained breathing apparatus as appropriate if exposure limit values of substances are exceeded or in a poorly ventilated environment.

Thermal hazard

Not available.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	liquid
Colour	colourless, Gardner scale 1-6 (manufacturer's methodology B5/TD1-1 (PND 67 3011))

C1037 nitrocellulose glossy varnish on the furniture CELOLESK

Creation date	19th October 2016	Version	3.0
Revision date	09th February 2024		

Odour	after organic solvents
Melting point/freezing point	data not available
2-methylpropan-1-ol (CAS: 78-83-1)	<-90 °C (BL dodavatele)
ethanol (CAS: 64-17-5)	-114.15 °C (BL dodavatele)
n-butyl acetate (CAS: 123-86-4)	-78 °C (BL dodavatele)
Technical xylene (mixed with ethylbenzene)	-94.96-13.2 °C (BL dodavatele)
Boiling point or initial boiling point and boiling range	data not available
2-methylpropan-1-ol (CAS: 78-83-1)	108 °C (BL dodavatele)
ethanol (CAS: 64-17-5)	78.3 °C (BL dodavatele)
n-butyl acetate (CAS: 123-86-4)	124-126.5 °C (BL dodavatele)
Technical xylene (mixed with ethylbenzene)	136.2-144.5 °C (BL dodavatele)
Flammability	Flammable liquid of risk class I (ČSN 65 0201)
ethanol (CAS: 64-17-5)	inflammable (BL dodavatele)
n-butyl acetate (CAS: 123-86-4)	inflammable (odvozeno od bodu vzplanutí)
Nitrocellulose, nitrogen content ≤ 12,6% (CAS: 9004-70-0)	Vysoce hořlavý (BL dodavatele)
Technical xylene (mixed with ethylbenzene)	inflammable (BL dodavatele)
Lower and upper explosion limit	
bottom	0.8 % (for Technical xylene (mixed with ethylbenzene))
2-methylpropan-1-ol (CAS: 78-83-1)	1.7 % (BL dodavatele)
ethanol (CAS: 64-17-5)	3.3 % (BL dodavatele)
n-butyl acetate (CAS: 123-86-4)	1.2 % (literatura)
Technical xylene (mixed with ethylbenzene)	0.8 % (BL dodavatele)
upper	19 % (for Ethanol)
2-methylpropan-1-ol (CAS: 78-83-1)	10.9 % (BL dodavatele)
ethanol (CAS: 64-17-5)	19 % (BL dodavatele)
n-butyl acetate (CAS: 123-86-4)	7.6 % (literatura)
Technical xylene (mixed with ethylbenzene)	7 % (BL dodavatele)
Flash point	9 °C (PND 67 3015)
2-methylpropan-1-ol (CAS: 78-83-1)	31 °C (BL dodavatele)
ethanol (CAS: 64-17-5)	12.85 °C (BL dodavatele)
n-butyl acetate (CAS: 123-86-4)	27 °C (BL dodavatele)
Nitrocellulose, nitrogen content ≤ 12,6% (CAS: 9004-70-0)	12 °C (BL dodavatele)
Technical xylene (mixed with ethylbenzene)	18-32 °C (BL dodavatele)
Auto-ignition temperature	data not available
2-methylpropan-1-ol (CAS: 78-83-1)	400 °C (BL dodavatele)
ethanol (CAS: 64-17-5)	362.85 °C (BL dodavatele)
n-butyl acetate (CAS: 123-86-4)	415 °C (BL dodavatele)
Nitrocellulose, nitrogen content ≤ 12,6% (CAS: 9004-70-0)	>180 °C (BL dodavatele)
Technical xylene (mixed with ethylbenzene)	432-528 °C (BL dodavatele)
Decomposition temperature	data not available
pH	non-soluble (in water)
2-methylpropan-1-ol (CAS: 78-83-1)	7 (undiluted at 20 °C) (BL dodavatele)
ethanol (CAS: 64-17-5)	7 (undiluted at 20 °C) (BL dodavatele)
Kinematic viscosity	>20.5 mm²/s at 40 °C
Kinematic viscosity	data not available
n-butyl acetate (CAS: 123-86-4)	0.83 mm²/s at 20 °C (BL dodavatele)
Solubility in water	not miscible
2-methylpropan-1-ol (CAS: 78-83-1)	70 g/l (20 °C) (BL dodavatele)
ethanol (CAS: 64-17-5)	789 000 mg/l při 20°C (BL dodavatele)
n-butyl acetate (CAS: 123-86-4)	5.3 g/l při 20 °C (pH 6) (BL dodavatele)
Nitrocellulose, nitrogen content ≤ 12,6% (CAS: 9004-70-0)	insoluble (BL dodavatele)
Technical xylene (mixed with ethylbenzene)	146-190.7 mg/l při 25 °C (BL dodavatele)

C1037 nitrocellulose glossy varnish on the furniture CELOLESK

Creation date	19th October 2016	Version	3.0
Revision date	09th February 2024		

Partition coefficient n-octanol/water (log value)	LogPow -0.35 to 3.2 (for the substances contained)
2-methylpropan-1-ol (CAS: 78-83-1)	1 (BL dodavatele)
n-butyl acetate (CAS: 123-86-4)	2.3 (BL dodavatele)
Vapour pressure	6.5 hPa to 93 hPa at 20 °C (for the substances contained)
2-methylpropan-1-ol (CAS: 78-83-1)	16 hPa at 20 °C (BL dodavatele)
ethanol (CAS: 64-17-5)	57.26 hPa at 19.65 °C (BL dodavatele)
n-butyl acetate (CAS: 123-86-4)	11.6 hPa at 20 °C (BL dodavatele)
Nitrocellulose, nitrogen content ≤ 12,6% (CAS: 9004-70-0)	5810 Pa (BL dodavatele)
Technical xylene (mixed with ethylbenzene)	650-944 Pa (BL dodavatele)
Density and/or relative density	
Density	0.95 g/cm³ at 23 °C (DIN 53217/3)
2-methylpropan-1-ol (CAS: 78-83-1)	0.8017 g/cm³ at 20 °C (BL dodavatele)
ethanol (CAS: 64-17-5)	0.7844 g/cm³ at 25 °C (BL dodavatele)
n-butyl acetate (CAS: 123-86-4)	0.8812 g/cm³ at 20 °C (BL dodavatele)
Technical xylene (mixed with ethylbenzene)	0.862-0.88 g/cm³ at 25 °C (BL dodavatele)
Relative vapour density	data not available
Particle characteristics	data not available
Form	liquid
VOC content in product: category and subcategory of products - not classified	

9.2. Other information

Appearance	medium liquid without extraneous, mechanical impurities (manufacturer's methodology B5/TD1-17 (ČSN EN ISO 1513))
Combustion temperature	19 °C (PND 65 6212)
Ignition temperature	325 °C (PND 33 0371)
Content of organic solvents (VOC)	0.707 kg/kg (calculation)
Total organic carbon (TOC)	0.511 kg/kg (calculation)
Solid content (dry matter)	≥25 % volume (calculation)
Max. VOC content in the product in its ready to use condition	664 g/l (calculation)
Flammability - temperature class: T2 (PND 33 0371); Calorific value: 28,87 MJ/kg (PND 65 6169); Heat of combustion: 31,07 MJ/kg (PND 65 6169).	

SECTION 10: Stability and reactivity

10.1. Reactivity

not available

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Unknown.

10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost.

10.5. Incompatible materials

Protect against strong acids, bases and oxidizing agents.

10.6. Hazardous decomposition products

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Inhalation of solvent vapors above values exceeding exposure limits for working environment may result in acute inhalation poisoning, depending on the level of concentration and exposure time. No toxicological data is available for the mixture.

 Responsible Care® OUR COMMITMENT TO SUSTAINABILITY	SAFETY DATA SHEET according to Regulation (EC) No 1907/2006 (REACH) as amended			 COLORLAK barvy, které vydrží
C1037 nitrocellulose glossy varnish on the furniture CELOLESK				
Creation date	19th October 2016	Version	3.0	
Revision date	09th February 2024			

Acute toxicity

Based on the available data, the criteria for classification of the mixture are not met.

C1037 nitrocellulose glossy varnish on the furniture CELOLESK								
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination	Source
Dermal	ATE		5946 mg/kg				Calculation of value	
Inhalation (vapor)	ATE		59.46 mg/l				Calculation of value	

2-methylpropan-1-ol								
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination	Source
Oral	LD ₅₀	OECD 401	>2000 mg/kg		Rat (Rattus norvegicus)			BL dodavatele
Inhalation (vapor)	LC ₅₀		>18.18 mg/l of air	14 days	Rat (Rattus norvegicus)			BL dodavatele
Dermal	LD ₅₀	OECD 402	>2000 mg/kg		Rabbit			BL dodavatele

ethanol								
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination	Source
Oral	LD ₅₀		7060 mg/kg		Rat			BL dodavatele
Inhalation	LC ₅₀		117000-125000 mg/m ³	4 hours	Rat (Rattus norvegicus)			BL dodavatele
Dermal	LD ₅₀		>20000 mg/kg		Rabbit			BL dodavatele

n-butyl acetate								
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination	Source
Oral	LD ₅₀		10736 mg/kg		Rat (Rattus norvegicus)			BL dodavatele
Inhalation	LC ₅₀	OECD 403	>21.1 mg/l	4 hours	Rat (Rattus norvegicus)			BL dodavatele
Dermal	LD ₅₀		>14000 mg/kg		Rabbit			BL dodavatele
Inhalation	LC ₀		>38.32 mg/l	6 hours	Rat (Rattus norvegicus)			BL dodavatele

 Responsible Care® OUR COMMITMENT TO SUSTAINABILITY	SAFETY DATA SHEET according to Regulation (EC) No 1907/2006 (REACH) as amended			 COLORLAK barvy, které vydrží
C1037 nitrocellulose glossy varnish on the furniture CELOLESK				
Creation date	19th October 2016			
Revision date	09th February 2024	Version	3.0	

Nitrocellulose, nitrogen content ≤ 12,6%								
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination	Source
Oral	LD ₅₀		>2000 mg/kg		Rat (Rattus norvegicus)			BL dodavatele

rosin								
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination	Source
Oral	LD ₅₀		1000 mg/kg bw		Rat			ECHA
Dermal	LD ₅₀		2000 mg/kg bw		Rat			ECHA

Technical xylene (mixed with ethylbenzene)								
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination	Source
Oral	LD ₅₀		3523 mg/kg bw		Rat			ECHA
Inhalation (vapor)	LD ₅₀		6350 ppm	4 hours	Rat			ECHA
Dermal	LD ₅₀		12126 mg/kg bw		Rabbit			ECHA
Oral	NOAEL		150 mg/kg bw		Rat			ECHA
Oral	LOAEL		150 mg/kg bw		Rat			ECHA
Dermal	ATE		1100 mg/kg bw					
Inhalation (vapor)	ATE		11 mg/l					

Skin corrosion/irritation

Causes skin irritation.

2-methylpropan-1-ol					
Route of exposure	Result	Method	Exposure time	Species	Source
	Irritating	OECD 404		Rabbit	BL dodavatele

Serious eye damage/irritation

Causes serious eye damage.

2-methylpropan-1-ol					
Route of exposure	Result	Method	Exposure time	Species	Source
Eye	Serious eye damage	OECD 405		Rabbit	BL dodavatele

Respiratory or skin sensitisation

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Germ cell mutagenicity

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

 Responsible Care® OUR COMMITMENT TO SUSTAINABILITY	SAFETY DATA SHEET according to Regulation (EC) No 1907/2006 (REACH) as amended			 COLORLAK barvy, které vydrží
C1037 nitrocellulose glossy varnish on the furniture CELOLESK				
Creation date	19th October 2016			
Revision date	09th February 2024	Version	3.0	

Carcinogenicity

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Reproductive toxicity

Data for the mixture are not available. Based on the available data, the criteria for classification of the mixture are not met.

2-methylpropan-1-ol							
Effect	Parameter	Method	Value	Result	Species	Sex	Source
Effects on fertility	NOAEL		7.5 mg/l	Negative	Rat (Rattus norvegicus)		BL dodavatele
Developmental toxicity	NOAEL	OECD 414	10 mg/l	Negative	Rat (Rattus norvegicus)		BL dodavatele

Toxicity for specific target organ - single exposure

May cause drowsiness or dizziness. May cause respiratory irritation. Data for the components of the mixture are not available.

Toxicity for specific target organ - repeated exposure

May cause damage to the central nervous system through prolonged or repeated exposure.

Repeated dose toxicity

2-methylpropan-1-ol								
Route of exposure	Parameter	Result	Method	Value	Exposure time	Species	Sex	Source
Drinking water	NOAEL	Negative	OECD 408	1450 mg/kg	90 days	Rat (Rattus norvegicus)		BL dodavatele

ethanol								
Route of exposure	Parameter	Result	Method	Value	Exposure time	Species	Sex	Source
Oral	NOAEL			9700 mg/kg bw/day		Mouse		echa
Inhalation	NOAEC			6.66 mg/l of air		Rat		echa

rosin								
Route of exposure	Parameter	Result	Method	Value	Exposure time	Species	Sex	Source
Oral	NOAEL			3000 ppm		Rat		ECHA

Aspiration hazard

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

11.2. Information on other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects.

 Responsible Care® OUR COMMITMENT TO SUSTAINABILITY	SAFETY DATA SHEET according to Regulation (EC) No 1907/2006 (REACH) as amended			 COLORLAK barvy, které vydrží
C1037 nitrocellulose glossy varnish on the furniture CELOLESK				
Creation date	19th October 2016	Version	3.0	
Revision date	09th February 2024			

Acute toxicity

2-methylpropan-1-ol						
Parameter	Method	Value	Exposure time	Species	Environment	Source
LC ₅₀		>100 mg/l	96 hours	Fish (Pimephales promelas)		BL dodavatel e
EC ₅₀		>100 mg/l	48 hours	Daphnia (Daphnia pulex)		BL dodavatel e
EC ₅₀	OECD 201	>100 mg/l	72 hours	Algae (Pseudokirchneriella subcapitata)		BL dodavatel e
EC ₁₀	OECD 209	>100 mg/l	16 hours	Bacteria (Pseudomonas putida)		BL dodavatel e

ethanol						
Parameter	Method	Value	Exposure time	Species	Environment	Source
LC ₅₀		>8140 mg/l	96 hours	Fish (Oncorhynchus mykiss)		BL dodavatel e
EC ₅₀		9268-14221 mg/l	48 hours	Crustaceans		BL dodavatel e
EC ₅₀		675-22000 mg/l	96 hours	Algae and other aquatic plants		echa
EC ₅₀		5.8 g/l	4 hours	Microorganisms (Photobacterium phosphoreum)		echa

n-butyl acetate						
Parameter	Method	Value	Exposure time	Species	Environment	Source
LC ₅₀		18 mg/l	96 hours	Fish (Pimephales promelas)		BL dodavatel e
EC ₅₀		44 mg/l	48 hours	Aquatic invertebrates (Daphnia sp.)		BL dodavatel e
EC ₅₀		397 mg/l	72 hours	Algae and other aquatic plants (Pseudokirchneriella subcapitata)		BL dodavatel e
EC ₅₀		356 mg/l	40 hours	Microorganisms (Tetrahymena pyriformis)		BL dodavatel e
EC ₅₀	OECD 208	>1000 mg/kg	14 days	Algae (Selenastrum capricornutum)		BL dodavatel e

Nitrocellulose, nitrogen content ≤ 12,6%						
Parameter	Method	Value	Exposure time	Species	Environment	Source
LC ₅₀	OECD 203	>5000 mg/l	96 hours	Fish (Brochydemicterio)		BL dodavatel e

 Responsible Care® OUR COMMITMENT TO SUSTAINABILITY	SAFETY DATA SHEET		 COLORLAK barvy, které vydrží
according to Regulation (EC) No 1907/2006 (REACH) as amended			
C1037 nitrocellulose glossy varnish on the furniture CELOLESK			
Creation date	19th October 2016	Version	3.0
Revision date	09th February 2024		

Nitrocellulose, nitrogen content ≤ 12,6%						
Parameter	Method	Value	Exposure time	Species	Environment	Source
NOEC	OECD 202	100000 mg/l	48 hours	Daphnia (Daphnia magna)		BL dodavatel e
ErC ₅₀	OECD 201	>90000 mg/l	72 hours	Algae (Selenastrum capricornutum)		BL dodavatel e
EC ₅₀	OECD 209	>10000 mg/l	3 hours	Bacteria (Salmonella typhimurium)		BL dodavatel e

rosin						
Parameter	Method	Value	Exposure time	Species	Environment	Source
LC ₅₀		1.7 mg/l	96 hours	Fish (Oncorhynchus mykiss)		ECHA
LC ₅₀		1.6 mg/l	48 hours	Aquatic invertebrates		ECHA
EC ₅₀		16.6 mg/l	72 hours	Algae and other aquatic plants		ECHA
EC ₅₀		10 g/l	3 hours	Microorganisms (Photobacterium phosphoreum)		ECHA

Technical xylene (mixed with ethylbenzene)						
Parameter	Method	Value	Exposure time	Species	Environment	Source
EC ₅₀		96 mg/l	24 hours	Microorganisms (Photobacterium phosphoreum)		ECHA
EC ₅₀		2.2 mg/l	73 hours	Algae (Selenastrum capricornutum)		ECHA
IC ₅₀		1 mg/l	24 hours	Aquatic invertebrates		ECHA
LC ₅₀		2.6 mg/l	4 days	Fish (Oncorhynchus mykiss)		ECHA

Chronic toxicity

2-methylpropan-1-ol						
Parameter	Method	Value	Exposure time	Species	Environment	Source
NOEC		20 mg/l	21 days	Daphnia (Daphnia magna)		BL dodavatel e

n-butyl acetate						
Parameter	Method	Value	Exposure time	Species	Environment	Source
NOEC	OECD 211	23 mg/l	21 days	Daphnia (Daphnia magna)		BL dodavatel e

		SAFETY DATA SHEET according to Regulation (EC) No 1907/2006 (REACH) as amended			
C1037 nitrocellulose glossy varnish on the furniture CELOLESK					
Creation date		19th October 2016		Version	
Revision date		09th February 2024		3.0	

Technical xylene (mixed with ethylbenzene)						
Parameter	Method	Value	Exposure time	Species	Environment	Source
NOEC		960 µg/l		Aquatic invertebrates		ECHA
NOEC		1.3 mg/l	56 days	Fish (Oncorhynchus mykiss)		ECHA

12.2. Persistence and degradability
 Data for the mixture are not available.
Biodegradability

2-methylpropan-1-ol						
Parameter	Method	Value	Exposure time	Environment	Result	Source
	OECD 301D	>70 %	28 days		Easily biodegradable	BL dodavatel e

ethanol						
Parameter	Method	Value	Exposure time	Environment	Result	Source
		94 %				BL dodavatel e
CHSK		2.08 mg/kg				BL dodavatel e
BSK ₅		1.46 mg/kg				BL dodavatel e

Nitrocellulose, nitrogen content ≤ 12,6%						
Parameter	Method	Value	Exposure time	Environment	Result	Source
	OECD 301B	>60 %	28 days			BL dodavatel e

12.3. Bioaccumulative potential
 Data for the mixture are not available.

2-methylpropan-1-ol						
Parameter	Value	Exposure time	Species	Environment	Temperature [°C]	Source
Log Pow	1				25°C	BL dodavatele

12.4. Mobility in soil
 Data for the mixture are not available.

2-methylpropan-1-ol						
Parameter	Value	Environment	Temperature	Result	Source	
Koc	2.1			High	BL dodavatele	

12.5. Results of PBT and vPvB assessment

C1037 nitrocellulose glossy varnish on the furniture CELOLESK

Creation date	19th October 2016	Version	3.0
Revision date	09th February 2024		

Product does not contain any substance meeting the criteria for PBT or vPvB in accordance with the Annex XIII of Regulation (EC) No 1907/2006 (REACH) as amended.

12.6. Endocrine disrupting properties

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

12.7. Other adverse effects

Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Proceed in accordance with valid regulations on waste disposal. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Empty containers may be used at waste incinerators to produce energy or deposited in a dump with appropriate classification. Perfectly cleaned containers can be submitted for recycling.

Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

Waste type code

08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

Packaging waste type code

15 01 10* packaging containing residues of or contaminated by hazardous substances

(*) - Hazardous waste according to Directive 2008/98/EC on hazardous waste

SECTION 14: Transport information

14.1. UN number or ID number

UN 1263

14.2. UN proper shipping name

PAINT

14.3. Transport hazard class(es)

3 Flammable liquids

14.4. Packing group

II

14.5. Environmental hazards

No.

14.6. Special precautions for user

Reference in the Sections 4 to 8.

14.7. Maritime transport in bulk according to IMO instruments

not relevant


Additional information

Hazard identification No.

UN number

Classification code

Safety signs



F1

3



C1037 nitrocellulose glossy varnish on the furniture CELOLESK

Creation date	19th October 2016	Version	3.0
Revision date	09th February 2024		

Road transport - ADR

Special provisions	163, 367, 640D, 650
Limited quantities	5 L
Excepted quantities	E2

Packaging

Packing instructions	P001, IBC02, R001
Special packing provisions	PP1
Mixed packing provisions	MP19

Portable tanks and bulk containers

Guidelines	T4
Special provisions	TP1, TP8, TP28

ADR tank

Tank code	LGBF
Vehicles for tank carriage	FL
Transport category	2
Tunnel restriction code	(D/E)

Special provision for

operation	S2, S20
-----------	---------

Railway transport - RID

Special provisions	163, 367, 640D, 650
Excepted quantities	E2

Packaging

Packing instructions	P001, IBC02, R001
Special packing provisions	PP1
Mixed packing provisions	MP19

Portable tanks and bulk containers

Guidelines	T4
Special provisions	TP1, TP8, TP28

RID Tanks

Tank code	LGBF
Transport category	0

Air transport - ICAO/IATA

Packaging instructions for limited amount	Y344
Packaging instructions passenger	355
Cargo packaging instructions	366

Marine transport - IMDG

EmS (emergency plan)	F-E, S-E
MFAG	310

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

15.2. Chemical safety assessment

not available

SECTION 16: Other information

C1037 nitrocellulose glossy varnish on the furniture CELOLESK

Creation date	19th October 2016	Version	3.0
Revision date	09th February 2024		

A list of standard risk phrases used in the safety data sheet

H207	Fire or projection hazard; increased risk of explosion if desensitising agent is reduced.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H373	May cause damage to the central nervous system through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
H312+H332	Harmful in contact with skin or if inhaled.

Guidelines for safe handling used in the safety data sheet

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water and soap.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P314	Get medical advice/attention if you feel unwell.
P370+P378	In case of fire: Use foam (alcohol resistant), carbon dioxide, a spray mist, powder to extinguish.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to by handing over to a person authorized to dispose of waste or a site designated by the town.

A list of additional standard phrases used in the safety data sheet

EUH208	Contains rosin. May produce an allergic reaction.
EUH066	Repeated exposure may cause skin dryness or cracking.

Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

Key to abbreviations and acronyms used in the safety data sheet

ADR	European agreement concerning the international carriage of dangerous goods by road
BCF	Bioconcentration Factor
BOD	Biochemical oxygen demand
CAS	Chemical Abstracts Service
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures
COD	Chemical oxygen demand
EC	Identification code for each substance listed in EINECS
EC ₁₀	Concentration of a substance when it is affected 10% of the population
EC ₅₀	Concentration of a substance when it is affected 50% of the population
EINECS	European Inventory of Existing Commercial Chemical Substances
EmS	Emergency plan

C1037 nitrocellulose glossy varnish on the furniture CELOLESK

Creation date	19th October 2016	Version	3.0
Revision date	09th February 2024		

EU	European Union
EuPCS	European Product Categorisation System
IATA	International Air Transport Association
IBC	International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals
IC ₅₀	Concentration causing 50% blockade
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
INCI	International Nomenclature of Cosmetic Ingredients
ISO	International Organization for Standardization
IUPAC	International Union of Pure and Applied Chemistry
LC ₀	Lethal concentration of a substance in which it can be expected death of 0% of the population
LC ₅₀	Lethal concentration of a substance in which it can be expected death of 50% of the population
LD ₅₀	Lethal dose of a substance in which it can be expected death of 50% of the population
LOAEL	Lowest observed adverse effect level
log K _{ow}	Octanol-water partition coefficient
NOAEC	No observed adverse effect concentration
NOAEL	No observed adverse effect level
NOEC	No observed effect concentration
OEL	Occupational Exposure Limits
PBT	Persistent, Bioaccumulative and Toxic
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Agreement on the transport of dangerous goods by rail
UN	Four-figure identification number of the substance or article taken from the UN Model Regulations
UVCB	Substances of unknown or variable composition, complex reaction products or biological materials
VOC	Volatile organic compounds
vPvB	Very Persistent and very Bioaccumulative
Acute Tox.	Acute toxicity
Aquatic Chronic	Hazardous to the aquatic environment (chronic)
Asp. Tox.	Aspiration hazard
Desen. Expl.	Desensitised explosives
Eye Dam.	Serious eye damage
Flam. Liq.	Flammable liquid
Skin Irrit.	Skin irritation
Skin Sens.	Skin sensitization
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

Recommended restrictions of use

not available

Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended.
REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

The changes (which information has been added, deleted or modified)

The version 3.0 replaces the SDS version from 26 March 2018. Changes were made in sections 1, 2, 3, 7, 8, 9, 11, 12, 13, 14, 15 and 16.

 Responsible Care® OUR COMMITMENT TO SUSTAINABILITY	SAFETY DATA SHEET according to Regulation (EC) No 1907/2006 (REACH) as amended	 COLORLAK barvy, které vydrží
C1037 nitrocellulose glossy varnish on the furniture CELOLESK		
Creation date	19th October 2016	
Revision date	09th February 2024	Version 3.0

More information

Classification procedure - calculation method.

Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.