

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



E0502 EKODUR ARCTIC interior paint/base

Creation date	03rd September 2018	Version	4.0
Revision date	20th May 2026		

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. Product identifier** E0502 EKODUR ARCTIC interior paint/base
Substance / mixture mixture
Number E0502:-A-C1000; A1E0100; B1D0000; B1T0000

1.2. Relevant identified uses of the substance or mixture and uses advised against

Mixture's intended use

EKODUR ARCTIC E0502 interior paint/base is intended as a base for tinting in TSCL DEKOR, and as a white paint for direct use, it is a dispersion interior paint with high resistance to dry abrasion, water-dilutable, vapor-permeable, quick-drying. It is used for interior coatings of masonry, lime, lime-cement and dispersion plasters, for repainting old coatings, mineral substrates, plasterboard, wood-fiber, chipboard and cement-bonded chipboard.

Main intended use

PC-PNT-2 Paints/coatings - Decorative

Mixture uses advised against

The product should not be used in ways other than those referred in Section 1.

Exposure scenario is attached to the Safety Data Sheet.

1.3. Details of the supplier of the safety data sheet

Manufacturer

Name or trade name	COLORLAK, a.s.
Address	Tovární 1076, Staré Město, 686 03 Czech Republic
Identification number (CRN)	49444964
VAT number	CZ49444964
Phone	+420 572527111
Email	colorlak@colorlak.cz
Web address	www.colorlak.cz

Competent person responsible for the safety data sheet

Name	Ing. Gabriela Kubíková
Email	kubikova@colorlak.cz

1.4. Emergency telephone number

European emergency number: 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification of the mixture in accordance with Regulation (EC) No 1272/2008

The mixture is not classified as dangerous according to Regulation (EC) No 1272/2008.

Most serious adverse physico-chemical effects

PROTECT FROM FROST!

2.2. Label elements

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P501	Dispose of contents/container to by handing over to a person authorized to dispose of waste or a site designated by the town.

Supplemental information

EUH208	Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.
EUH210	Safety data sheet available on request.
Density	1.47-1.65 g/cm ³ at 23 °C (manufacturer's methodology B5/TD1-5 (ČSN EN ISO 2811-1))
VOC	0,011 kg/kg
TOC	0,009 kg/kg
Dry matter	≥60 % weight
VOC limit value	cat. A (a) WB: 30 g/l
Max. VOC content in the product in its ready to use condition	17 g/l

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



E0502 EKODUR ARCTIC interior paint/base

Creation date 03rd September 2018 Version 4.0
Revision date 20th May 2026

2.3. Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended. Does not contain any PMT or vPvM components.

The titanium dioxide contained contains < 1% particles with an aerodynamic diameter $\leq 10 \mu\text{m}$ and therefore the criteria for classification and additional warnings are not met.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

The interior base is an aqueous dispersion of macromolecular substances with the addition of special additives, pigments and fillers.

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
CAS: 1317-65-3 EC: 215-279-6	limestone	45-55		
CAS: 13463-67-7 EC: 236-675-5 Registration number: 01-2119489379-17	titanium dioxide	≤ 6.5	not classified as dangerous	4
CAS: 14807-96-6 EC: 238-877-9	talc ($\text{Mg}_3\text{H}_2(\text{SiO}_3)_4$)	≤ 4	not classified as dangerous	
CAS: 9032-42-2	2-Hydroxyethyl methyl cellulose	0.1-1	not classified as dangerous	
Index: 603-027-00-1 CAS: 107-21-1 EC: 203-473-3 Registration number: 01-2119456816-28	ethanediol	≤ 0.02	Acute Tox. 4, H302 STOT RE 2, H373 (kidneys)	5
Index: 605-001-00-5 CAS: 50-00-0 EC: 200-001-8	formaldehyde ...%	≤ 0.005	Acute Tox. 4, H302 Skin Corr. 1B, H314 Skin Sens. 1A, H317 Acute Tox. 2, H330 Muta. 2, H341 Carc. 1B, H350 Specific concentration limit: Skin Corr. 1B, H314: $C \geq 25 \%$ Skin Irrit. 2, H315: $5 \% \leq C < 25 \%$ Eye Irrit. 2, H319: $5 \% \leq C < 25 \%$ STOT SE 3, H335: $C \geq 5 \%$ ATE Inhalation (gases) = 100 ppm ATE Oral = 500 mg/kg bw	1, 2, 3, 6

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



E0502 EKODUR ARCTIC interior paint/base

Creation date 03rd September 2018 Version 4.0
Revision date 20th May 2026

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Index: 613-167-00-5 CAS: 55965-84-9	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	≤0.0014	Acute Tox. 3, H301 Acute Tox. 2, H310+H330 Skin Corr. 1C, H314 Skin Sens. 1A, H317 Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100) EUH071 Specific concentration limit: Eye Irrit. 2, H319: 0.06 % ≤ C < 0.6 % Skin Sens. 1A, H317: C ≥ 0.0015 % Skin Irrit. 2, H315: 0.06 % ≤ C < 0.6 % Skin Corr. 1C, H314: C ≥ 0.6 % Eye Dam. 1, H318: C ≥ 0.6 % ATE Inhalation (dust/mist) = 0,31 mg/l	1
Index: 603-107-00-6 CAS: 111-77-3 EC: 203-906-6	2-(2-methoxyethoxy)ethanol	≤0.001	Repr. 1B, H360D Specific concentration limit: Repr. 1B, H360D: C ≥ 3 %	5, 6

Notes

- Note B: Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'. In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis.*
- Note D: Certain substances which are susceptible to spontaneous polymerisation or decomposition are generally placed on the market in a stabilised form. It is in this form that they are listed in Part 3 of Annex VI to Regulation (EC) No 1272/2008. However, such substances are sometimes placed on the market in a non-stabilised form. In this case, the supplier who places such a substance on the market must state on the label the name of the substance followed by the words "non-stabilised".*
- Note F: This substance may contain a stabiliser. If the stabiliser changes the hazardous properties of the substance, as indicated by the classification in Part 3, classification and labelling should be provided in accordance with the rules for classification and labelling of hazardous mixtures.*
- Note V: If the substance is to be placed on the market as fibres (with diameter < 3 µm, length > 5 µm and aspect ratio ≥ 3:1) or particles of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or additional routes of exposure (oral or dermal) should be applied.*
- A substance for which exposure limits are set.*
- The use of the substance is restricted by Annex XVII of REACH Regulation*

Full text of all classifications and hazard statements is given in the section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Take care of your own safety. If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet.

If inhaled

Terminate the exposure immediately; move the affected person to fresh air.

If on skin

Remove contaminated clothes.

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



E0502 EKODUR ARCTIC interior paint/base

Creation date	03rd September 2018	Version	4.0
Revision date	20th May 2026		

If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person.

If swallowed

Rinse out the mouth with clean water. In the event of issues, find medical help.

4.2. Most important symptoms and effects, both acute and delayed

If inhaled

Not expected.

If on skin

Not expected.

If in eyes

Not expected.

If swallowed

Not expected.

4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Accommodate extinguishing components to the location of fire.

Unsuitable extinguishing media

not available

5.2. Special hazards arising from the substance or mixture

It is not a flammable liquid.

5.3. Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with chemical resistant gloves. Use a self-contained breathing apparatus and full-body protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Follow the instructions in the Sections 7 and 8.

6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water.

6.3. Methods and material for containment and cleaning up

After removal of the product, wash the contaminated site with plenty of water.

6.4. Reference to other sections

See the Section 7, 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Prevent formation of gases and vapours in concentrations exceeding the occupational exposure limits. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose.

Content	Packaging type	Material of package
1 kg	bucket	PP
5 kg	bucket	PP
12 kg	bucket	PP
20 kg	bucket	PP

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



E0502 EKODUR ARCTIC interior paint/base

Creation date 03rd September 2018 Version 4.0
Revision date 20th May 2026

Storage class

12 - Non-combustible liquids that cannot be assigned to any of the above storage classes

Storage temperature

+5 až +25 °C

7.3. Specific end use(s)
not available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

The mixture contains substances for which occupational exposure limits are set.

European Union

Commission Directive 2000/39/EC

Substance name (component)	Type	Value
ethanediol (CAS: 107-21-1)	OEL 8 hours	52 mg/m ³
	OEL 8 hours	20 ppm
	OEL 15 minutes	104 mg/m ³
	OEL 15 minutes	40 ppm

Notes

Skin.

European Union

Commission Directive 2006/15/EC

Substance name (component)	Type	Value
2-(2-methoxyethoxy)ethanol (CAS: 111-77-3)	OEL 8 hours	50,1 mg/m ³
	OEL 8 hours	10 ppm

Notes

Skin.

DNEL

ethanediol				
Workers / consumers	Route of exposure	Value	Effect	Source
Workers	Inhalation	35 mg/m ³	Acute effects local	echa
Workers	Dermal	106 mg/kg bw/day	Chronic effects systemic	echa
Consumers	Inhalation	7 mg/m ³	Acute effects local	echa
Consumers	Dermal	53 mg/kg bw/day	Chronic effects systemic	echa

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Workers / consumers	Route of exposure	Value	Effect	Source
Workers	Inhalation	0.02 mg/m ³	Chronic effects local	BL dodavatele
Workers	Inhalation	0.04 mg/m ³	Acute effects local	BL dodavatele
Consumers	Inhalation	0.04 mg/m ³	Acute effects local	BL dodavatele
Consumers	Inhalation	0.02 mg/m ³	Chronic effects local	BL dodavatele
Consumers	Oral	0.09 mg/kg	Chronic effects systemic	BL dodavatele
Consumers	Oral	0.11 mg/kg	Acute effects systemic	BL dodavatele

titanium dioxide

Workers / consumers	Route of exposure	Value	Effect	Source
	Inhalation	10 mg/m ³	Chronic effects local	BL dodavatele

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



E0502 EKODUR ARCTIC interior paint/base

Creation date 03rd September 2018 Version 4.0
Revision date 20th May 2026

PNEC

ethanediol		
Route of exposure	Value	Source
Freshwater environment	10 mg/l	echa
Marine water	1 mg/l	echa
Water (intermittent release)	10 mg/l	echa
Microorganisms in sewage treatment	199.5 mg/l	echa
Freshwater sediment	37 mg/kg of dry substance of sediment	echa
Sea sediments	3.7 mg/kg of dry substance of sediment	echa
Soil (agricultural)	1.53 mg/kg of dry substance of soil	echa

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)		
Route of exposure	Value	Source
Freshwater environment	0.00339 mg/l	BL dodavatele
Marine water	0.00339 mg/l	BL dodavatele
Microorganisms in sewage treatment	0.23 mg/l	BL dodavatele
Freshwater sediment	0.027 mg/kg	BL dodavatele
Sea sediments	0.027 mg/kg	BL dodavatele
Soil (agricultural)	0.01 mg/kg	BL dodavatele

titanium dioxide		
Route of exposure	Value	Source
Freshwater environment	0.127 mg/l	BL dodavatele
Marine water	1 mg/l	BL dodavatele
Water (intermittent release)	0.61 mg/l	BL dodavatele
Freshwater sediment	1000 mg/kg	BL dodavatele
Sea sediments	100 mg/kg	BL dodavatele
Soil (agricultural)	100 mg/kg	BL dodavatele
Microorganisms in sewage treatment	100 mg/l	BL dodavatele
Food chain	1667 mg/kg	BL dodavatele

8.2. Exposure controls

Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

Eye/face protection

It is not needed.

Skin protection

For prolonged or repeated contact, wear protective gloves (EN 374).

Respiratory protection



Halfmask with a filter against organic vapours or a self-contained breathing apparatus as appropriate if exposure limit values of substances are exceeded or in a poorly ventilated environment.

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



E0502 EKODUR ARCTIC interior paint/base

Creation date	03rd September 2018	Version	4.0
Revision date	20th May 2026		

Thermal hazard

Not available.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2.

More information

Exposure scenario is attached to the Safety Data Sheet.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	liquid
Colour	white, transparent, semi-white, snow-white, according to shades
Odour	slight
Melting point/freezing point	data not available
2-(2-methoxyethoxy)ethanol (CAS: 111-77-3)	-84.15 °C (ECHA)
ethanediol (CAS: 107-21-1)	-13 °C (ECHA)
talca (Mg ₃ H ₂ (SiO ₃) ₄) (CAS: 14807-96-6)	>1300 °C (BL dodavatele)
titanium dioxide (CAS: 13463-67-7)	>1560 °C (BL dodavatele)
Boiling point or initial boiling point and boiling range	100 °C (mixture in water)
2-(2-methoxyethoxy)ethanol (CAS: 111-77-3)	193 °C (ECHA)
ethanediol (CAS: 107-21-1)	197.4 °C (ECHA)
titanium dioxide (CAS: 13463-67-7)	3000 °C (BL dodavatele)
Flammability	not a flammable liquid (ČSN 65 0201)
limestone (CAS: 1317-65-3)	non-flammable (10 mg/l při 20°C, 15 mg/l při 25°C)
Lower and upper explosion limit	
bottom	2.6 % (for propane 1,2 - diol)
upper	12.5 % (for propane 1,2 - diol)
Flash point	data not available
2-(2-methoxyethoxy)ethanol (CAS: 111-77-3)	91 °C (ECHA)
ethanediol (CAS: 107-21-1)	111 °C (ECHA)
Auto-ignition temperature	data not available
2-(2-methoxyethoxy)ethanol (CAS: 111-77-3)	215 °C (ECHA)
2-Hydroxyethyl methyl cellulose (CAS: 9032-42-2)	>170 °C (BL dodavatele)
ethanediol (CAS: 107-21-1)	398 °C (ECHA)
Decomposition temperature	data not available
limestone (CAS: 1317-65-3)	>600 °C (BL dodavatele)
talca (Mg ₃ H ₂ (SiO ₃) ₄) (CAS: 14807-96-6)	>1000 °C (BL dodavatele)
pH	4-6 (60% solution) (estimate)
2-Hydroxyethyl methyl cellulose (CAS: 9032-42-2)	6-8 (undiluted) (BL dodavatele)
limestone (CAS: 1317-65-3)	8.5-10.5 (10% solution at 20 °C) (BL dodavatele)
talca (Mg ₃ H ₂ (SiO ₃) ₄) (CAS: 14807-96-6)	9-9.5 (10% solution) (BL dodavatele)
Kinematic viscosity	>20.5 mm ² /s at 40 °C
Solubility in water	miscible
2-Hydroxyethyl methyl cellulose (CAS: 9032-42-2)	>10 g/l při 20°C (BL dodavatele)
ethanediol (CAS: 107-21-1)	1000 g/l při 20°C (ECHA)
limestone (CAS: 1317-65-3)	almost insoluble (BL dodavatele (10 mg/l při 20°C, 15 mg/l při 25°C))
titanium dioxide (CAS: 13463-67-7)	soluble (BL dodavatele)
Partition coefficient n-octanol/water (log value)	LogPow -1.36 to 3.2 (range of substances contained)
2-(2-methoxyethoxy)ethanol (CAS: 111-77-3)	-0.47 (BL dodavatele)
ethanediol (CAS: 107-21-1)	-1.36 (ECHA)
Vapour pressure	0.013 hPa to 0.45 hPa at 20 °C (range of substances contained)
2-(2-methoxyethoxy)ethanol (CAS: 111-77-3)	0.24 hPa at 20 °C (ECHA)
ethanediol (CAS: 107-21-1)	0.123 hPa at 25 °C (ECHA)

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



E0502 EKODUR ARCTIC interior paint/base

Creation date	03rd September 2018	Version	4.0
Revision date	20th May 2026		

Density and/or relative density

Density

1.47-1.65 g/cm³ at 23 °C (manufacturer's methodology B5/TD1-5 (ČSN EN ISO 2811-1))

2-(2-methoxyethoxy)ethanol (CAS: 111-77-3)

1020 g/cm³ at 20 °C (ECHA)

2-Hydroxyethyl methyl cellulose (CAS: 9032-42-2)

1.1-1.5 g/cm³ at 20 °C (BL dodavatele)

ethanediol (CAS: 107-21-1)

1.11 g/cm³ at 20 °C (ECHA)

limestone (CAS: 1317-65-3)

2.4-2.9 g/cm³ (BL dodavatele)

talc (Mg₃H₂(SiO₃)₄) (CAS: 14807-96-6)

2.58-2.83 g/cm³ (BL dodavatele)

Relative vapour density

data not available

Particle characteristics

data not available

Form

liquid: viscous, odorless and free of foreign mechanical impurities (manufacturer's methodology B5/TD1-17 (ČSN EN ISO 1513))

9.2. Other information

Vapour density

> 1 (air = 1)

Content of organic solvents (VOC)

0.011 kg/kg (calculation)

Total organic carbon (TOC)

0.009 kg/kg (calculation)

Solid content (dry matter)

≥60 % weight (calculation)

VOC limit value

cat. A (a) WB: 30 g/l

Max. VOC content in the product in its ready to use condition

17 g/l (calculation)

SECTION 10: Stability and reactivity

10.1. Reactivity

The mixture is non-flammable.

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Unknown.

10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost.

10.5. Incompatible materials

Protect against strong acids, bases and oxidizing agents.

10.6. Hazardous decomposition products

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Hazardous substances in concentrations exceeding exposure limits may cause acute inhalation poisoning, depending on the concentration and duration of exposure. No toxicological data is available for the mixture.

Acute toxicity

Based on the available data, the criteria for classification of the mixture are not met.

E0502 EKODUR ARCTIC interior paint/base								
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination	Source
Oral	ATE		307620 mg/kg				Calculation of value	
Dermal	ATE		3571429 mg/kg				Calculation of value	
Inhalation (vapor)	ATE		5952 mg/l				Calculation of value	

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



E0502 EKODUR ARCTIC interior paint/base

Creation date 03rd September 2018 Version 4.0
Revision date 20th May 2026

2-(2-methoxyethoxy)ethanol

Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination	Source
Oral	LD ₅₀		>5000 mg/kg		Mouse			BL dodavatele
Dermal	LD ₅₀		>5000 mg/kg		Rabbit			BL dodavatele

2-Hydroxyethyl methyl cellulose

Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination	Source
Oral	LD ₅₀	OECD 404	>2000 mg/kg		Rat (Rattus norvegicus)			BL dodavatele

ethanediol

Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination	Source
Dermal	LD ₅₀		10670 mg/kg		Rabbit			BL dodavatele
Inhalation (dust/mist)	LC ₅₀		>2.5 mg/l of air	6 hours	Rat (Rattus norvegicus)	F/M		BL dodavatele
Oral	LD ₅₀	OECD 401	7712 mg/kg		Rat (Rattus norvegicus)	F/M		BL dodavatele

formaldehyde ...%

Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination	Source
Inhalation (gases)	ATE		100 ppm					
Oral	ATE		500 mg/kg bw					

limestone

Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination	Source
Oral	LD ₅₀	OECD 425	6450 mg/kg bw		Rat (Rattus norvegicus)			BL dodavatele

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination	Source
Inhalation (dust/mist)	LC ₅₀		0.31 mg/l	4 hours				BL dodavatele
Inhalation (dust/mist)	ATE		0.31 mg/l					

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



E0502 EKODUR ARCTIC interior paint/base

Creation date 03rd September 2018 Version 4.0
Revision date 20th May 2026

titanium dioxide								
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination	Source
Oral	LD ₅₀		>5000 mg/kg					BL dodavatele
Inhalation	LC ₅₀		>6.82 mg/l of air					BL dodavatele

Skin corrosion/irritation

Data for the mixture are not available. Based on the available data, the criteria for classification of the mixture are not met.

ethanediol				
Route of exposure	Result	Exposure time	Species	Source
Dermal	Not irritating		Rabbit	BL dodavatele

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)				
Route of exposure	Result	Exposure time	Species	Source
	Corrosive			BL dodavatele

talc (Mg ₃ H ₂ (SiO ₃) ₄)				
Route of exposure	Result	Exposure time	Species	Source
		3 days	Human	výrobce

Serious eye damage/irritation

Data for the mixture are not available. Based on the available data, the criteria for classification of the mixture are not met.

ethanediol				
Route of exposure	Result	Exposure time	Species	Source
	Not irritating		Rabbit	BL dodavatele

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)				
Route of exposure	Result	Exposure time	Species	Source
	Serious eye damage			BL dodavatele

Respiratory or skin sensitisation

Data for the mixture are not available. Based on the available data, the criteria for classification of the mixture are not met.

ethanediol						
Route of exposure	Result	Method	Exposure time	Species	Sex	Source
Dermal	Negative	OECD 406		Guinea-pig (Cavia aperea f. porcellus)		BL dodavatele

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



E0502 EKODUR ARCTIC interior paint/base

Creation date 03rd September 2018 Version 4.0
Revision date 20th May 2026

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Route of exposure	Result	Method	Exposure time	Species	Sex	Source
Dermal	Sensitizing	OECD 406		Guinea-pig (Cavia aperea f. porcellus)		BL dodavatele
Dermal	Sensitizing	OECD 429		Mouse		BL dodavatele

Germ cell mutagenicity

Data for the mixture are not available. Based on the available data, the criteria for classification of the mixture are not met.

ethanediol

Result	Method	Exposure time	Specific target organ	Species	Sex	Source
Negative	OECD 471			Bacteria (Salmonella typhimurium)		BL dodavatele
Negative	OECD 473			Hamster		BL dodavatele
Negative	OECD 476			Mouse		BL dodavatele
Negative	OECD 478			Rat (Rattus norvegicus)	F/M	BL dodavatele

Carcinogenicity

Data for the mixture are not available. Based on the available data, the criteria for classification of the mixture are not met.

ethanediol

Route of exposure	Parameter	Value	Exposure time	Result	Species	Sex	Source
Oral	NOAEL	1500 mg/kg bw/day	103 weeks	Negative	Mouse	M	BL dodavatele

Reproductive toxicity

Data for the mixture are not available. Based on the available data, the criteria for classification of the mixture are not met.

ethanediol

Effect	Parameter	Value	Result	Species	Sex	Source
Effects on fertility	NOAEL	≥1000 mg/kg bw/day	Negative	Rat (Rattus norvegicus)	F/M	BL dodavatele

Toxicity for specific target organ - single exposure

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



E0502 EKODUR ARCTIC interior paint/base

Creation date 03rd September 2018 Version 4.0
Revision date 20th May 2026

Toxicity for specific target organ - repeated exposure

Data for the mixture are not available. Based on the available data, the criteria for classification of the mixture are not met.

ethanediol							
Route of exposure	Parameter	Value	Specific target organ	Result	Species	Sex	Source
Oral			Kidneys	Positive			BL dodavatele

Repeated dose toxicity

ethanediol								
Route of exposure	Parameter	Result	Method	Value	Exposure time	Species	Sex	Source
Oral	NOAEL		OECD 408	150 mg/kg	112 days (7 days/week)	Rat (Rattus norvegicus)	M	BL dodavatele
Oral	LOAEL		OECD 408	500 mg/kg	112 days (7 days/week)	Rat (Rattus norvegicus)	M	BL dodavatele

Aspiration hazard

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

11.2. Information on other hazards

Endocrine disrupting properties

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any components that may cause endocrine disruption for humans.

Other information

not available

SECTION 12: Ecological information

12.1. Toxicity

Data for the mixture are not available. Based on the available data, the criteria for classification of the mixture are not met.

Acute toxicity

2-(2-methoxyethoxy)ethanol						
Parameter	Method	Value	Exposure time	Species	Environment	Source
LC ₅₀		>100 mg/l	96 hours	Fish (Pimephales promelas)		BL dodavatele
EC ₅₀		>100 mg/l	48 hours	Daphnia (Daphnia magna)		BL dodavatele
EC ₅₀		>100 mg/l	96 hours	Algae (Selenastrum capricornutum)		BL dodavatele

2-Hydroxyethyl methyl cellulose						
Parameter	Method	Value	Exposure time	Species	Environment	Source
LC ₅₀	OECD 203	>500 mg/l	96 hours	Fish (Oncorhynchus mykiss)		BL dodavatele

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



E0502 EKODUR ARCTIC interior paint/base

Creation date 03rd September 2018 Version 4.0
Revision date 20th May 2026

2-Hydroxyethyl methyl cellulose						
Parameter	Method	Value	Exposure time	Species	Environment	Source
EC ₅₀	OECD 203	>100 mg/l	96 hours	Daphnia (Daphnia magna)		BL dodavatel e
EC ₅₀	OECD 209	>1000 mg/l	96 hours	Other aquatic organisms		BL dodavatel e
EC ₅₀	OECD 209	>100 mg/l	72 hours	Algae (Selenastrum capricornutum)		BL dodavatel e

ethanediol						
Parameter	Method	Value	Exposure time	Species	Environment	Source
LC ₅₀		72860 mg/l	96 hours	Fish (Pimephales promelas)	Fresh water	BL dodavatel e
NOEC	OECD 201	>100 mg/l	72 hours	Algae (Pseudokirchneriella subcapitata)	Fresh water	BL dodavatel e
EC ₅₀	OECD 202	>100 mg/l	48 hours	Daphnia (Daphnia magna)	Fresh water	BL dodavatel e
EC ₂₀		>1995 mg/l	30 minutes		Activated sludge	BL dodavatel e

limestone						
Parameter	Method	Value	Exposure time	Species	Environment	Source
LC ₅₀		>10000 mg/l	96 hours	Fish (Oncorhynchus mykiss)		BL dodavatel e
LC ₅₀		>1000 mg/l	48 hours	Daphnia (Daphnia magna)		BL dodavatel e
EC ₅₀		>200 mg/l	72 hours	Algae (Desmodesmus subspicatus)		BL dodavatel e

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)						
Parameter	Method	Value	Exposure time	Species	Environment	Source
LC ₅₀		0.58 mg/l	96 hours	Fish (Danio rerio (danio pruhované))		BL dodavatel e
EC ₅₀		1.02 mg/l	48 hours	Daphnia (Daphnia magna (perloočka velká))		BL dodavatel e
EC ₅₀	OECD 201	0.379 mg/l	72 hours	Algae (Pseudokirchneriella subcapitata (zelené řasy))		BL dodavatel e
EC ₁₀	OECD 201	0.188 mg/l	72 hours	Algae (Pseudokirchneriella subcapitata (zelené řasy))		BL dodavatel e

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



E0502 EKODUR ARCTIC interior paint/base

Creation date 03rd September 2018 Version 4.0
Revision date 20th May 2026

talc (Mg ₃ H ₂ (SiO ₃) ₄)						
Parameter	Method	Value	Exposure time	Species	Environment	Source
LC ₅₀		>100000 mg/l	24 hours	Fish (Oncorhynchus mykiss)		výrobce
LC ₅₀		94983.781 mg/kg	48 hours	Crustaceans		výrobce
LC ₅₀		48545.539 mg/l		Algae (Selenastrum capricornutum)		výrobce

titanium dioxide						
Parameter	Method	Value	Exposure time	Species	Environment	Source
LC ₅₀		>100 mg/l	96 hours	Fish (Oncorhynchus mykiss)	Fresh water	BL dodavatel
LC ₅₀		>1000 mg/l	96 hours	Fish (Pimephales promelas)	Fresh water	BL dodavatel
LC ₅₀	OECD 202	>100 mg/l	48 hours	Daphnia (Daphnia magna)	Fresh water	BL dodavatel

Chronic toxicity

ethanediol					
Parameter	Value	Exposure time	Species	Environment	Source
NOEC	15380 mg/l	7 days	Fish (Pimephales promelas)	Fresh water	BL dodavatele
NOEC	8590 mg/l	7 days	Daphnia (Ceriodaphnia dubia)	Fresh water	BL dodavatele

12.2. Persistence and degradability

Data for the mixture are not available.

Biodegradability

2-Hydroxyethyl methyl cellulose						
Parameter	Method	Value	Exposure time	Environment	Result	Source
	OECD 301E	0 %	28 days		Hardly biodegradable	BL dodavatel
	OECD 302B	11 %	28 days		Hardly biodegradable	BL dodavatel

ethanediol						
Parameter	Method	Value	Exposure time	Environment	Result	Source
	OECD 301A	90-100 %	10 days	Activated sludge	Easily biodegradable	BL dodavatel

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



E0502 EKODUR ARCTIC interior paint/base

Creation date 03rd September 2018 Version 4.0
Revision date 20th May 2026

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Parameter	Method	Value	Exposure time	Environment	Result	Source
					Hardly biodegradable	BL dodavatele

12.3. Bioaccumulative potential

Data for the mixture are not available.

2-Hydroxyethyl methyl cellulose

Parameter	Value	Source
Log Pow	<1	BL dodavatele

ethanediol

Parameter	Value	Source
Log Pow	-1.36	BL dodavatele

12.4. Mobility in soil

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any PMT or vPvM components.

12.5. Results of PBT and vPvB assessment

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any PBT or vPvB components.

12.6. Endocrine disrupting properties

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any components that may cause endocrine disruption in the environment.

12.7. Other adverse effects

Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Perfectly cleaned containers can be submitted for recycling.

Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

Waste type code

08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

Packaging waste type code

15 01 10* packaging containing residues of or contaminated by hazardous substances

(*) - Hazardous waste according to Directive 2008/98/EC on hazardous waste

SECTION 14: Transport information

14.1. UN number or ID number

not subject to transport regulations

14.2. UN proper shipping name

not relevant

14.3. Transport hazard class(es)

not relevant

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



E0502 EKODUR ARCTIC interior paint/base

Creation date	03rd September 2018	Version	4.0
Revision date	20th May 2026		

14.4. Packing group

not relevant

14.5. Environmental hazards

No.

14.6. Special precautions for user

Reference in the Sections 4 to 8.

14.7. Maritime transport in bulk according to IMO instruments

not relevant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

Restrictions pursuant to Annex XVII of Regulation (EC) No. 1907/2006 (REACH), as amended

2-(2-methoxyethoxy)ethanol

Restriction	Conditions of restriction
30	1. Shall not be placed on the market, or used, — as substances, — as constituents of other substances, or, — in mixtures, for supply to the general public when the individual concentration in the substance or mixture is equal to or greater than: — either the relevant specific concentration limit specified in Part 3 of Annex VI to Regulation (EC) No 1272/2008, or, — the relevant generic concentration limit specified in Part 3 of Annex I of Regulation (EC) No 1272/2008. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of substances and mixtures, suppliers shall ensure before the placing on the market that the packaging of such substances and mixtures is marked visibly, legibly and indelibly as follows: "Restricted to professional users". 2. By way of derogation, paragraph 1 shall not apply to: (a) medicinal or veterinary products as defined by Directive 2001/82/EC and Directive 2001/83/EC; (b) cosmetic products as defined by Directive 76/768/EEC; (c) the following fuels and oil products: — motor fuels which are covered by Directive 98/70/EC, — mineral oil products intended for use as fuel in mobile or fixed combustion plants, — fuels sold in closed systems (e.g. liquid gas bottles); (d) artists' paints covered by Regulation (EC) No 1272/2008; (e) the substances listed in Appendix 11, column 1, for the applications or uses listed in Appendix 11, column 2. Where a date is specified in column 2 of Appendix 11, the derogation shall apply until the said date. (f) devices covered by Regulation (EU) 2017/745.
54	Shall not be placed on the market after 27 June 2010, for supply to the general public, as a constituent of paints, paint strippers, cleaning agents, self-shining emulsions or floor sealants in concentrations equal to or greater than 0,1 % by weight.

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



E0502 EKODUR ARCTIC interior paint/base

Creation date 03rd September 2018 Version 4.0
Revision date 20th May 2026

formaldehyde ...%

Restriction	Conditions of restriction
28	1. Shall not be placed on the market, or used, — as substances, — as constituents of other substances, or, — in mixtures, for supply to the general public when the individual concentration in the substance or mixture is equal to or greater than: — either the relevant specific concentration limit specified in Part 3 of Annex VI to Regulation (EC) No 1272/2008, or, — the relevant generic concentration limit specified in Part 3 of Annex I of Regulation (EC) No 1272/2008. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of substances and mixtures, suppliers shall ensure before the placing on the market that the packaging of such substances and mixtures is marked visibly, legibly and indelibly as follows: “Restricted to professional users”. 2. By way of derogation, paragraph 1 shall not apply to: (a) medicinal or veterinary products as defined by Directive 2001/82/EC and Directive 2001/83/EC; (b) cosmetic products as defined by Directive 76/768/EEC; (c) the following fuels and oil products: — motor fuels which are covered by Directive 98/70/EC, — mineral oil products intended for use as fuel in mobile or fixed combustion plants, — fuels sold in closed systems (e.g. liquid gas bottles); (d) artists' paints covered by Regulation (EC) No 1272/2008; (e) the substances listed in Appendix 11, column 1, for the applications or uses listed in Appendix 11, column 2. Where a date is specified in column 2 of Appendix 11, the derogation shall apply until the said date. (f) devices covered by Regulation (EU) 2017/745.

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



E0502 EKODUR ARCTIC interior paint/base

Creation date 03rd September 2018 Version 4.0
Revision date 20th May 2026

formaldehyde ...%

Restriction	Conditions of restriction
72	1. Shall not be placed on the market after 1 November 2020 in any of the following: (a) clothing or related accessories; (b) textiles other than clothing which, under normal or reasonably foreseeable conditions of use, come into contact with human skin to an extent similar to clothing; (c) footwear; if the clothing, related accessory, textile other than clothing or footwear is for use by consumers and the substance is present in a concentration, measured in homogeneous material, equal to or greater than that specified for that substance in Appendix 12. 2. By way of derogation, in relation to the placing on the market of formaldehyde [CAS No 50-00-0] in jackets, coats or upholstery, the relevant concentration for the purposes of paragraph 1 shall be 300 mg/kg during the period between 1 November 2020 and 1 November 2023. The concentration specified in Appendix 12 shall apply thereafter. 3. Paragraph 1 shall not apply to: (a) clothing, related accessories or footwear, or parts of clothing, related accessories or footwear, made exclusively of natural leather, fur or hide; (b) non-textile fasteners and non-textile decorative attachments; (c) second-hand clothing, related accessories, textiles other than clothing or footwear (d) wall-to-wall carpets and textile floor coverings for indoor use, rugs and runners. 4. Paragraph 1 shall not apply to clothing, related accessories, textiles other than clothing, or footwear within the scope of Regulation (EU) 2016/425 of the European Parliament and of the Council (*) or Regulation (EU) 2017/745 of the European Parliament and of the Council (**). 5. Paragraph 1(b) shall not apply to disposable textiles. 'Disposable textiles' means textiles that are designed to be used only once or for a limited time and are not intended for subsequent use for the same or a similar purpose. 6. Paragraphs 1 and 2 shall apply without prejudice to the application of any stricter restrictions set out in this Annex or in other applicable Union legislation. 7. The Commission shall review the exemption in paragraph 3(d) and, if appropriate, modify that point accordingly. (*) Regulation (EU) 2016/425 of the European Parliament and of the Council of 9 March 2016 on personal protective equipment and repealing Council Directive 89/686/EEC (OJ L 81, 31.3.2016, p. 51). (**) Regulation (EU) 2017/745 of the European Parliament and of the Council of 5 April 2017 on medical devices, amending Directive 2001/83/EC, Regulation (EC) No 178/2002 and Regulation (EC) No 1223/2009 and repealing Council Directives 90/385/EEC and 93/42/EEC (OJ L 117, 5.5.2017, p. 1).

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



E0502 EKODUR ARCTIC interior paint/base

Creation date 03rd September 2018 Version 4.0
Revision date 20th May 2026

formaldehyde ...%

Restriction	Conditions of restriction
77	1. Shall not be placed on the market in articles, after 6 August 2026, if, under the test conditions specified in Appendix 14, the concentration of formaldehyde released from those articles exceeds: (a) 0,062 mg/m³ for furniture and wood-based articles; (b) 0,080 mg/m³ for articles other than furniture and wood-based articles. The first subparagraph shall not apply to: (a) articles in which formaldehyde or formaldehyde releasing substances are exclusively naturally present in the materials from which the articles are produced; (b) articles that are exclusively for outdoor use under foreseeable conditions; (c) articles in constructions, that are exclusively used outside the building shell and vapour barrier and that do not emit formaldehyde into indoor air; (d) articles exclusively for industrial or professional use unless formaldehyde released from them leads to exposure of the general public under foreseeable conditions of use; (e) articles for which the restriction laid down in entry 72 applies; (f) articles that are biocidal products within the scope of Regulation (EU) No 528/2012 of the European Parliament and of the Council; (g) devices within the scope of Regulation (EU) 2017/745; (h) personal protective equipment within the scope of Regulation (EU) 2016/425; (i) articles intended to come into contact directly or indirectly with food within the scope of Regulation (EC) No 1935/2004; (j) second-hand articles. 2. Shall not be placed on the market in road vehicles after 6 August 2027 if, under the test conditions specified in Appendix 14, the concentration of formaldehyde in the interior of those vehicles exceeds 0,062 mg/m³. The first subparagraph shall not apply to: (a) road vehicles exclusively for industrial or professional use unless the concentration of formaldehyde in the interior of those vehicles leads to exposure of the general public under foreseeable conditions of use; (b) second-hand vehicles.

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out (mixture).

SECTION 16: Other information

A list of standard risk phrases used in the safety data sheet

EUH071	Corrosive to the respiratory tract.
EUH208	Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.
EUH210	Safety data sheet available on request.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310+H330	Fatal in contact with skin or if inhaled.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H360D	May damage the unborn child.
H373	May cause damage to the kidneys through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



E0502 EKODUR ARCTIC interior paint/base

Creation date	03rd September 2018	Version	4.0
Revision date	20th May 2026		

Guidelines for safe handling used in the safety data sheet

- P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read label before use.
P501 Dispose of contents/container to be handed over to a person authorized to dispose of waste or a site designated by the town.

Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

Key to abbreviations and acronyms used in the safety data sheet

Acute Tox.	Acute toxicity
ADR	Agreement concerning the international carriage of dangerous goods by road
Aquatic Acute	Hazardous to the aquatic environment
Aquatic Chronic	Hazardous to the aquatic environment (chronic)
ATE	Acute toxicity estimate
BCF	Bioconcentration Factor
Carc.	Carcinogenicity
CAS	Chemical Abstracts Service
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures
EC	Identification code for each substance listed in EINECS
EC ₁₀	Concentration of a substance when it is affected 10 % of the population
EC ₂₀	Concentration of a substance when it is affected 20 % of the population
EC ₅₀	Concentration of a substance when it is affected 50 % of the population
EINECS	European Inventory of Existing Commercial Chemical Substances
EmS	Emergency Response Procedures for Ships Carrying Dangerous Goods
EU	European Union
EuPCS	European Product Categorisation System
Eye Dam.	Serious eye damage
Eye Irrit.	Eye irritation
IATA	International Air Transport Association
IBC	International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
INCI	International Nomenclature of Cosmetic Ingredients
ISO	International Organization for Standardization
IUPAC	International Union of Pure and Applied Chemistry
LC ₅₀	Lethal concentration of a substance in which it can be expected death of 50% of the population
LD ₅₀	Lethal dose of a substance in which it can be expected death of 50% of the population
LOAEL	Lowest observed adverse effect level
log K _{ow}	Octanol-water partition coefficient
Muta.	Germ cell mutagenicity
NOAEL	No observed adverse effect level
NOEC	No observed effect concentration
OEL	Occupational Exposure Limits
PBT	Persistent, bioaccumulative and toxic
PMT	Persistent, mobile and toxic
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
Repr.	Reproductive toxicity
RID	Regulation concerning the International Carriage of Dangerous Goods by Rail
Skin Corr.	Skin corrosion

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



E0502 EKODUR ARCTIC interior paint/base

Creation date	03rd September 2018	Version	4.0
Revision date	20th May 2026		

Skin Irrit.	Skin irritation
Skin Sens.	Skin sensitization
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure
UN number	Four-figure identification number of the substance or article taken from the UN Model Regulations
UVCB	Substances of unknown or variable composition, complex reaction products or biological materials
VOC	Volatile organic compounds
vPvB	Very persistent and very bioaccumulative
vPvM	Very persistent and very mobile

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

Recommended restrictions of use

not available

Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended.
REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

The changes (which information has been added, deleted or modified)

The version 4.0 replaces the SDS version from Tuesday, 9 August 2022. Changes were made in sections 1, 2, 8, 9, 10, 11, 12, 13, 15 and 16.

More information

Classification procedure - calculation method.

Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.

Příloha bezpečnostního listu pro výrobek: Vodou ředitelná nátěrová hmota

1. Expoziční scénář: Průmyslové použití

Sektor použití : SU3
 Kategorie chemických výrobků : PC9a
 Dílčí procesy kryté expozičním scénářem : PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC10, PROC13, PROC 15
 Uvolňování výrobku do životního prostředí : ERC4

Základní podmínky omezující riziko pro pracovníky:

Trvání pracovních činností : expozice trvající nejvýše 8 hodin / den
 Koncentrace : práce s nátěrovou hmotou, popř. naředěnou na aplikační hustotu
 Teplota : provádění prací při doporučené teplotě 19 až 25°C a vzdušné vlhkosti do 70%
 Obecná opatření na omezení rizik : pracovat v ochranném pracovním oděvu, při kontaktu s nátěrovou hmotou používat ochranné rukavice a ochranné brýle, limitní koncentrace látek obsažených ve směsi jsou uvedeny v oddíle 8 bezpečnostního listu a mohou se lišit v závislosti na typu nátěrové hmoty
 Při práci dodržovat obecné zásady hygieny a bezpečnosti práce.
 Prostředí, kde jsou činnosti prováděny : vnitřní prostředí s odvětráváním.

Doplňující požadavky omezující riziko pro pracovníky vykonávající dílčí pracovní činnosti:

Dílčí pracovní činnost prováděná s výrobkem	Kategorie procesu	Požadované doplňující opatření
Přečerpávání nátěrových hmot z / do zásobníků a zařízení v uzavřeném systému	PROC1 Použití v rámci uzavřeného výrobního procesu	Nevyžadováno
Přečerpávání nátěrových hmot z / do zásobníků a zařízení v nesespecializovaném zařízení s možností expozice osob a životního prostředí	PROC8a přeprava výrobku (napouštění / vypouštění) z / do nádob / kontejnerů v nesespecializovaných zařízeních	Místní odsávání, popř. dobré větrání (3 - 5 výměn vzduchu za hodinu).
Přečerpávání nátěrových hmot z / do zásobníků a zařízení v nesespecializovaném zařízení s možností expozice osob a životního prostředí	PROC8b PROC8a přeprava výrobku (napouštění / vypouštění) z / do nádob / kontejnerů v specializovaných zařízeních	Místní odsávání, popř. dobré větrání (3 - 5 výměn vzduchu za hodinu).
Míchání, směšování, ředění nátěrových hmot v otevřených zařízeních s možností expozice osob a životního prostředí	PROC5 míchání nebo směšování v dávkových procesech při výrobě směsí	Místní odsávání, popř. dobré větrání (3 - 5 výměn vzduchu za hodinu).
Aplikace stříkáním	PROC7 průmyslové nástřikové techniky	Robotický nástřik provádět v uzavřených komorách nebo uzavřených kabinách s odsáváním a zajištěním nezávislého přívodu vzduchu. Ruční nástřik provádějte ve stříkacích kabinách nebo v intenzívně větraných prostorách (5-10 výměn vzduchu za hodinu) za použití polomasky nebo masky s filtrem typu A/P2.
Ruční aplikace nátěrových hmot válečkem, štětkou, stěrkou	PROC10 aplikace válečkem, stěrkou nebo štětkou	Místní odsávání, popř. dobré větrání (3 - 5 výměn vzduchu za hodinu).
Nanášení nátěrových hmot poléváním nebo ponořením	PROC13 úprava předmětů máčením a poléváním	Místní odsávání, popř. dobré větrání (3 - 5 výměn vzduchu za hodinu).
Volné sušení nátěrového filmu při normální teplotě nebo mírně zvýšené teplotě	PROC4 použití v rámci dávkového a jiného procesu s větší možností expozice	Provádět za místního odsávání, popř. dobré větrání (3 - 5 výměn vzduchu za hodinu).
Kontinuální postupy sušení a vytvrzování nátěrových hmot za zvýšené teploty v sušicích tunelech s odsáváním par	PROC2 použití v rámci nepřetržitého chemického výrobního procesu s příležitostnou kontrolovanou	Nevyžaduje další opatření na omezení rizik.

Dílčí pracovní činnost prováděná s výrobkem	Kategorie procesu	Požadované doplňující opatření
	expozici (např. odběr vzorků)	
Násadové postupy sušení a vytvrzování filmu nátěrových hmot za zvýšené teploty v odsávaných komorách.	PROC3 použití v rámci uzavřeného dávkového procesu výroby směsí	Nevyžaduje další opatření na omezení rizik.
Strojní čištění a promývání uzavřených nádrží, zásobníků a zařízení vybavených odsáváním par	PROC3 použití v rámci uzavřeného dávkového procesu výroby směsí	Nevyžaduje další opatření na omezení rizik.
Ruční čištění malých zásobníků, aplikačních zařízení a nářadí	PROC10 aplikace válečkem, stěrkou nebo štětcem	Lokální odsávání v místě potencionálního úniku emisí nebo dobré větrání (3 – 5 výměn vzduch za hodinu).
Kontrolní činnosti prováděné s nátěrovými hmotami v laboratořích	PROC15 použití jako laboratorního reagentu (práce s výrobkem v laboratořích)	Dobré větrání (3 – 5 výměn vzduch za hodinu).
Činnosti s odpady výrobku a odpady znečištěnými výrobkem		Při nebezpečí styku s odpady používat rukavice. Odpady ukládat do uzavíratelných obalů uložených v dobře větraných skladech nebo ve venkovním prostředí. Odpady zajistit proti úniku do vody a půdy.

Doplňující požadavky omezující riziko pro životní prostředí

Omezování emisí do ovzduší	Při nanášení barvy stříkáním odstraňovat ze vzduchu odtahovaného z pracovních prostor úlet aerosolu barvy. Při překročení limitů spotřeby rozpouštědel stanovených vyhláškou využívat postupy zaručujícími dodržení emisních parametrů stanovených předpisy pro ochranu ovzduší.
Omezování emisí do vody	Barvu a odpady znečištěné barvou skladovat v objektech stavebně zajištěných proti úniku úkapů a havarijních úniků do podzemních a povrchových vod. Při vypouštění odpadních vod dodržovat parametry stanovené pro dané zařízení vodohospodářským orgánem.
Odstraňování odpadů	Odpady barvy a materiálů znečištěných barvou odstraňovat ve spolupráci s osobami oprávněnými k nakládání s odpady.

2. Expoziční scénář: profesionální použití

Sektor použití : SU22
Kategorie chemických výrobků : PC9a
Dílčí procesy kryté expozičním scénářem : PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC 15, PROC19
Uvolňování výrobku do životního prostředí : ERC8a, ERC8d

Základní podmínky omezující riziko pro pracovníky:

Trvání pracovních činností : expozice trvající nejvýše 8 hodin / den
Koncentrace : práce s nátěrovou hmotou, popř. naředěnou na aplikační hustotu
Teplota : provádění prací při doporučené teplotě 19 až 25°C a vzdušné vlhkosti do 70%
Obecná opatření na omezení rizik : pracovat v ochranném pracovním oděvu, při kontaktu s nátěrovou hmotou používat ochranné rukavice a ochranné brýle, limitní koncentrace látek obsažených ve směsi jsou uvedeny v oddíle 8 bezpečnostního listu a mohou se lišit v závislosti na typu nátěrové hmoty
Při práci dodržovat obecné zásady hygieny a bezpečnosti práce.
Prostředí, kde jsou činnosti prováděny : vnitřní prostředí s odvětráváním, popř. venkovní prostředí.

Doplňující požadavky omezující riziko pro pracovníky vykonávající dílčí pracovní činnosti:

Dílčí pracovní činnost prováděná s výrobkem	Kategorie procesu	Požadované doplňující opatření
Přečerpávání nátěrových hmot z / do zásobníků a zařízení v nespécializovaném zařízení s možností expozice osob a životního prostředí	PROC8a přeprava výrobku (napouštění / vypouštění) z / do nádob / kontejnerů v nespécializovaných zařízeních	Uvnitř budov: Místní odsávání, popř. dobré větrání (3 – 5 výměn vzduchu za hodinu). Venku: zajistit úkapy nátěrových hmot.
Míchání, směšování, ředění nátěrových hmot v otevřených zařízeních s možností expozice osob a	PROC5 míchání nebo směšování	Uvnitř: Místní odsávání, popř. dobré větrání (3 – 5 výměn vzduchu za hodinu).

Dílčí pracovní činnost prováděná s výrobkem	Kategorie procesu	Požadované doplňující opatření
životního prostředí	v dávkových procesech při výrobě směsí	Venku: činnosti vykonávat nejdéle 4 hod./den bez potřeby dalších opatření, nebo používat ochranu dýchacích orgánů s filtrem typu A/P2.
Aplikace stříkáním	PROC11 neprůmyslové nástřikové techniky	Uvnitř: nástřik provádět v uzavřených komorách nebo uzavřených kabinách s odsáváním a zajištěním nezávislého přívodu vzduchu. Místní odsávání, popř. dobré větrání (3 – 5 výměn vzduchu za hodinu). Ruční nástřik provádějte ve stříkacích kabinách nebo v intenzivně větraných prostorách (5-10 výměn vzduchu za hodinu) za použití polomasky nebo masky s filtrem typu A/P2. Venku: Nevyžaduje další opatření na omezení rizik.
Ruční aplikace nátěrových hmot válečkem, štětcem, stěrkou	PROC10 aplikace válečkem, stěrkou nebo štětcem	Uvnitř: Místní odsávání, popř. dobré větrání (3 – 5 výměn vzduchu za hodinu). Venku: nevyžaduje se další opatření
Nanášení nátěrových hmot poléváním nebo ponořením	PROC13 úprava předmětů máčením a poléváním	Uvnitř: Místní odsávání, popř. dobré větrání (3 – 5 výměn vzduchu za hodinu). Venku: Nevyžaduje se další opatření.
Násadové postupy sušení a vytvrzování filmu nátěrových hmot za zvýšené teploty v odsávaných komorách.	PROC3 použití v rámci uzavřeného dávkového procesu výroby směsí	Nevyžaduje další opatření na omezení rizik.
Volné sušení nátěrového filmu při normální teplotě nebo mírně zvýšené teplotě	PROC4 použití v rámci dávkového a jiného procesu s větší možností expozice	Uvnitř: Provádět za místního odsávání, popř. dobré větrání (3 – 5 výměn vzduchu za hodinu). Venku: nevyžaduje se další opatření
Ruční čištění malých zásobníků, aplikačních zařízení a nářadí	PROC10 aplikace válečkem, stěrkou nebo štětcem	Uvnitř: Lokální odsávání v místě potencionálního úniku emisí nebo dobré větrání (3 – 5 výměn vzduchu za hodinu). Venku: nevyžaduje se další opatření
Činnosti, při kterých dochází k přímému kontaktu s výrobkem bez použití pracovního nástroje	PROC19 ruční mísení s úzkým kontaktem za použití OOPP	Uvnitř: rukavice, místní odsávání nebo dobré větrání Venku: rukavice
Kontrolní činnosti prováděné s nátěrovými hmotami v laboratořích	PROC15 použití jako laboratorního reagentu (práce s výrobkem v laboratořích)	Dobré větrání (3 – 5 výměn vzduchu za hodinu).
Činnosti s odpady výrobku a odpady znečištěnými výrobkem		Při nebezpečí styku s odpady používat rukavice. Odpady ukládat do uzavíratelných obalů uložených v dobře větraných skladech nebo ve venkovním prostředí. Odpady zajistit proti úniku do vody a půdy. Uvnitř: dobré větrání (3 – 5 výměn vzduchu za hodinu).

Doplňující požadavky omezující riziko pro životní prostředí

Omezování emisí do ovzduší	Nejsou požadována žádná zvláštní opatření
Omezování emisí do vody	Barvu a odpady znečištěné barvou skladovat v objektech stavebně zajištěných proti úniku úkapů a havarijních úniků do podzemních a povrchových vod. Při vypouštění odpadních vod dodržovat parametry stanovené pro dané zařízení vodo hospodářským orgánem.
Odstraňování odpadů	Odpady barvy a materiálů znečištěných barvou odstraňovat ve spolupráci s osobami oprávněnými k nakládání s odpady.