

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date	25th January 2018	Version	6.0
Revision date	03rd February 2025		

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. Product identifier**
Substance / mixture
Number
UFI
Other mixture names
SU2013 Syntetická vrchní barva UNIVERZAL
- 1.2. Relevant identified uses of the substance or mixture and uses advised against**
Mixture's intended use
UNIVERSAL SU2013 paint is used for topcoats of wood and metal exposed to the effects of weather (fences, gutters, window doors, constructions of all kinds, railings and various sheet metal products). It is also suitable for ordinary mineral surfaces (masonry) in the interior, which must be mature, dry and insulated against moisture.
Main intended use
PC-PNT-3 Paints/coatings - Protective and functional
Mixture uses advised against
The product should not be used in ways other than those referred in Section 1.
Exposure scenario is attached to the Safety Data Sheet.
- 1.3. Details of the supplier of the safety data sheet**
Manufacturer
Name or trade name
Address
Identification number (CRN)
VAT Reg No
Phone
E-mail
Web address
Competent person responsible for the safety data sheet
Name
E-mail
- 1.4. Emergency telephone number**
European emergency number: 112
- COLORLAK, a.s.
Tovární 1076, Staré Město, 686 03
Czech Republic
49444964
CZ49444964
+420 572527111
colorlak@colorlak.cz
www.colorlak.cz
- Ing. Gabriela Kubíková
kubikova@colorlak.cz

SECTION 2: Hazards identification

- 2.1. Classification of the substance or mixture**
Classification of the mixture in accordance with Regulation (EC) No 1272/2008
The mixture is classified as dangerous.
- Flam. Liq. 3, H226
STOT SE 3, H336
Aquatic Chronic 3, H412
Most serious adverse physico-chemical effects
Flammable liquid and vapour.
Most serious adverse effects on human health and the environment
May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects.

- 2.2. Label elements**
Hazard pictogram



Signal word
Warning

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date 25th January 2018
Revision date 03rd February 2025 Version 6.0

Hazardous substances

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics

Hazard statements

H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read label before use.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing vapours/aerosols.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P312 Call a POISON CENTRE/doctor if you feel unwell.
P370+P378 In case of fire: Use foam (alcohol resistant), carbon dioxide, a spray mist, powder to extinguish.
P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.
P501 Dispose of contents/container to be handing over to a person authorized to dispose of waste or a site designated by the town.

Supplemental information

EUH204 Contains isocyanates. May produce an allergic reaction.
EUH208 Contains neodecanoic acid, cobalt salt. May produce an allergic reaction.
EUH066 Repeated exposure may cause skin dryness or cracking.
Density 0.94-1.12 g/cm³ at 20 °C (ČSN EN ISO 2811-2)
VOC 0,303 kg/kg
TOC 0,254 kg/kg
Dry matter ≥38 % weight
VOC limit value cat. A (d) SB: 300 g/l
Max. VOC content in the product in its ready to use condition 292 g/l

2.3. Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended. Does not contain any PMT or vPvM components. The titanium dioxide contained contains < 1% of particles with an aerodynamic diameter ≤ 10 µm, and therefore the criteria for classification and supplementary warnings are not met.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

UNIVERSAL SU2013 paint is a dispersion of organic and inorganic substances in a solution of alkyd resin and organic solvents with the addition of a drying agent.

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Index: 022-006-00-2 CAS: 13463-67-7 EC: 236-675-5 Registration number: 01-2119489379-17	titanium dioxide	≤20		6, 7, 8

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date	25th January 2018	Version	6.0
Revision date	03rd February 2025		

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
EC: 919-857-5 Registration number: 01-2119463258-33	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics	15-25	Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336 EUH066	9, B
CAS: 14807-96-6 EC: 238-877-9	talc (Mg3H2(SiO3)4)	≤10	not classified as dangerous	
CAS: 1309-37-1 EC: 215-168-2 Registration number: 01-2119457614-35-0000	diiron trioxide	≤6.7	not classified as dangerous	
Index: 013-002-00-1 CAS: 7429-90-5 EC: 231-072-3 Registration number: 01-2119529243-45	aluminium powder (stabilised)	5.2	Flam. Sol. 1, H228 Water-react. 2, H261	5, C
Index: 649-327-00-6 EC: 918-481-9 Registration number: 01-2119457273-39	hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	2-5	Asp. Tox. 1, H304 EUH066	B
EC: 926-141-6 Registration number: 01-2119456620-43	hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclic, <2% aromatics	1-3	Asp. Tox. 1, H304 EUH066	B
CAS: 1333-86-4 EC: 215-609-9 Registration number: 01-2119384822-32	carbon black	≤1		
CAS: 7631-86-9 EC: 231-545-4 Registration number: 01-2119379499-16	Silica, amorphous	0.1-1	not classified as dangerous	
Index: 649-405-00-X CAS: 64742-88-7 EC: 265-191-7 Registration number: 01-2119537181-47	solvent naphtha (petroleum), medium aliph.	0.2-0.5	Asp. Tox. 1, H304 STOT RE 1, H372 (central nervous system)	
CAS: 51274-00-1 EC: 257-098-5 Registration number: 01-2119457554-33	Iron hydroxide oxide yellow	≤0.25	not classified as dangerous	
CAS: 27253-31-2 EC: 248-373-0 Registration number: 01-2119970733-31	neodecanoic acid, cobalt salt	0.1-0.4	Acute Tox. 4, H302 Skin Sens. 1, H317 STOT RE 1, H372 (the gastrointestinal tract) Aquatic Chronic 3, H412	B
Index: 603-002-00-5 CAS: 64-17-5 EC: 200-578-6 Registration number: 01-2119457610-43	ethanol	≤0.1	Flam. Liq. 2, H225 Eye Irrit. 2, H319	
CAS: 9011-05-6 EC: 618-464-3	urea, polymer with formaldehyde	≤0.08	Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 STOT SE 3, H335	

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date	25th January 2018	Version	6.0
Revision date	03rd February 2025		

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
EC: 905-588-0 Registration number: 01-2119539452-40	Technical xylene (mixed with ethylbenzene)	≤0.06	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Acute Tox. 4, H312+H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Specific concentration limit: STOT RE 2, H373 (central nervous system): C ≥ 10 %	9, B
CAS: 34590-94-8 EC: 252-104-2 Registration number: 01-2119450011-60	(2-methoxymethylethoxy)propanol	≤0.03	not classified as dangerous Specific concentration limit: ATE Oral = 5001 mg/kg bw ATE Inhalation (vapor) = 3,35 mg/l ATE Dermal = 9510 mg/kg bw	9
Index: 607-195-00-7 CAS: 108-65-6 EC: 203-603-9 Registration number: 01-2119475791-29	2-methoxy-1-methylethyl acetate	≤0.02	Flam. Liq. 3, H226 STOT SE 3, H336	9
Index: 607-025-00-1 CAS: 123-86-4 EC: 204-658-1 Registration number: 01-2119485493-29	n-butyl acetate	≤0.02	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	9
Index: 615-006-00-4 CAS: 26471-62-5 EC: 247-722-4 Registration number: 01-2119454791-34	m-tolylidene diisocyanate	≤0.01	Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 Acute Tox. 2, H330 Resp. Sens. 1, H334 STOT SE 3, H335 Carc. 2, H351 Aquatic Chronic 3, H412 Specific concentration limit: Resp. Sens. 1, H334: C ≥ 0.1 %	2, 9, A
Index: 601-023-00-4 CAS: 100-41-4 EC: 202-849-4 Registration number: 01-2119489370-35	ethylbenzene	≤0.009	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Acute Tox. 4, H332 STOT RE 2, H373 (hearing organs)	9
CAS: 77-58-7 EC: 201-039-8 Registration number: 01-2119496068-27	Dibutyltin dilaurate	≤0.001	Eye Irrit. 2, H319 Muta. 2, H341 Repr. 1B, H360FD STOT SE 1, H370 STOT RE 1, H372 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	A
Index: 603-108-00-1 CAS: 78-83-1 EC: 201-148-0 Registration number: 01-2119484609-23	2-methylpropan-1-ol	≤0.001	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335, H336	

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date	25th January 2018	Version	6.0
Revision date	03rd February 2025		

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Index: 601-021-00-3 CAS: 108-88-3 EC: 203-625-9 Registration number: 01-2119471310-51	toluene	≤0.0003	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Repr. 2 (**), H361d STOT RE 2 (**), H373	9, A, D
Index: 605-001-00-5 CAS: 50-00-0 EC: 200-001-8 Registration number: 01-2119488953-20	formaldehyde ...%	≤0.0001	Acute Tox. 3, H301+H311 Skin Corr. 1B, H314 Skin Sens. 1A, H317 Eye Dam. 1, H318 Acute Tox. 2, H330 Muta. 2, H341 Carc. 1B, H350 Specific concentration limit: Skin Corr. 1B, H314: C ≥ 25 % Skin Irrit. 2, H315: 5 % ≤ C < 25 % Eye Irrit. 2, H319: 5 % ≤ C < 25 % STOT SE 3, H335: C ≥ 5 % ATE Inhalation (gases) = 100 ppm ATE Oral = 500 mg/kg bw Skin Sens. 1, H317: C ≥ 0.2 %	1, 3, 4, A

Notes

** another exposure route cannot be ruled out

*** reproductive toxicity: supplementary letters specify whether fetal harm (d) or fertility harm (f) may occur

- Note B: Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'. In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis.
- Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
- Note D: Certain substances which are susceptible to spontaneous polymerisation or decomposition are generally placed on the market in a stabilised form. It is in this form that they are listed in Part 3 of Annex VI to Regulation (EC) No 1272/2008. However, such substances are sometimes placed on the market in a non-stabilised form. In this case, the supplier who places such a substance on the market must state on the label the name of the substance followed by the words "non-stabilised".
- Note F: This substance may contain a stabiliser. If the stabiliser changes the hazardous properties of the substance, as indicated by the classification in Part 3, classification and labelling should be provided in accordance with the rules for classification and labelling of hazardous mixtures.
- Note T: This substance may be marketed in a form which does not have the physical hazards as indicated by the classification in the entry in Part 3. If the results of the relevant method or methods in accordance with Part 2 of Annex I of this Regulation show that the specific form of substance marketed does not exhibit this physical property or these physical hazards, the substance shall be classified in accordance with the result or results of this test or these tests. Relevant information, including reference to the relevant test method(s) shall be included in the safety data sheet.
- Note V: If the substance is to be placed on the market as fibres (with diameter < 3 µm, length > 5 µm and aspect ratio ≥ 3:1) or particles of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or additional routes of exposure (oral or dermal) should be applied.

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date	25th January 2018	Version	6.0
Revision date	03rd February 2025		

- 7 *Note W: It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung.*

This note aims to describe the particular toxicity of the substance; it does not constitute a criterion for classification according to this Regulation.

- 8 *Note 10: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter $\leq 10 \mu\text{m}$.*
- 9 *A substance for which exposure limits are set.*
- A *The use of the substance is restricted by Annex XVII of REACH Regulation*
- B *Substance of unknown or variable composition, complex reaction products or biological materials - UVCB.*
- C *Explosive precursor*
- D *Drug precursor*

Full text of all classifications and hazard statements is given in the section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Take care of your own safety. If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet. If unconscious, put the person in the stabilized (recovery) position on his side with his head slightly bent backwards and make sure that airways are free; never induce vomiting. If the person vomits by himself, make sure that the vomit is not inhaled. In life threatening conditions first of all provide resuscitation of the affected person and ensure medical assistance. Respiratory arrest - provide artificial respiration immediately. Cardiac arrest - provide indirect cardiac massage immediately.

If inhaled

Terminate the exposure immediately; move the affected person to fresh air. Protect the person against growing cold. Provide medical treatment if irritation, dyspnoea or other symptoms persist.

If on skin

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible. Soap, soap solution or shampoo should be used if there is no skin injury. Provide medical treatment if skin irritation persists. Rinse skin with water or shower.

If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. Rinsing should continue at least for 10 minutes.

If swallowed

Rinse out the mouth with clean water. In the event of issues, find medical help.

4.2. Most important symptoms and effects, both acute and delayed

If inhaled

May cause drowsiness or dizziness.

If on skin

Not expected.

If in eyes

Not expected.

If swallowed

Irritation, nausea.

4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

Unsuitable extinguishing media

Water - full jet.

5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date 25th January 2018
Revision date 03rd February 2025 Version 6.0

5.3. Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Closed containers with the product near the fire should be cooled with water. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide sufficient ventilation. Flammable liquid and vapour. Remove all ignition sources. Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Do not inhale mist/vapours/spray.

6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water.

6.3. Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.

6.4. Reference to other sections

See the Section 7, 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Prevent formation of gases and vapours in flammable or explosive concentrations and concentrations exceeding the occupational exposure limits. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. Use non-sparking tools. Use of antistatic clothes and footwear is recommended. Do not inhale mist/vapours/spray. No smoking. Use only outdoors or in a well-ventilated area. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Take action to prevent static discharges. Avoid release to the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Do not expose to sunlight. Store locked up. Keep container tightly closed. Keep cool.

Content	Packaging type	Material of package
0,35 l	can / tin	FE
0,6 l	can / tin	FE
0,75 l	can / tin	FE
2,5 l	bucket	FE
3,5 l	bucket	FE
9 l	bucket	FE
9 kg	bucket	FE
18 kg	bucket	FE
20 kg	bucket	FE
30 l	barrel / drum	FE

Storage class 3A - Flammable liquids (flash point below 55 °C)
Storage temperature +5 až +25 °C

The specific requirements or rules relating to the substance/mixture

Solvent vapours are heavier than air and accumulate especially near the floor where they may form an explosive mixture with the air.

7.3. Specific end use(s)

not available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

The mixture contains substances for which occupational exposure limits are set.

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date 25th January 2018
Revision date 03rd February 2025 Version 6.0

European Union

Commission Directive (EU) 2019/1831

Substance name (component)	Type	Value
n-butyl acetate (CAS: 123-86-4)	OEL 8 hours	241 mg/m ³
	OEL 8 hours	50 ppm
	OEL 15 minutes	723 mg/m ³
	OEL 15 minutes	150 ppm

European Union

Commission Directive 2000/39/EC

Substance name (component)	Type	Value
(2-methoxymethylethoxy)propanol (CAS: 34590-94-8)	OEL 8 hours	308 mg/m ³
	OEL 8 hours	50 ppm
	OEL 8 hours	270 mg/m ³
	OEL 8 hours	44,55 ppm
2-methoxy-1-methylethyl acetate (CAS: 108-65-6)	OEL 8 hours	275 mg/m ³
	OEL 8 hours	50 ppm
	OEL 15 minutes	550 mg/m ³
	OEL 15 minutes	100 ppm
ethylbenzene (CAS: 100-41-4)	OEL 8 hours	442 mg/m ³
	OEL 8 hours	100 ppm
	OEL 15 minutes	884 mg/m ³
	OEL 15 minutes	200 ppm

Notes

Skin.

European Union

Commission Directive 2006/15/EC

Substance name (component)	Type	Value
toluene (CAS: 108-88-3)	OEL 8 hours	192 mg/m ³
	OEL 8 hours	50 ppm
	OEL 15 minutes	384 mg/m ³
	OEL 15 minutes	100 ppm

Notes

Skin.

European Union

Commission Directive 91/322/EEC

Substance name (component)	Type	Value
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics	OEL 8 hours	1200 mg/m ³
	OEL 15 minutes	197 ppm
Technical xylene (mixed with ethylbenzene)	OEL 8 hours	442 mg/m ³
	OEL 8 hours	100 ppm
	OEL 15 minutes	884 mg/m ³
	OEL 15 minutes	200 ppm
	OEL 8 hours	221 mg/m ³
	OEL 8 hours	50 ppm
	OEL 15 minutes	442 mg/m ³
	OEL 15 minutes	100 ppm

European Union

Directive (EU) 2024/869 of the European Parliament and of the Council

Substance name (component)	Type	Value
m-tolylidene diisocyanate (CAS: 26471-62-5)	OEL 8 hours	10 µg/m ³

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date 25th January 2018
Revision date 03rd February 2025 Version 6.0

European Union

Directive (EU) 2024/869 of the European Parliament and of the Council

Substance name (component)	Type	Value
m-tolylidene diisocyanate (CAS: 26471-62-5)	OEL 15 minutes	20 µg/m ³

Notes

The substance can cause sensitisation of the skin and of the respiratory tract.

As NCO.

DNEL

(2-methoxymethylethoxy)propanol				
Workers / consumers	Route of exposure	Value	Effect	Source
Workers	Dermal	283 mg/kg bw/day	Chronic effects systemic	BL dodavatele
Workers	Inhalation	308 mg/m ³	Chronic effects systemic	BL dodavatele
Consumers	Dermal	121 mg/kg bw/day	Chronic effects systemic	BL dodavatele
Consumers	Inhalation	37.2 mg/m ³	Chronic effects systemic	BL dodavatele
Consumers	Oral	36 mg/kg bw/day	Chronic effects systemic	BL dodavatele

2-methoxy-1-methylethyl acetate				
Workers / consumers	Route of exposure	Value	Effect	Source
Workers	Inhalation	275 mg/m ³	Chronic effects systemic	BL dodavatele
Workers	Dermal	796 mg/kg bw/day	Chronic effects systemic	BL dodavatele
Consumers	Inhalation	33 mg/m ³	Chronic effects systemic	BL dodavatele
Consumers	Dermal	320 mg/kg bw/day	Chronic effects systemic	BL dodavatele
Consumers	Oral	36 mg/kg bw/day	Chronic effects systemic	BL dodavatele

2-methylpropan-1-ol				
Workers / consumers	Route of exposure	Value	Effect	Source
Workers	Inhalation	310 mg/m ³	Chronic effects local	BL dodavatele
Consumers	Inhalation	55 mg/m ³	Chronic effects local	BL dodavatele

aluminium powder (stabilised)				
Workers / consumers	Route of exposure	Value	Effect	Source
Workers	Inhalation	3.72 mg/m ³	Chronic effects systemic	echa
Consumers	Oral	3.95 mg/kg bw/day	Chronic effects systemic	echa

carbon black				
Workers / consumers	Route of exposure	Value	Effect	Source
Workers	Inhalation	2 mg/m ³	Acute effects local	BL dodavatele

Dibutyltin dilaurate				
Workers / consumers	Route of exposure	Value	Effect	Source
Workers	Inhalation	0.02 mg/m ³	Chronic effects systemic	ECHA
Workers	Dermal	0.43 mg/kg bw/day	Chronic effects systemic	ECHA
Consumers	Inhalation	0.0046 mg/m ³	Chronic effects systemic	ECHA
Consumers	Dermal	0.16 mg/kg bw/day	Chronic effects systemic	ECHA
Consumers	Oral	0.0031 mg/kg bw/day	Chronic effects systemic	ECHA

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date 25th January 2018
Revision date 03rd February 2025 Version 6.0

ethanol				
Workers / consumers	Route of exposure	Value	Effect	Source
Workers	Inhalation	950 mg/m ³	Chronic effects systemic	BL dodavatele
Workers	Dermal	343 mg/kg bw/day	Chronic effects systemic	BL dodavatele
Consumers	Inhalation	114 mg/m ³	Chronic effects systemic	echa
Consumers	Dermal	206 mg/kg bw/day	Chronic effects systemic	echa
Consumers	Oral	87 mg/kg bw/day	Chronic effects systemic	echa

ethylbenzene				
Workers / consumers	Route of exposure	Value	Effect	Source
Workers	Inhalation	77 mg/m ³	Chronic effects systemic	echa
Workers	Dermal	180 mg/kg bw/day	Chronic effects systemic	echa
Consumers	Inhalation	15 mg/m ³	Chronic effects systemic	echa
Consumers	Oral	1.6 mg/kg bw/day	Chronic effects systemic	echa

formaldehyde ...%				
Workers / consumers	Route of exposure	Value	Effect	Source
Workers	Inhalation	9 mg/m ³	Chronic effects systemic	echa
Workers	Dermal	240 mg/kg bw/day	Chronic effects systemic	echa
Consumers	Inhalation	3.2 mg/m ³	Chronic effects systemic	echa
Consumers	Dermal	102 mg/kg bw/day	Chronic effects systemic	echa
Consumers	Oral	4.1 mg/kg bw/day	Chronic effects systemic	echa

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics				
Workers / consumers	Route of exposure	Value	Effect	Source
Workers	Dermal	208 mg/kg bw/day	Chronic effects systemic	BL dodavatele
Workers	Inhalation	871 mg/m ³	Chronic effects systemic	BL dodavatele
Consumers	Dermal	125 mg/kg bw/day	Chronic effects systemic	BL dodavatele
Consumers	Inhalation	185 mg/m ³	Chronic effects systemic	BL dodavatele
Consumers	Oral	125 mg/m ³	Chronic effects systemic	BL dodavatele

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics				
Workers / consumers	Route of exposure	Value	Effect	Source
Workers (0)	Inhalation	871 mg/m ³	Chronic effects systemic	BL dodavatele
Workers (0)	Dermal	208 mg/kg bw/day	Chronic effects systemic	BL dodavatele
Consumers (0)	Inhalation	185 mg/m ³	Chronic effects systemic	BL dodavatele
Consumers (0)	Dermal	125 mg/kg bw/day	Chronic effects systemic	BL dodavatele
Consumers (0)	Oral	125 mg/kg bw/day	Chronic effects systemic	BL dodavatele

Iron hydroxide oxide yellow				
Workers / consumers	Route of exposure	Value	Effect	Source
Workers	Inhalation	10 mg/m ³	Acute effects systemic	BL dodavatele
Workers	Inhalation	10 mg/m ³	Acute effects local	BL dodavatele

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date 25th January 2018
Revision date 03rd February 2025 Version 6.0

m-tolylidene diisocyanate				
Workers / consumers	Route of exposure	Value	Effect	Source
Workers	Inhalation	0.035 mg/m ³	Chronic effects systemic	BL dodavatele
Workers	Inhalation	0.14 mg/m ³	Acute effects systemic	BL dodavatele
Workers	Inhalation	0.035 mg/m ³	Chronic effects local	BL dodavatele
Workers	Inhalation	0.14 mg/m ³	Acute effects local	BL dodavatele

n-butyl acetate				
Workers / consumers	Route of exposure	Value	Effect	Source
Workers	Inhalation	600 mg/m ³	Acute effects local	BL dodavatele
Consumers	Inhalation	300 mg/m ³	Acute effects local	BL dodavatele
Workers	Inhalation	300 mg/m ³	Chronic effects local	BL dodavatele
Consumers	Inhalation	35.7 mg/m ³	Chronic effects local	BL dodavatele
Workers	Dermal	11 mg/kg	Chronic effects systemic	BL dodavatele
Workers	Dermal	11 mg/kg	Acute effects systemic	BL dodavatele
Consumers	Dermal	6 mg/kg	Chronic effects systemic	BL dodavatele
Consumers	Dermal	6 mg/kg	Acute effects systemic	BL dodavatele
Consumers	Oral	2 mg/kg	Chronic effects systemic	BL dodavatele
Consumers	Oral	2 mg/kg	Acute effects systemic	BL dodavatele

neodecanoic acid, cobalt salt				
Workers / consumers	Route of exposure	Value	Effect	Source
Workers	Inhalation	0.273 mg/m ³	Chronic effects local	BL dodavatele
Consumers	Inhalation	0.043 mg/m ³	Chronic effects local	BL dodavatele
Consumers	Oral	0.032 mg/kg bw/day	Chronic effects systemic	BL dodavatele

Silica, amorphous				
Workers / consumers	Route of exposure	Value	Effect	Source
Workers	Inhalation	4 mg/m ³	Chronic effects systemic	BL dodavatele

Technical xylene (mixed with ethylbenzene)				
Workers / consumers	Route of exposure	Value	Effect	Source
Workers	Inhalation	77 mg/m ³	Chronic effects systemic	ECHA
Workers	Inhalation	289 mg/m ³	Acute effects local	ECHA
Workers	Dermal	180 mg/kg bw/day	Chronic effects systemic	ECHA
Consumers	Inhalation	14.8 mg/m ³	Chronic effects systemic	ECHA
Consumers	Dermal	108 mg/kg bw/day	Chronic effects systemic	ECHA
Consumers	Oral	1.6 mg/kg bw/day	Chronic effects systemic	ECHA

titanium dioxide				
Workers / consumers	Route of exposure	Value	Effect	Source
	Inhalation	10 mg/m ³	Chronic effects local	BL dodavatele

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date 25th January 2018
Revision date 03rd February 2025 Version 6.0

toluene				
Workers / consumers	Route of exposure	Value	Effect	Source
Workers	Inhalation	192 mg/m ³	Chronic effects systemic	BL dodavatele
Workers	Inhalation	192 mg/m ³	Chronic effects local	BL dodavatele
Workers	Inhalation	384 mg/m ³	Acute effects systemic	BL dodavatele
Workers	Inhalation	384 mg/m ³	Acute effects local	BL dodavatele
Workers	Dermal	384 mg/kg bw/day	Chronic effects systemic	BL dodavatele
Consumers	Inhalation	226 mg/m ³	Acute effects systemic	BL dodavatele
Consumers	Inhalation	226 mg/m ³	Acute effects local	BL dodavatele
Consumers	Dermal	226 mg/kg bw/day	Chronic effects systemic	BL dodavatele
Consumers	Inhalation	56.5 mg/m ³	Chronic effects systemic	BL dodavatele
Consumers	Oral	8.13 mg/kg bw/day	Chronic effects systemic	BL dodavatele
Consumers	Inhalation	56.5 mg/m ³	Chronic effects local	BL dodavatele

PNEC

(2-methoxymethylethoxy)propanol		
Route of exposure	Value	Source
Freshwater environment	19 mg/l	BL dodavatele
Marine water	1.9 mg/l	BL dodavatele
Water (intermittent release)	190 mg/l	BL dodavatele
Microorganisms in sewage treatment	4168 mg/l	BL dodavatele
Freshwater sediment	70.2 mg/kg of dry substance	BL dodavatele
Sea sediments	7.02 mg/kg of dry substance	BL dodavatele
Soil (agricultural)	2.74 mg/kg of dry substance	BL dodavatele

2-methoxy-1-methylethyl acetate		
Route of exposure	Value	Source
Freshwater environment	0.635 mg/l	BL dodavatele
Marine water	0.0635 mg/l	BL dodavatele
Microorganisms in sewage treatment	100 mg/l	BL dodavatele
Freshwater sediment	3.29 mg/kg of dry substance of sediment	BL dodavatele
Sea sediments	0.329 mg/kg of dry substance of sediment	BL dodavatele
Soil (agricultural)	0.29 mg/kg of dry substance of soil	BL dodavatele

2-methylpropan-1-ol		
Route of exposure	Value	Source
Freshwater environment	0.4 mg/l	BL dodavatele
Marine water	0.04 mg/l	BL dodavatele
Water (intermittent release)	11 mg/l	BL dodavatele
Microorganisms in sewage treatment	10 mg/l	BL dodavatele
Freshwater sediment	1.52 mg/kg of dry substance of sediment	BL dodavatele
Sea sediments	0.152 mg/kg of dry substance of sediment	BL dodavatele
Soil (agricultural)	0.0699 mg/kg of dry substance of soil	BL dodavatele

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date 25th January 2018
Revision date 03rd February 2025 Version 6.0

aluminium powder (stabilised)		
Route of exposure	Value	Source
Microorganisms in sewage treatment	20 mg/l	echa

carbon black		
Route of exposure	Value	Source
Freshwater environment	5 mg/l	BL dodavatele
Marine water	5 mg/l	BL dodavatele

Dibutyltin dilaurate		
Route of exposure	Value	Source
Freshwater environment	0.463 µg/l	ECHA
Marine water	0.0463 µg/l	ECHA
Microorganisms in sewage treatment	100 mg/l	ECHA
Food chain	0.2 mg/kg of food	ECHA

ethanol		
Route of exposure	Value	Source
Freshwater environment	0.96 mg/l	BL dodavatele
Marine water	0.79 mg/l	BL dodavatele
Water (intermittent release)	2.75 mg/l	echa
Microorganisms in sewage treatment	580 mg/l	BL dodavatele
Freshwater sediment	3.6 mg/kg of dry substance of sediment	echa
Sea sediments	2.9 mg/kg of dry substance of sediment	echa
Soil (agricultural)	0.63 mg/kg	BL dodavatele
Food chain	380-720 mg/kg of food	echa

ethylbenzene		
Route of exposure	Value	Source
Freshwater environment	100 µg/l	echa
Marine water	10-100 µg/l	echa
Water (intermittent release)	100 µg/l	echa
Microorganisms in sewage treatment	9.6 mg/l	echa
Freshwater sediment	13.7 mg/kg of dry substance of sediment	echa
Sea sediments	1.37 mg/kg of dry substance of sediment	echa
Soil (agricultural)	2.68 mg/kg of dry substance of soil	echa
Food chain	20 mg/kg of food	echa

formaldehyde ...%		
Route of exposure	Value	Source
Freshwater environment	440 µg/l	echa
Marine water	440 µg/l	echa
Water (intermittent release)	4.44 mg/l	echa
Microorganisms in sewage treatment	190 µg/l	echa

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date 25th January 2018
Revision date 03rd February 2025 Version 6.0

formaldehyde ...%

Route of exposure	Value	Source
Freshwater sediment	2.3 mg/kg of dry substance of sediment	echa
Sea sediments	2.3 mg/kg of dry substance of sediment	echa
Soil (agricultural)	200 µg/kg	echa

m-tolylidene diisocyanate

Route of exposure	Value	Source
Freshwater environment	0.013 mg/l	BL dodavatele
Marine water	0.00125 mg/l	BL dodavatele
Microorganisms in sewage treatment	>1 mg/l	BL dodavatele
Soil (agricultural)	>1 mg/kg	BL dodavatele

n-butyl acetate

Route of exposure	Value	Source
Freshwater environment	0.18 mg/l	BL dodavatele
Marine water	0.018 mg/l	BL dodavatele
Water (intermittent release)	0.36 mg/l	BL dodavatele
Microorganisms in sewage treatment	35.6 mg/l	BL dodavatele
Freshwater sediment	0.981 mg/kg	BL dodavatele
Sea sediments	0.0981 mg/kg	BL dodavatele
Soil (agricultural)	0.0903 mg/kg	BL dodavatele

neodecanoic acid, cobalt salt

Route of exposure	Value	Source
Freshwater environment	0.62 µg/l	BL dodvatele
Marine water	2.36 µg/l	BL dodvatele
Microorganisms in sewage treatment	0.37 mg/l	BL dodvatele
Freshwater sediment	53.8 mg/kg of dry substance of sediment	BL dodavatele
Sea sediments	69.8 mg/kg of dry substance of sediment	BL dodavatele
Soil (agricultural)	10.9 mg/kg of dry substance	BL dodavatele

Technical xylene (mixed with ethylbenzene)

Route of exposure	Value	Source
Freshwater environment	327 µg/l	ECHA
Marine water	327 µg/l	ECHA
Soil (agricultural)	2.31 mg/kg of dry substance of soil	ECHA
Food chain	327 µg/l	ECHA
Microorganisms in sewage treatment	6.58 mg/l	EHCA
Sea sediments	12.46 mg/kg of dry substance of sediment	ECHA
Freshwater sediment	12.46 mg/kg of dry substance of sediment	ECHA

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date 25th January 2018
Revision date 03rd February 2025 Version 6.0

titanium dioxide		
Route of exposure	Value	Source
Freshwater environment	0.127 mg/l	BL dodavatele
Marine water	1 mg/l	BL dodavatele
Water (intermittent release)	0.61 mg/l	BL dodavatele
Freshwater sediment	1000 mg/kg	BL dodavatele
Sea sediments	100 mg/kg	BL dodavatele
Soil (agricultural)	100 mg/kg	BL dodavatele
Microorganisms in sewage treatment	100 mg/l	BL dodavatele
Food chain	1667 mg/kg	BL dodavatele

toluene		
Route of exposure	Value	Source
Freshwater environment	0.68 mg/l	BL dodavatele
Marine water	0.68 mg/l	BL dodavatele
Water (intermittent release)	0.68 mg/l	BL dodavatele
Microorganisms in sewage treatment	13.61 mg/l	echa
Freshwater sediment	16.39 mg/kg of dry substance of sediment	BL dodavatele
Sea sediments	16.39 mg/kg of dry substance of sediment	BL dodavatele
Soil (agricultural)	2.89 mg/kg of dry substance of soil	BL dodavatele

8.2. Exposure controls

Follow the usual measures intended for health protection at work and especially for good ventilation. This can be achieved only by local suction or efficient general ventilation. If exposure limits cannot be observed in this mode, suitable protection of airways must be used. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

Eye/face protection

It is not needed.

Skin protection

Hand protection: Protective gloves resistant to the product (EN 374). Gloves material: Nitrile rubber (EN 374). Recommended material thickness: min. 0.4 mm. Penetration time of glove material $\geq$ 480 minutes (EN 374). No tests have been carried out, the durability of the gloves should be tested before use. Find out the exact penetration time of the material from the glove manufacturer and follow it. Contaminated skin should be washed thoroughly.

Respiratory protection

Halfmask with a filter against organic vapours or a self-contained breathing apparatus as appropriate if exposure limit values of substances are exceeded or in a poorly ventilated environment.

Thermal hazard

Not available.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2.

More information

Exposure scenario is attached to the Safety Data Sheet.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	liquid
Colour	white, black, red, brown, blue, orange, silver, grey, green, yellow, mixture containing generic product identifier "colorant", by shades
Odour	after organic solvents
Melting point/freezing point	data not available

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date	25th January 2018	Version	6.0
Revision date	03rd February 2025		

(2-methoxymethylethoxy)propanol (CAS: 34590-94-8)	-83 °C (BL dodavatele)
2-methoxy-1-methylethyl acetate (CAS: 108-65-6)	-66 °C (BL dodavatele)
2-methylpropan-1-ol (CAS: 78-83-1)	<-90 °C (BL dodavatele)
aluminium powder (stabilised) (CAS: 7429-90-5)	660 °C (ECHA)
carbon black (CAS: 1333-86-4)	3652-3697 °C (BL dodavatele)
Dibutyltin dilaurate (CAS: 77-58-7)	16-18 °C (BL dodavatele)
diiron trioxide (CAS: 1309-37-1)	>1000 °C (BL dodavatele)
ethanol (CAS: 64-17-5)	-114.15 °C (BL dodavatele)
ethylbenzene (CAS: 100-41-4)	-95.15--94.9 °C (ECHA)
hydrocarbons, C10-C13, n-alkanes, isolakanes, cyclics, <2% aromatics	<-20 °C (BL dodavatele)
hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclic, <2% aromatics	-45 °C (ECHA)
Iron hydroxide oxide yellow (CAS: 51274-00-1)	>1000 °C (BL dodavatele)
m-tolylidene diisocyanate (CAS: 26471-62-5)	9.5 °C (BL dodavatele)
n-butyl acetate (CAS: 123-86-4)	-78 °C (BL dodavatele)
Silica, amorphous (CAS: 7631-86-9)	1700 °C (BL dodavatele)
talc (Mg3H2(SiO3)4) (CAS: 14807-96-6)	>1300 °C (BL dodavatele)
Technical xylene (mixed with ethylbenzene)	-94.96-13.2 °C (BL dodavatele)
titanium dioxide (CAS: 13463-67-7)	>1560 °C (BL dodavatele)
toluene (CAS: 108-88-3)	-95 °C (BL dodavatele)
Boiling point or initial boiling point and boiling range	data not available
(2-methoxymethylethoxy)propanol (CAS: 34590-94-8)	189.6 °C (BL dodavatele)
2-methoxy-1-methylethyl acetate (CAS: 108-65-6)	145.8 °C (BL dodavatele)
2-methylpropan-1-ol (CAS: 78-83-1)	108 °C (BL dodavatele)
aluminium powder (stabilised) (CAS: 7429-90-5)	2450 °C (ECHA)
Dibutyltin dilaurate (CAS: 77-58-7)	>200 °C (BL dodavatele)
ethanol (CAS: 64-17-5)	78.3 °C (BL dodavatele)
ethylbenzene (CAS: 100-41-4)	136.1 °C (ECHA)
hydrocarbons, C10-C13, n-alkanes, isolakanes, cyclics, <2% aromatics	160-245 °C (BL dodavatele)
hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclic, <2% aromatics	203-238 °C (BL dodavatele)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics	154-193 °C (BL dodavatele)
m-tolylidene diisocyanate (CAS: 26471-62-5)	252-254 °C (BL dodavatele)
n-butyl acetate (CAS: 123-86-4)	124-126.5 °C (BL dodavatele)
solvent naphtha (petroleum), medium aliph. (CAS: 64742-88-7)	146-299 °C (ECHA)
Technical xylene (mixed with ethylbenzene)	136.2-144.5 °C (BL dodavatele)
titanium dioxide (CAS: 13463-67-7)	3000 °C (BL dodavatele)
toluene (CAS: 108-88-3)	110.6 °C (BL dodavatele)
Flammability	Flammable liquid of risk class II (ČSN 65 0201)
ethanol (CAS: 64-17-5)	inflammable (BL dodavatele)
n-butyl acetate (CAS: 123-86-4)	inflammable (odvozeno od bodu vzplanutí)
Technical xylene (mixed with ethylbenzene)	inflammable (BL dodavatele)
toluene (CAS: 108-88-3)	Flammable liquid of risk class II (BL dodavatele)
Lower and upper explosion limit	
bottom	0.6 % (for Hydrocarbons, C10-C13, alkanes, isoalkanes, cyclics, <2% aromatics)
(2-methoxymethylethoxy)propanol (CAS: 34590-94-8)	1.1 % (BL dodavatele)
2-methoxy-1-methylethyl acetate (CAS: 108-65-6)	1.5 % (BL dodavatele)
2-methylpropan-1-ol (CAS: 78-83-1)	1.7 % (BL dodavatele)
ethanol (CAS: 64-17-5)	3.3 % (BL dodavatele)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics	0.7 % (BL dodavatele)

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date	25th January 2018	Version	6.0
Revision date	03rd February 2025		

m-tolylidene diisocyanate (CAS: 26471-62-5)	0.9 % (BL dodavatele)
n-butyl acetate (CAS: 123-86-4)	1.2 % (literatura)
Technical xylene (mixed with ethylbenzene)	0.8 % (BL dodavatele)
toluene (CAS: 108-88-3)	1.3 % (BL dodavatele)
upper	50 % (for butan-2-one-oxime)
(2-methoxymethylethoxy)propanol (CAS: 34590-94-8)	14 % (BL dodavatele)
2-methoxy-1-methylethyl acetate (CAS: 108-65-6)	7.0 % (BL dodavatele)
2-methylpropan-1-ol (CAS: 78-83-1)	10.9 % (BL dodavatele)
ethanol (CAS: 64-17-5)	19 % (BL dodavatele)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics	6 % (BL dodavatele)
m-tolylidene diisocyanate (CAS: 26471-62-5)	9.5 % (BL dodavatele)
n-butyl acetate (CAS: 123-86-4)	7.6 % (literatura)
Technical xylene (mixed with ethylbenzene)	7 % (BL dodavatele)
toluene (CAS: 108-88-3)	6.7 % (BL dodavatele)
Flash point	33 °C (ČSN 67 3015)
(2-methoxymethylethoxy)propanol (CAS: 34590-94-8)	75 °C (BL dodavatele)
2-methoxy-1-methylethyl acetate (CAS: 108-65-6)	45 °C (BL dodavatele)
2-methylpropan-1-ol (CAS: 78-83-1)	31 °C (BL dodavatele)
carbon black (CAS: 1333-86-4)	>600 °C (BL dodavatele)
Dibutyltin dilaurate (CAS: 77-58-7)	>180 °C (BL dodavatele)
ethanol (CAS: 64-17-5)	12.85 °C (BL dodavatele)
ethylbenzene (CAS: 100-41-4)	22.85 °C (ECHA)
hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	>61 °C (BL dodavatele)
hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclic, <2% aromatics	79 °C (BL dodavatele)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics	41 °C (BL dodavatele)
m-tolylidene diisocyanate (CAS: 26471-62-5)	132 °C (BL dodavatele)
n-butyl acetate (CAS: 123-86-4)	27 °C (BL dodavatele)
solvent naphtha (petroleum), medium aliph. (CAS: 64742-88-7)	29-70 °C (ECHA)
Technical xylene (mixed with ethylbenzene)	18-32 °C (BL dodavatele)
toluene (CAS: 108-88-3)	4.4 °C (BL dodavatele)
Auto-ignition temperature	data not available
(2-methoxymethylethoxy)propanol (CAS: 34590-94-8)	207 °C (BL dodavatele)
2-methoxy-1-methylethyl acetate (CAS: 108-65-6)	333 °C (BL dodavatele)
2-methylpropan-1-ol (CAS: 78-83-1)	400 °C (BL dodavatele)
carbon black (CAS: 1333-86-4)	>140 °C (BL dodavatele)
ethanol (CAS: 64-17-5)	362.85 °C (BL dodavatele)
ethylbenzene (CAS: 100-41-4)	430-432 °C (ECHA)
hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	>200 °C (BL dodavatele)
hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclic, <2% aromatics	200 °C (ECHA)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics	237 °C (BL dodavatele)
m-tolylidene diisocyanate (CAS: 26471-62-5)	>595 °C (BL dodavatele)
n-butyl acetate (CAS: 123-86-4)	415 °C (BL dodavatele)
solvent naphtha (petroleum), medium aliph. (CAS: 64742-88-7)	220-250 °C (ECHA)
Technical xylene (mixed with ethylbenzene)	432-528 °C (BL dodavatele)
toluene (CAS: 108-88-3)	480 °C (BL dodavatele)
Decomposition temperature	data not available
Iron hydroxide oxide yellow (CAS: 51274-00-1)	180 °C (BL dodavatele)

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date	25th January 2018	Version	6.0
Revision date	03rd February 2025		

talc (Mg ₃ H ₂ (SiO ₃) ₄) (CAS: 14807-96-6)	>1000 °C (BL dodavatele)
pH	non-soluble (in water)
2-methylpropan-1-ol (CAS: 78-83-1)	7 (undiluted at 20 °C) (BL dodavatele)
carbon black (CAS: 1333-86-4)	6-11 (3% solution) (BL dodavatele)
diiron trioxide (CAS: 1309-37-1)	5-8 (5% solution) (BL dodavatele)
ethanol (CAS: 64-17-5)	7 (undiluted at 20 °C) (BL dodavatele)
Iron hydroxide oxide yellow (CAS: 51274-00-1)	4.5-7.5 (0.005% solution) (BL dodavatele)
talc (Mg ₃ H ₂ (SiO ₃) ₄) (CAS: 14807-96-6)	9-9.5 (10% solution) (BL dodavatele)
Kinematic viscosity	>20.5 mm ² /s at 40 °C
	data not available
(2-methoxymethylethoxy)propanol (CAS: 34590-94-8)	4.55 mm ² /s at 20 °C (BL dodavatele)
2-methoxy-1-methylethyl acetate (CAS: 108-65-6)	1.23 mm ² /s at 40 °C (BL dodavatele)
hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclic, <2% aromatics	2.4 mm ² /s (ECHA)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics	1.02 mm ² /s at 40 °C (BL dodavatele)
	1.35 mm ² /s at 20 °C (BL dodavatele)
n-butyl acetate (CAS: 123-86-4)	0.83 mm ² /s at 20 °C (BL dodavatele)
Solubility in water	not miscible
(2-methoxymethylethoxy)propanol (CAS: 34590-94-8)	>1000 g/l (25 °C) (BL dodavatele)
2-methoxy-1-methylethyl acetate (CAS: 108-65-6)	247 g/l (BL dodavatele)
2-methylpropan-1-ol (CAS: 78-83-1)	70 g/l (20 °C) (BL dodavatele)
aluminium powder (stabilised) (CAS: 7429-90-5)	20 µg/l při 20°C (ECHA)
ethanol (CAS: 64-17-5)	789 000 mg/l při 20°C (BL dodavatele)
ethylbenzene (CAS: 100-41-4)	200 mg/l při 25°C (ECHA)
formaldehyde ...% (CAS: 50-00-0)	550 g/l při 20°C (ECHA)
Iron hydroxide oxide yellow (CAS: 51274-00-1)	insoluble (BL dodavatele)
n-butyl acetate (CAS: 123-86-4)	5.3 g/l při 20 °C (pH 6) (BL dodavatele)
Silica, amorphous (CAS: 7631-86-9)	>1 mg/l (BL dodavatele)
Technical xylene (mixed with ethylbenzene)	146-190.7 mg/l při 25 °C (BL dodavatele)
titanium dioxide (CAS: 13463-67-7)	soluble (BL dodavatele)
toluene (CAS: 108-88-3)	573-587 mg/l při 25°C (BL dodavatele)
Solubility in fats	data not available
Partition coefficient n-octanol/water (log value)	LogPow -0.35 to 6 (range of substances contained)
2-methylpropan-1-ol (CAS: 78-83-1)	1 (BL dodavatele)
ethylbenzene (CAS: 100-41-4)	3.03-3.6 (ECHA)
formaldehyde ...% (CAS: 50-00-0)	0.35 (ECHA)
Vapour pressure	0.067 hPa to 57.26 hPa at 20 °C (range of substances contained)
(2-methoxymethylethoxy)propanol (CAS: 34590-94-8)	0.037 kPa at 20 °C (BL dodavatele)
2-methoxy-1-methylethyl acetate (CAS: 108-65-6)	355 at 20 °C (BL dodavatele)
2-methylpropan-1-ol (CAS: 78-83-1)	16 hPa at 20 °C (BL dodavatele)
aluminium powder (stabilised) (CAS: 7429-90-5)	0.13-1300 Pa at 974 °C (ECHA)
Dibutyltin dilaurate (CAS: 77-58-7)	0.00077 hPa at 25 °C (BL dodavatele)
ethanol (CAS: 64-17-5)	57.26 hPa at 19.65 °C (BL dodavatele)
ethylbenzene (CAS: 100-41-4)	9.52-10.1 hPa at 20 °C (ECHA)
hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	<0.1 kPa at 20 °C (BL dodavatele)
hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclic, <2% aromatics	20 Pa at 20 °C (ECHA)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics	20 hPa at 20 °C (BL dodavatele)
m-tolylidene diisocyanate (CAS: 26471-62-5)	<7 hPa at 20 °C (BL dodavatele)
n-butyl acetate (CAS: 123-86-4)	12-21 at 20 °C (literatura)

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date	25th January 2018	Version	6.0
Revision date	03rd February 2025		

solvent naphtha (petroleum), medium aliph. (CAS: 64742-88-7)	10-37 hPa at 38 °C (ECHA)
Technical xylene (mixed with ethylbenzene)	650-944 Pa (BL dodavatele)
toluene (CAS: 108-88-3)	3088.9 Pa at 21.1 °C (BL dodavatele)
Density and/or relative density	
Density	0.94-1.12 g/cm ³ at 20 °C (ČSN EN ISO 2811-2)
2-methoxy-1-methylethyl acetate (CAS: 108-65-6)	0.964 g/cm ³ at 25 °C (BL dodavatele)
2-methylpropan-1-ol (CAS: 78-83-1)	0.8017 g/cm ³ at 20 °C (BL dodavatele)
aluminium powder (stabilised) (CAS: 7429-90-5)	2.7 g/cm ³ at 20 °C (ECHA)
carbon black (CAS: 1333-86-4)	1.7-1.9 g/cm ³ at 20 °C (BL dodavatele)
Dibutyltin dilaurate (CAS: 77-58-7)	1.03 g/cm ³ at 20 °C (BL dodavatele)
ethanol (CAS: 64-17-5)	0.7844 g/cm ³ at 25 °C (BL dodavatele)
ethylbenzene (CAS: 100-41-4)	0.867-0.868 g/cm ³ at 20 °C (ECHA)
hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	0.751-0.851 g/cm ³ at 15 °C (BL dodavatele)
hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclic, <2% aromatics	0.81 g/cm ³ at 15 °C (ECHA)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics	0.78 g/cm ³ at 15 °C (BL dodavatele)
Iron hydroxide oxide yellow (CAS: 51274-00-1)	4.1 g/cm ³ at 20 °C (BL dodavatele)
m-tolylidene diisocyanate (CAS: 26471-62-5)	1.22 g/cm ³ at 20 °C (BL dodavatele)
n-butyl acetate (CAS: 123-86-4)	0.8812 g/cm ³ at 20 °C (BL dodavatele)
Silica, amorphous (CAS: 7631-86-9)	2.2 g/cm ³ at 20 °C (BL dodavatele)
solvent naphtha (petroleum), medium aliph. (CAS: 64742-88-7)	0.77-0.85 g/cm ³ at 15 °C (ECHA)
talc (Mg ₃ H ₂ (SiO ₃) ₄) (CAS: 14807-96-6)	2.58-2.83 g/cm ³ (BL dodavatele)
Technical xylene (mixed with ethylbenzene)	0.862-0.88 g/cm ³ at 25 °C (BL dodavatele)
toluene (CAS: 108-88-3)	0.866 g/cm ³ at 20 °C (BL dodavatele)
Relative vapour density	data not available
Particle characteristics	data not available
Form	liquid, Medium-viscous liquid without mechanical impurities, shell formation and stirrable sediment allowed (manufacturer's methodology B5/TD1-17 (ČSN EN ISO 1513))

9.2. Other information

Evaporation rate	data not available
Vapour density	> 1 (air = 1)
Combustion temperature	44 °C (ČSN 65 6212)
Ignition temperature	235 °C (ČSN 33 0371)
Content of organic solvents (VOC)	0.303 kg/kg (calculation)
Total organic carbon (TOC)	0.254 kg/kg (calculation)
Solid content (dry matter)	≥38 % weight (manufacturer's methodology B5/TD1-12B (ČSN EN ISO 3251))
VOC limit value	cat. A (d) SB: 300 g/l
Max. VOC content in the product in its ready to use condition	292 g/l (calculation)
Calorific value: 26.78 MJ/kg (ČSN 65 6169); Heat of combustion: 28.52 MJ/kg (ČSN 65 6169); Flammability - temperature class: T3 (ČSN 33 0371).	

SECTION 10: Stability and reactivity

10.1. Reactivity

not available

10.2. Chemical stability

The product is stable under normal conditions.

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date	25th January 2018	Version	6.0
Revision date	03rd February 2025		

10.3. Possibility of hazardous reactions

Unknown.

10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost.

10.5. Incompatible materials

Protect against strong acids, bases and oxidizing agents.

10.6. Hazardous decomposition products

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Inhalation of solvent vapors above values exceeding exposure limits for working environment may result in acute inhalation poisoning, depending on the level of concentration and exposure time. No toxicological data is available for the mixture.

Acute toxicity

Based on the available data, the criteria for classification of the mixture are not met.

SU2013 Synthetic top color UNIVERSAL								
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination	Source
Oral	ATE		52931 mg/kg				Calculation of value	
Dermal	ATE		598357 mg/kg				Calculation of value	
Inhalation (vapor)	ATE		2584 mg/l				Calculation of value	

(2-methoxymethylethoxy)propanol								
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination	Source
Oral	LD ₅₀	OECD 401	>5000 mg/kg		Rat			BL dodavat ele
Dermal	LD ₅₀	OECD 402	9510 mg/kg		Rabbit			BL dodavat ele
Inhalation (vapor)	LC ₅₀		275 ppm	7 hours	Rat			BL dodavat ele
Inhalation	LC ₅₀	OECD 403	3.35 mg/l	7 hours	Rat (Rattus norvegicus)			BL dodavat ele
Oral	ATE		5001 mg/kg bw					
Inhalation (vapor)	ATE		3.35 mg/l					
Dermal	ATE		9510 mg/kg bw					

2-methoxy-1-methylethyl acetate								
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination	Source
Oral	LD ₅₀	OECD 401	6190 mg/kg		Rat (Rattus norvegicus)	F/M		BL dodavat ele

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date
Revision date

25th January 2018
03rd February 2025

Version

6.0

2-methoxy-1-methylethyl acetate								
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination	Source
Inhalation	LC ₀		>23.5 mg/l	6 hours	Rat (Rattus norvegicus)			BL dodavat ele
Dermal	LD ₅₀	OECD 402	>5000 mg/kg		Rat (Rattus norvegicus)			BL dodavat ele
Inhalation (gases)	LC ₅₀	OECD 403	>2000 ppm	3 hours	Rat (Rattus norvegicus)	M		BL dodavat ele

2-methylpropan-1-ol								
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination	Source
Oral	LD ₅₀	OECD 401	>2000 mg/kg		Rat (Rattus norvegicus)			BL dodavat ele
Inhalation (vapor)	LC ₅₀		>18.18 mg/l of air	14 days	Rat (Rattus norvegicus)			BL dodavat ele
Dermal	LD ₅₀	OECD 402	>2000 mg/kg		Rabbit			BL dodavat ele

aluminium powder (stabilised)								
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination	Source
Oral	LD ₅₀		15900 mg/kg bw		Rat			echa
Inhalation	LC ₅₀		888 mg/m ³ of air	4 hours	Rat			echa

carbon black								
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination	Source
Oral	LD ₅₀	OECD 401	>8000 mg/kg		Rat			BL dodavat ele
Inhalation	LC ₀		4.6 mg/m ³	4 hours	Rat			BL dodavat ele
Inhalation	NOAEL		1.1 mg/m ³	13 weeks	Rat			BL dodavat ele

Dibutyltin dilaurate								
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination	Source
Oral	LD ₅₀		2071 mg/kg bw		Rat (Rattus norvegicus)			ECHA
Dermal	LD ₅₀		2000 mg/kg bw		Rat (Rattus norvegicus)			ECHA

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date
Revision date

25th January 2018
03rd February 2025

Version

6.0

diiron trioxide

Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination	Source
Oral	LD ₅₀		>5000 mg/kg		Rat			BL dodavatele

ethanol

Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination	Source
Oral	LD ₅₀		7060 mg/kg		Rat			BL dodavatele
Inhalation	LC ₅₀		117000-125000 mg/m ³	4 hours	Rat (Rattus norvegicus)			BL dodavatele
Dermal	LD ₅₀		>20000 mg/kg		Rabbit			BL dodavatele

ethylbenzene

Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination	Source
Oral	LD ₅₀		3500 mg/kg		Rat			
Dermal	LD ₅₀		17800 mg/kg		Rat			
Inhalation (vapor)	LC ₅₀		17400 mg/kg	4 hours	Rat			

formaldehyde ...%

Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination	Source
Oral	LD ₅₀	OECD 401	460 mg/kg		Rat (Rattus norvegicus)	M		BL dodavatele
Inhalation (gases)	LC ₅₀	OECD 403	<463 ppm	4 hours	Rat (Rattus norvegicus)	F/M		BL dodavatele
Inhalation (gases)	ATE		100 ppm					
Oral	ATE		500 mg/kg bw					

hydrocarbons, C10-C13, n-alanes, isolakanes, cyclics, <2% aromatics

Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination	Source
	EC ₅₀		5 mg/l of air	72 hours	Rat			ECHA
Dermal	LD ₅₀	OECD 402	>5000 mg/kg	72 hours	Rabbit			BL dodavatele
Inhalation (vapor)	LC ₅₀	OECD 403	>5000 mg/m ³	4 hours	Rat			BL dodavatele
Oral	LD ₅₀	OECD 401	>5000 mg/kg		Rat			BL dodavatele

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date
Revision date

25th January 2018
03rd February 2025

Version

6.0

hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclic, <2% aromatics

Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination	Source
Inhalation (vapor)	LC ₅₀	OECD 403	>5000 mg/m ³	8 hours	Rat			
Dermal	LD ₅₀	OECD 402	>5000 mg/kg		Rabbit			BL-dodavatel
Oral	LD ₅₀	OECD 401	>5000 mg/kg					

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics

Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination	Source
Oral	LD ₅₀	OECD 401	>5000 mg/kg		Rat			BL dodavatel
Inhalation	LC ₅₀	OECD 403	5000 mg/m ³	4 hours	Rat			BL dodavatel
Dermal	LD ₅₀	OECD 402	>5000 mg/kg		Rabbit			BL dodavatel

Iron hydroxide oxide yellow

Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination	Source
Oral	LD ₅₀		>10000 mg/kg		Rat			BL dodavatel
Inhalation (dust/mist)	LD ₅₀		>195 mg/m ³	2 weeks	Rat			BL dodavatel

m-tolylidene diisocyanate

Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination	Source
Oral	LD ₅₀	OECD 401	5110 mg/kg		Rat (Rattus norvegicus)	M		BL dodavatel
Oral	LD ₅₀	OECD 401	4130 mg/kg		Rat (Rattus norvegicus)	F		BL dodavatel
Dermal	LD ₅₀	OECD 402	>9400 mg/kg		Rabbit	F/M		BL dodavatel
Inhalation	LC ₅₀	OECD 403	0.107 mg/l	4 hours	Rat (Rattus norvegicus)	F/M		BL dodavatel
Inhalation	LC ₅₀	OECD 403	0.47 mg/l	1 hour	Rat (Rattus norvegicus)	F/M		BL dodavatel

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date
Revision date

25th January 2018
03rd February 2025

Version

6.0

n-butyl acetate

Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination	Source
Oral	LD ₅₀		10736 mg/kg		Rat (Rattus norvegicus)			BL dodavatele
Inhalation	LC ₅₀	OECD 403	>21.1 mg/l	4 hours	Rat (Rattus norvegicus)			BL dodavatele
Dermal	LD ₅₀		>14000 mg/kg		Rabbit			BL dodavatele
Inhalation	LC ₀		>38.32 mg/l	6 hours	Rat (Rattus norvegicus)			BL dodavatele

neodecanoic acid, cobalt salt

Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination	Source
Oral	LD ₅₀	OECD 425	1098 mg/kg		Rat (Rattus norvegicus)	F		BL dodavatele
Dermal	LD ₅₀	OECD 402	>5000 mg/kg		Rat (Rattus norvegicus)	F/M		BL dodavatele

Silica, amorphous

Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination	Source
Dermal	LD ₅₀		>5000 mg/kg		Rabbit			BL dodavatele
Oral	LD ₅₀	OECD 401	>5000 mg/kg		Rat			BL dodavatele

solvent naphtha (petroleum), medium aliph.

Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination	Source
Oral	LD ₅₀		5000 mg/kg		Rat			ECHA
Inhalation	LC ₅₀		5.28 mg/l	4 hours	Rat			ECHA
Dermal	LD ₅₀		2000 mg/kg		Rabbit			ECHA
Oral	NOAEL		750 mg/kg bw/day		Rat			ECHA
Inhalation	NOAEL		1 mg/l of air		Rat			ECHA
Inhalation	NOAEL		1 mg/l of air		Mouse			ECHA
Inhalation	LOAEL		500 mg/m ³ of air		Rat			ECHA
Inhalation	NOAEC		24 mg/m ³ of air		Rat			ECHA

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date 25th January 2018
Revision date 03rd February 2025 Version 6.0

Technical xylene (mixed with ethylbenzene)

Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination	Source
Oral	LD ₅₀		3523 mg/kg bw		Rat			ECHA
Inhalation (vapor)	LD ₅₀		6350 ppm	4 hours	Rat			ECHA
Dermal	LD ₅₀		12126 mg/kg bw		Rabbit			ECHA
Oral	NOAEL		150 mg/kg bw		Rat			ECHA
Oral	LOAEL		150 mg/kg bw		Rat			ECHA

titanium dioxide

Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination	Source
Oral	LD ₅₀		>5000 mg/kg					BL dodavatele
Inhalation	LC ₅₀		>6.82 mg/l of air					BL dodavatele

toluene

Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination	Source
Oral	LD ₅₀		5000 mg/kg bw					BL dodavatele
Inhalation	LC ₅₀		188 mg/l		Rat (Rattus norvegicus)			
Dermal	LD ₅₀		5000 mg/kg bw					BL dodavatele

Skin corrosion/irritation

Data for the mixture are not available. Based on the available data, the criteria for classification of the mixture are not met.

2-methoxy-1-methylethyl acetate

Route of exposure	Result	Method	Exposure time	Species	Source
Dermal	Not irritating	OECD 404		Rabbit	BL dodavatele

2-methylpropan-1-ol

Route of exposure	Result	Method	Exposure time	Species	Source
	Irritating	OECD 404		Rabbit	BL dodavatele

formaldehyde ...%

Route of exposure	Result	Method	Exposure time	Species	Source
	Corrosive	OECD 404		Rabbit	BL dodavatele

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date 25th January 2018
Revision date 03rd February 2025 Version 6.0

hydrocarbons, C10-C13, n-alkanes, isolakanes, cyclics, <2% aromatics

Route of exposure	Result	Method	Exposure time	Species	Source
Oral	Negative, Slightly irritating	OECD 404			

hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclic, <2% aromatics

Route of exposure	Result	Method	Exposure time	Species	Source
Dermal	Negative, Slightly irritating	OECD 404			

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics

Route of exposure	Result	Method	Exposure time	Species	Source
	Slightly irritating	OECD 404			BL dodavatele

neodecanoic acid, cobalt salt

Route of exposure	Result	Method	Exposure time	Species	Source
	Not irritating	OECD 404		Rabbit	BL dodavatele

talc (Mg3H2(SiO3)4)

Route of exposure	Result	Method	Exposure time	Species	Source
			3 days	Human	výrobce

Irritation

m-tolylidene diisocyanate

Route of exposure	Result	Exposure time	Species	Source
	Irritating, Highly irritating		Rabbit	BL dodavatele

Serious eye damage/irritation

Data for the mixture are not available. Based on the available data, the criteria for classification of the mixture are not met.

2-methoxy-1-methylethyl acetate

Route of exposure	Result	Method	Exposure time	Species	Source
Eye	Slightly irritating	OECD 405		Rabbit	BL dodavatele

2-methylpropan-1-ol

Route of exposure	Result	Method	Exposure time	Species	Source
Eye	Serious eye damage	OECD 405		Rabbit	BL dodavatele

hydrocarbons, C10-C13, n-alkanes, isolakanes, cyclics, <2% aromatics

Route of exposure	Result	Method	Exposure time	Species	Source
Eye	Slightly irritating	OECD 405			

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date 25th January 2018
Revision date 03rd February 2025 Version 6.0

hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclic, <2% aromatics

Route of exposure	Result	Method	Exposure time	Species	Source
Eye	Negative, Slightly irritating	OECD 405			

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics

Route of exposure	Result	Method	Exposure time	Species	Source
Eye	Slightly irritating	OECD 405			BL dodavatele

neodecanoic acid, cobalt salt

Route of exposure	Result	Method	Exposure time	Species	Source
Eye	Not irritating	OECD 405		Rabbit	BL dodavatele

Respiratory or skin sensitisation

Data for the mixture are not available. Based on the available data, the criteria for classification of the mixture are not met.

2-methoxy-1-methylethyl acetate

Route of exposure	Result	Method	Exposure time	Species	Sex	Source
Dermal	Negative	OECD 406		Guinea-pig (Cavia aperea f. porcellus)		BL dodavatele

formaldehyde ...%

Route of exposure	Result	Method	Exposure time	Species	Sex	Source
Dermal	Sensitizing	OECD 406		Guinea-pig (Cavia aperea f. porcellus)		BL dodavatele

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

Route of exposure	Result	Method	Exposure time	Species	Sex	Source
	Negative					

hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclic, <2% aromatics

Route of exposure	Result	Method	Exposure time	Species	Sex	Source
	Negative					

neodecanoic acid, cobalt salt

Route of exposure	Result	Method	Exposure time	Species	Sex	Source
Dermal	Sensitizing	OECD 429		Mouse		BL dodavatele

Sensitization

m-tolylidene diisocyanate

Route of exposure	Result	Method	Exposure time	Species	Sex	Source
Dermal	Positive	OECD 429		Mouse		BL dodavatele

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date 25th January 2018
Revision date 03rd February 2025 Version 6.0

Germ cell mutagenicity

Data for the mixture are not available. Based on the available data, the criteria for classification of the mixture are not met.

formaldehyde ...%						
Result	Method	Exposure time	Specific target organ	Species	Sex	Source
Positive	OECD 471			Bacteria (Salmonella typhimurium)		BL dodavatel e
Positive	OECD 471			Chinese hamster (Cricetulus barabensis)		BL dodavatel e
Negative				Rat (Rattus norvegicus)	M	BL dodavatel e

hydrocarbons, C10-C13, n-alanes, isolakanes, cyclics, <2% aromatics						
Result	Method	Exposure time	Specific target organ	Species	Sex	Source
Negative	OECD 471					

hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclic, <2% aromatics						
Result	Method	Exposure time	Specific target organ	Species	Sex	Source
Negative	OECD 471					

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics						
Result	Method	Exposure time	Specific target organ	Species	Sex	Source
Negative	OECD 471					BL dodavatel e

neodecanoic acid, cobalt salt						
Result	Method	Exposure time	Specific target organ	Species	Sex	Source
Negative	OECD 471					BL dodavatel e
Negative	OECD 475			Rat (Rattus norvegicus)		BL dodavatel e

Carcinogenicity

Data for the mixture are not available. Based on the available data, the criteria for classification of the mixture are not met.

(2-methoxymethylethoxy)propanol								
Route of exposure	Parameter	Method	Value	Exposure time	Result	Species	Sex	Source
Inhalation (vapor)		OECD 453	18184.5 mg/m ³	2 years (6 hour/day)	Negative	Rat (Rattus norvegicus)	F/M	BL dodavate le

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date
Revision date

25th January 2018
03rd February 2025

Version

6.0

2-methoxy-1-methylethyl acetate

Route of exposure	Parameter	Method	Value	Exposure time	Result	Species	Sex	Source
Inhalation	NOAEL		≥11.07 mg/l	24 months (6 hour/day, 5 days/week)		Rat (Rattus norvegicus)	F/M	BL dodavatele

formaldehyde ...%

Route of exposure	Parameter	Method	Value	Exposure time	Result	Species	Sex	Source
					Positive			BL dodavatele

hydrocarbons, C10-C13, n-alanes, isolakanes, cyclics, <2% aromatics

Route of exposure	Parameter	Method	Value	Exposure time	Result	Species	Sex	Source
Oral		OECD 453			Negative			

hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclic, <2% aromatics

Route of exposure	Parameter	Method	Value	Exposure time	Result	Species	Sex	Source
Oral		OECD 453			Negative			

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics

Route of exposure	Parameter	Method	Value	Exposure time	Result	Species	Sex	Source
		OECD 453			Negative			BL dodavatele

m-tolylidene diisocyanate

Route of exposure	Parameter	Method	Value	Exposure time	Result	Species	Sex	Source
Inhalation (vapor)		OECD 453			Tumor formation, No effect	Rat (Rattus norvegicus)	F/M	BL dodavatele

toluene

Route of exposure	Parameter	Method	Value	Exposure time	Result	Species	Sex	Source
	NOAEC		4522 mg/m ³		Not carcinogenic			BL dodavatele

Reproductive toxicity

Data for the mixture are not available. Based on the available data, the criteria for classification of the mixture are not met.

(2-methoxymethylethoxy)propanol

Effect	Parameter	Method	Value	Exposure time	Result	Species	Sex	Source
Effects on fertility	NOAEL	OECD 416	300 ppm			Rat (Rattus norvegicus)	F/M	BL dodavatele
Effects on fertility	NOEC	OECD 416	6061.35 mg/m ³			Rat (Rattus norvegicus)	F/M	BL dodavatele

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date
Revision date

25th January 2018
03rd February 2025

Version

6.0

(2-methoxymethylethoxy)propanol

Effect	Parameter	Method	Value	Exposure time	Result	Species	Sex	Source
Developmental toxicity	NOEC		1818.4 mg/m ³	10 days (6 hour/day)		Rabbit		BL dodavatele

2-methylpropan-1-ol

Effect	Parameter	Method	Value	Exposure time	Result	Species	Sex	Source
Effects on fertility	NOAEL		7.5 mg/l		Negative	Rat (Rattus norvegicus)		BL dodavatele
Developmental toxicity	NOAEL	OECD 414	10 mg/l		Negative	Rat (Rattus norvegicus)		BL dodavatele

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

Effect	Parameter	Method	Value	Exposure time	Result	Species	Sex	Source
		OECD 413			Negative			

hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclic, <2% aromatics

Effect	Parameter	Method	Value	Exposure time	Result	Species	Sex	Source
		OECD 413			Negative			

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics

Effect	Parameter	Method	Value	Exposure time	Result	Species	Sex	Source
		OECD 413			Negative			BL dodavatele

m-tolylidene diisocyanate

Effect	Parameter	Method	Value	Exposure time	Result	Species	Sex	Source
Effects on fertility	NOAEL	OECD 416	<0.02 ppm		No effect	Rat (Rattus norvegicus)	F/M	BL dodavatele
Developmental toxicity	NOAEL	OECD 414	0.1 ppm	21 days (6 hour/day)	No effect	Rat (Rattus norvegicus)	F	BL dodavatele

neodecanoic acid, cobalt salt

Effect	Parameter	Method	Value	Exposure time	Result	Species	Sex	Source
Effects on fertility	NOAEL	OECD 422	5 mg/kg bw		Negative	Rat (Rattus norvegicus)	F/M	BL dodavatele

toluene

Effect	Parameter	Method	Value	Exposure time	Result	Species	Sex	Source
Developmental toxicity	Inhalačně		1000 ppm		Toxic for reproduction			BL dodavatele

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date 25th January 2018
Revision date 03rd February 2025 Version 6.0

Toxicity for specific target organ - single exposure

May cause drowsiness or dizziness.

hydrocarbons, C10-C13, n-alkanes, isolakanes, cyclics, <2% aromatics						
Route of exposure	Parameter	Value	Result	Species	Sex	Source
			Negative			

hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclic, <2% aromatics						
Route of exposure	Parameter	Value	Result	Species	Sex	Source
			Negative			

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics						
Route of exposure	Parameter	Value	Result	Species	Sex	Source
			Positive			BL dodavatele

m-tolylidene diisocyanate						
Route of exposure	Parameter	Value	Result	Species	Sex	Source
Inhalation			Irritating			BL dodavatele

Toxicity for specific target organ - repeated exposure

Data for the mixture are not available. Based on the available data, the criteria for classification of the mixture are not met.

hydrocarbons, C10-C13, n-alkanes, isolakanes, cyclics, <2% aromatics							
Route of exposure	Parameter	Method	Value	Result	Species	Sex	Source
Oral		OECD 408		Negative			

hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclic, <2% aromatics							
Route of exposure	Parameter	Method	Value	Result	Species	Sex	Source
Oral		OECD 408		Negative			

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics							
Route of exposure	Parameter	Method	Value	Result	Species	Sex	Source
		OECD 408		Negative			BL dodavatele

neodecanoic acid, cobalt salt							
Route of exposure	Parameter	Method	Value	Result	Species	Sex	Source
Oral				Positive			BL dodavatele

Repeated dose toxicity

(2-methoxymethylethoxy)propanol								
Route of exposure	Parameter	Result	Method	Value	Exposure time	Species	Sex	Source
Oral	NOAEL			1000 mg/kg	4 weeks (7 days/week)	Rat (Rattus norvegicus)	F/M	BL dodavatele

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date

25th January 2018

Revision date

03rd February 2025

Version

6.0

(2-methoxymethylethoxy)propanol

Route of exposure	Parameter	Result	Method	Value	Exposure time	Species	Sex	Source
Inhalation (vapor)	NOAEL		OECD 413	1232 mg/m ³	13 weeks (6 hour/day, 5 days/week)	Rat (Rattus norvegicus)	F/M	BL dodavatel e
Dermal	NOAEL		OECD 411	2850 mg/kg	90 days (5 days/week)	Rabbit	M	BL dodavatel e

2-methoxy-1-methylethyl acetate

Route of exposure	Parameter	Result	Method	Value	Exposure time	Species	Sex	Source
Inhalation	NOAEL			1000 ppm		Rat		echa
Dermal	NOAEL			1000-1838 mg/kg bw/day		Rabbit		echa
Oral	NOAEL		OECD 422	1000 mg/kg		Rat (Rattus norvegicus)	F/M	BL dodavatel e

2-methylpropan-1-ol

Route of exposure	Parameter	Result	Method	Value	Exposure time	Species	Sex	Source
Drinking water	NOAEL	Negative	OECD 408	1450 mg/kg	90 days	Rat (Rattus norvegicus)		BL dodavatel e

aluminium powder (stabilised)

Route of exposure	Parameter	Result	Method	Value	Exposure time	Species	Sex	Source
Oral	NOAEL			200-3225 mg/kg bw/day		Rat		echa
Inhalation	LOAEC			50 mg/m ³ of air		Rat		echa

Dibutyltin dilaurate

Route of exposure	Parameter	Result	Method	Value	Exposure time	Species	Sex	Source
Oral	NOAEL			0.3 mg/kg bw/day		Rat (Rattus norvegicus)		ECHA

ethanol

Route of exposure	Parameter	Result	Method	Value	Exposure time	Species	Sex	Source
Oral	NOAEL			9700 mg/kg bw/day		Mouse		echa
Inhalation	NOAEC			6.66 mg/l of air		Rat		echa

ethylbenzene

Route of exposure	Parameter	Result	Method	Value	Exposure time	Species	Sex	Source
Oral	NOAEL			75 mg/kg bw/day		Rat		echa
Inhalation	NOAEC			75 mg/kg bw/day		Rat		echa

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date
Revision date

25th January 2018
03rd February 2025

Version

6.0

formaldehyde ...%

Route of exposure	Parameter	Result	Method	Value	Exposure time	Species	Sex	Source
Oral	LOAEL		OECD 453	82 mg/kg	2 years	Rat (Rattus norvegicus)	M	BL dodavatel e

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics

Route of exposure	Parameter	Result	Method	Value	Exposure time	Species	Sex	Source
Oral	NOAEL			500-5000 mg/kg bw/day		Rat		ECHA
Inhalation	NOAEL			200 ppm		Rat		ECHA

m-tolylidene diisocyanate

Route of exposure	Parameter	Result	Method	Value	Exposure time	Species	Sex	Source
Inhalation (vapor)	LOAEL		OECD 453	0.05 ppm		Rat (Rattus norvegicus)	F/M	BL dodavatel e

neodecanoic acid, cobalt salt

Route of exposure	Parameter	Result	Method	Value	Exposure time	Species	Sex	Source
Oral	NOAEL		OECD 422	5 mg/kg	40-49 days (7 days/week)	Rat (Rattus norvegicus)	F/M	BL dodavatel e

toluene

Route of exposure	Parameter	Result	Method	Value	Exposure time	Species	Sex	Source
Oral	NOAEL			625 mg/kg bw/day		Rat (Rattus norvegicus)		echa
Inhalation	NOAEC			1.131 mg/l of air		Rat (Rattus norvegicus)		echa
Oral	NOAEL			625 mg/kg bw/day				BL dodavatel e
Inhalation	NOAEC			98 mg/m ³				BL dodavatel e

Aspiration hazard

Data for the mixture are not available. Based on the available data, the criteria for classification of the mixture are not met.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics

Route of exposure	Result	Exposure time	Species	Sex	Source
	Positive				BL dodavatele

11.2. Information on other hazards

Endocrine disrupting properties

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any components that may cause endocrine disruption for humans.

Other information

not available

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date 25th January 2018
Revision date 03rd February 2025 Version 6.0

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects.

Acute toxicity

(2-methoxymethylethoxy)propanol						
Parameter	Method	Value	Exposure time	Species	Environment	Source
LC ₅₀	OECD 203	>1000 mg/l	96 hours	Fish (Oncorhynchus mykiss)		BL dodavatel e
LC ₅₀	OECD 202	1919 mg/l	48 hours	Daphnia (Daphnia magna)		BL dodavatel e
ErC ₅₀	OECD 201	>969 mg/l	96 hours	Algae (Pseudokirchneriella subcapitata)		BL dodavatel e
EC ₁₀		4168 mg/l	18 hours	Microorganisms (Pseudomonas putida)		BL dodavatel e

2-methoxy-1-methylethyl acetate						
Parameter	Method	Value	Exposure time	Species	Environment	Source
LC ₅₀		134 mg/l	96 hours	Fish (Oncorhynchus mykiss)		BL dodavatel e
EC ₅₀		408 mg/l	48 hours	Daphnia (Daphnia magna)		BL dodavatel e
EC ₅₀		500 mg/l	48 hours	Aquatic invertebrates		echa
ErC ₅₀	OECD 201	>1000 mg/l	96 hours	Algae (Selenastrum capricornutum)		BL dodavatel e
EC ₁₀		1 g/l	30 minutes	Microorganisms (Photobacterium phosphoreum)		echa

2-methylpropan-1-ol						
Parameter	Method	Value	Exposure time	Species	Environment	Source
LC ₅₀		>100 mg/l	96 hours	Fish (Pimephales promelas)		BL dodavatel e
EC ₅₀		>100 mg/l	48 hours	Daphnia (Daphnia pulex)		BL dodavatel e
EC ₅₀	OECD 201	>100 mg/l	72 hours	Algae (Pseudokirchneriella subcapitata)		BL dodavatel e
EC ₁₀	OECD 209	>100 mg/l	16 hours	Bacteria (Pseudomonas putida)		BL dodavatel e

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date
Revision date

25th January 2018
03rd February 2025

Version

6.0

aluminium powder (stabilised)

Parameter	Method	Value	Exposure time	Species	Environment	Source
LC ₅₀		430-3910 µg/l	16 days	Fish (Oncorhynchus mykiss)		ECHA
EC ₅₀		1.5-2.56 mg/l	48 hours	Aquatic invertebrates		ECHA
EC ₅₀		5.4-570 µg/l	96 hours	Algae and other aquatic plants		ECHA

carbon black

Parameter	Method	Value	Exposure time	Species	Environment	Source
LC ₅₀	OECD 203	>1000 mg/l	96 hours	Fish (Branchydanio rerio)		BL dodavatel
EC ₅₀	OECD 202	>5600 mg/l	24 hours	Daphnia (Daphnia magna)		BL dodavatel
EC ₅₀		>10000 mg/l	72 hours	Algae (Scenedesmus subspicatus)		BL dodavatel
EC ₀		≥800 mg/l	3 hours	Microorganisms	Activated sludge	BL dodavatel

Dibutyltin dilaurate

Parameter	Method	Value	Exposure time	Species	Environment	Source
EC ₅₀		463 µg/l	48 hours	Aquatic invertebrates		ECHA
EC ₅₀		1 mg/l	72 hours	Algae and other aquatic plants		ECHA
EC ₅₀		1 g/l	3 hours	Microorganisms (Photobacterium phosphoreum)		ECHA

diiron trioxide

Parameter	Method	Value	Exposure time	Species	Environment	Source
LC ₅₀		>1000 mg/l	48 hours	Fish (Leuciscus idus)		BL dodavatel

ethanol

Parameter	Method	Value	Exposure time	Species	Environment	Source
LC ₅₀		>8140 mg/l	96 hours	Fish (Oncorhynchus mykiss)		BL dodavatel
EC ₅₀		9268-14221 mg/l	48 hours	Crustaceans		BL dodavatel
EC ₅₀		675-22000 mg/l	96 hours	Algae and other aquatic plants		ECHA
EC ₅₀		5.8 g/l	4 hours	Microorganisms (Photobacterium phosphoreum)		ECHA

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date
Revision date

25th January 2018
03rd February 2025

Version

6.0

ethylbenzene

Parameter	Method	Value	Exposure time	Species	Environment	Source
LC ₅₀		4.2-5.1 mg/l	96 hours	Fish (Oncorhynchus mykiss)		echa
EC ₅₀		1.8-2.4 mg/l	48 hours	Aquatic invertebrates		echa
EC ₅₀		3.6-7.7 mg/l	96 hours	Algae and other aquatic plants		echa
EC ₅₀		96 mg/l	24 hours	Microorganisms (Photobacterium phosphoreum)		echa

formaldehyde ...%

Parameter	Method	Value	Exposure time	Species	Environment	Source
LC ₅₀		6.7 mg/l	96 hours	Fish	Salt water	BL dodavatel e
EC ₅₀	OECD 202	5.8 mg/l	48 hours	Daphnia (Daphnia pulex)	Fresh water	BL dodavatel e
ErC ₅₀	OECD 201	4.89 mg/l	72 hours	Algae and other aquatic plants (Desmodesmus subspicatus)		BL dodavatel e
EC ₅₀	OECD 209	19 mg/l	3 hours	Microorganisms	Activated sludge	BL dodavatel e

hydrocarbons, C10-C13, n-alkanes, isolkanes, cyclics, <2% aromatics

Parameter	Method	Value	Exposure time	Species	Environment	Source
LL _o		1000 mg/l	96 hours	Fish (Oncorhynchus mykiss)		BL dodavatel e
EL _o		1000 mg/l	48 hours	Daphnia (Daphnia magna)		BL dodavatel e
EL _o		1000 mg/l	72 hours	Algae (Pseudokirchneriella subcapitata)		BL dodavatel e

hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclic, <2% aromatics

Parameter	Method	Value	Exposure time	Species	Environment	Source
EL _o		1000 mg/l	48 hours	Invertebrates (Daphnia magna)		BL_dodavatel
EL _o		1000 mg/l	72 hours	Algae (Selenastrum capricornutum)		BL-dodavatel
LL _o		1000 mg/l	96 hours	Fish (Oncorhynchus mykiss)		BL-dodavatel

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date
Revision date

25th January 2018
03rd February 2025

Version

6.0

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics

Parameter	Method	Value	Exposure time	Species	Environment	Source
EL ₅₀		>1000 mg/l	72 hours	Algae (Pseudokirchneriella subcapitata)		BL dodavatel e
EL ₀		1000 mg/l	48 hours	Daphnia (Daphnia magna (Hrotnatka velká))		BL dodavatel e
LL ₅₀		>1000 mg/l	96 hours	Fish (Oncorhynchus mykiss)		BL dodavatel e
NOELR		100 mg/l	72 hours	Algae (Pseudokirchneriella subcapitata)		BL dodavatel e

Iron hydroxide oxide yellow

Parameter	Method	Value	Exposure time	Species	Environment	Source
EC ₅₀		>10000 mg/l	3 hours	Bacteria (Salmonella typhimurium)	Fresh water	BL dodavatel e
EC ₅₀	OECD 202	>100 mg/l	48 hours	Daphnia (Daphnia magna)	Fresh water	BL dodavatel e
LC ₀	OECD 203	>1000000 mg/l	96 hours	Fish (Oncorhynchus mykiss)	Fresh water	BL dodavatel e

m-tolylidene diisocyanate

Parameter	Method	Value	Exposure time	Species	Environment	Source
LC ₅₀	OECD 203	133 mg/l	96 hours	Fish (Oncorhynchus mykiss)		BL dodavatel e
EC ₅₀	OECD 202	12.5 mg/l	48 hours	Daphnia (Daphnia magna)		BL dodavatel e
NOEC		1.1 mg/l	21 days	Daphnia (Daphnia magna)		BL dodavatel e
ErC ₅₀	OECD 201	4300 mg/l	96 hours	Algae (Selenastrum capricornutum)		BL dodavatel e
ErC ₅₀	OECD 201	3230 mg/l	96 hours	Algae (Selenastrum capricornutum)		BL dodavatel e
EC ₅₀	OECD 209	>100 mg/l	3 hours	Bacteria (Salmonella typhimurium)		BL dodavatel e
NOEC	OECD 207	>1000 mg/kg	14 days	Microorganisms (Photobacterium phosphoreum)		BL dodavatel e
NOEC	OECD 208	>1000 mg/kg	14 days	Higher plants		BL dodavatel e

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date
Revision date

25th January 2018
03rd February 2025

Version

6.0

n-butyl acetate

Parameter	Method	Value	Exposure time	Species	Environment	Source
LC ₅₀		18 mg/l	96 hours	Fish (Pimephales promelas)		BL dodavatel e
EC ₅₀		44 mg/l	48 hours	Aquatic invertebrates (Daphnia sp.)		BL dodavatel e
EC ₅₀		397 mg/l	72 hours	Algae and other aquatic plants (Pseudokirchneriella subcapitata)		BL dodavatel e
EC ₅₀		356 mg/l	40 hours	Microorganisms (Tetrahymena pyriformis)		BL dodavatel e
EC ₅₀	OECD 208	>1000 mg/kg	14 days	Algae (Selenastrum capricornutum)		BL dodavatel e

neodecanoic acid, cobalt salt

Parameter	Method	Value	Exposure time	Species	Environment	Source
LC ₅₀		85.3 mg/l	96 hours	Fish (Danio rerio)	Fresh water	BL dodavatel e
LC ₅₀		429 mg/l	96 hours	Aquatic invertebrates (Chironomus sp. (Rod pakomáři))	Fresh water	BL dodavatel e
EC ₅₀		71.3 mg/l	96 hours	Algae and other aquatic plants (Dunaliella tertiolecta (Řasa))	Salt water	BL dodavatel e
EC ₁₀	OECD 209	3.73 mg/l	30 minutes	Microorganisms (Photobacterium phosphoreum)	Activated sludge	BL dodavatel e

Silica, amorphous

Parameter	Method	Value	Exposure time	Species	Environment	Source
LC ₅₀	OECD 203	>10000 mg/l	96 hours	Fish (Danio rerio)		BL dodavatel e
EC ₅₀	OECD 202	>1000 mg/l	24 hours	Daphnia (Daphnia magna)		BL dodavatel e
EC ₅₀		120 mg/l	48 hours	Algae (Selenastrum capricornutum)		BL dodavatel e
NOEC		60 mg/l	48 hours	Algae (Selenastrum capricornutum)		BL dodavatel e

talco (Mg₃H₂(SiO₃)₄)

Parameter	Method	Value	Exposure time	Species	Environment	Source
LC ₅₀		>100000 mg/l	24 hours	Fish (Oncorhynchus mykiss)		výrobce

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date
Revision date

25th January 2018
03rd February 2025

Version

6.0

talc (Mg₃H₂(SiO₃)₄)

Parameter	Method	Value	Exposure time	Species	Environment	Source
LC ₅₀		94983.781 mg/kg	48 hours	Crustaceans		výrobce
LC ₅₀		48545.539 mg/l		Algae (Selenastrum capricornutum)		výrobce

Technical xylene (mixed with ethylbenzene)

Parameter	Method	Value	Exposure time	Species	Environment	Source
EC ₅₀		96 mg/l	24 hours	Microorganisms (Photobacterium phosphoreum)		ECHA
EC ₅₀		2.2 mg/l	73 hours	Algae (Selenastrum capricornutum)		ECHA
IC ₅₀		1 mg/l	24 hours	Aquatic invertebrates		ECHA
LC ₅₀		2.6 mg/l	4 days	Fish (Oncorhynchus mykiss)		ECHA

titanium dioxide

Parameter	Method	Value	Exposure time	Species	Environment	Source
LC ₅₀		>100 mg/l	96 hours	Fish (Oncorhynchus mykiss)	Fresh water	BL dodavatel
LC ₅₀		>1000 mg/l	96 hours	Fish (Pimephales promelas)	Fresh water	BL dodavatel
LC ₅₀	OECD 202	>100 mg/l	48 hours	Daphnia (Daphnia magna)	Fresh water	BL dodavatel

toluene

Parameter	Method	Value	Exposure time	Species	Environment	Source
LC ₅₀		5.5 mg/l	96 hours	Fish (Oncorhynchus mykiss)		BL dodavatel
EC ₅₀		3.78 mg/l	48 hours	Invertebrates	Fresh water	BL dodavatel
EC ₅₀		134 mg/l	3 hours	Algae (Chlorella vulgaris)	Fresh water	BL dodavatel
EC ₅₀		84 mg/l	24 hours	Microorganisms (Photobacterium phosphoreum)		BL dodavatel

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date
Revision date

25th January 2018
03rd February 2025

Version

6.0

Chronic toxicity

(2-methoxymethylethoxy)propanol						
Parameter	Method	Value	Exposure time	Species	Environment	Source
NOEC		>0.5 mg/l	22 days	Daphnia (Daphnia magna)		BL dodavatel e
LOEC		>0.5 mg/l	22 days	Daphnia (Daphnia magna)		BL dodavatel e

2-methoxy-1-methylethyl acetate						
Parameter	Method	Value	Exposure time	Species	Environment	Source
LC ₅₀		63.5 mg/l	14 days	Fish (Oncorhynchus mykiss)		ECHA

2-methylpropan-1-ol						
Parameter	Method	Value	Exposure time	Species	Environment	Source
NOEC		20 mg/l	21 days	Daphnia (Daphnia magna)		BL dodavatel e

formaldehyde ...%						
Parameter	Method	Value	Exposure time	Species	Environment	Source
EC ₅₀	OECD 211	≥6.4 mg/l	21 days	Daphnia (Daphnia magna)	Fresh water	BL dodavatel e

n-butyl acetate						
Parameter	Method	Value	Exposure time	Species	Environment	Source
NOEC	OECD 211	23 mg/l	21 days	Daphnia (Daphnia magna)		BL dodavatel e

neodecanoic acid, cobalt salt						
Parameter	Method	Value	Exposure time	Species	Environment	Source
NOEC		31802 µg/l		Fish (Cyprinodon variegatus (halančíkovec diamantový))	Salt water	BL dodavatel e
NOEC		351.4 µg/l	96 hours	Fish (Pimephales promelas (střevle))	Fresh water	BL dodavatel e
EC ₁₀	OECD 211	7.55 µg/l		Aquatic invertebrates (Hyalella azteca (Různonožci))		BL dodavatel e

Technical xylene (mixed with ethylbenzene)						
Parameter	Method	Value	Exposure time	Species	Environment	Source
NOEC		960 µg/l		Aquatic invertebrates		ECHA

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date 25th January 2018
Revision date 03rd February 2025 Version 6.0

Technical xylene (mixed with ethylbenzene)

Parameter	Method	Value	Exposure time	Species	Environment	Source
NOEC		1.3 mg/l	56 days	Fish (Oncorhynchus mykiss)		ECHA

toluene

Parameter	Method	Value	Exposure time	Species	Environment	Source
NOEC		1.4 mg/l	40 days	Fish (Pimephales promelas)		BL dodavatel e
NOEC		0.74 mg/l	7 days	Invertebrates	Fresh water	BL dodavatel e
NOEC		10 mg/l		Algae	Fresh water	BL dodavatel e

12.2. Persistence and degradability

Data for the mixture are not available.

Biodegradability

(2-methoxymethylethoxy)propanol

Parameter	Method	Value	Exposure time	Environment	Result	Source
	OECD 301F	75 %	28 days		Easily biodegradable	BL dodavatel e

2-methylpropan-1-ol

Parameter	Method	Value	Exposure time	Environment	Result	Source
	OECD 301D	>70 %	28 days		Easily biodegradable	BL dodavatel e

ethanol

Parameter	Method	Value	Exposure time	Environment	Result	Source
		94 %				BL dodavatel e
CHSK		2.08 mg/kg				BL dodavatel e
BSK ₅		1.46 mg/kg				BL dodavatel e

formaldehyde ...%

Parameter	Method	Value	Exposure time	Environment	Result	Source
	OECD 301A	99 %	28 days		Easily biodegradable	BL dodavatel e

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date 25th January 2018
Revision date 03rd February 2025 Version 6.0

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

Parameter	Method	Value	Exposure time	Environment	Result	Source
Degradovaný podíl	OECD 301F	80 %	28 days	Fresh water	Easily biodegradable	BL dodavatel e

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics

Parameter	Method	Value	Exposure time	Environment	Result	Source
		80 %	28 days		Easily biodegradable	BL dodavatel e

m-tolylidene diisocyanate

Parameter	Method	Value	Exposure time	Environment	Result	Source
	OECD 302C	0 %	28 days		Not biodegradable	BL dodavatel e

12.3. Bioaccumulative potential

Data for the mixture are not available.

(2-methoxymethylethoxy)propanol

Parameter	Method	Value	Exposure time	Species	Environment	Temperature [°C]	Value determination	Source
Log Pow	OECD 107	0.006				25°C		BL dodavatel e

2-methylpropan-1-ol

Parameter	Method	Value	Exposure time	Species	Environment	Temperature [°C]	Value determination	Source
Log Pow		1				25°C		BL dodavatel e

formaldehyde ...%

Parameter	Method	Value	Exposure time	Species	Environment	Temperature [°C]	Value determination	Source
BCF		<1						BL dodavatel e
Log Pow		0.35					Experimentally	BL dodavatel e

hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclic, <2% aromatics

Parameter	Method	Value	Exposure time	Species	Environment	Temperature [°C]	Value determination	Source
		69	28 days		Fresh water			BL-dodavatel e

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date 25th January 2018
Revision date 03rd February 2025 Version 6.0

m-tolylidene diisocyanate

Parameter	Method	Value	Exposure time	Species	Environment	Temperature [°C]	Value determination	Source
Log Pow		3.43				22°C		BL dodavatele

neodecanoic acid, cobalt salt

Parameter	Method	Value	Exposure time	Species	Environment	Temperature [°C]	Value determination	Source
BCF		180-4000						BL dodavatele

12.4. Mobility in soil

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any PMT or vPvM components.

2-methylpropan-1-ol

Parameter	Value	Result	Source
Koc	2.1	High	BL dodavatele

formaldehyde ...%

Parameter	Value	Result	Source
Koc	15.9		BL dodavatele

12.5. Results of PBT and vPvB assessment

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any PBT or vPvB components.

12.6. Endocrine disrupting properties

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any components that may cause endocrine disruption in the environment.

12.7. Other adverse effects

Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Empty containers may be used at waste incinerators to produce energy or deposited in a dump with appropriate classification. Perfectly cleaned containers can be submitted for recycling.

Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

Waste type code

08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

Packaging waste type code

15 01 10* packaging containing residues of or contaminated by hazardous substances

(*) - Hazardous waste according to Directive 2008/98/EC on hazardous waste

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date	25th January 2018	Version	6.0
Revision date	03rd February 2025		

SECTION 14: Transport information

14.1. UN number or ID number

UN 1263

14.2. UN proper shipping name

PAINT

14.3. Transport hazard class(es)

3 Flammable liquids

14.4. Packing group

III

14.5. Environmental hazards

No.

14.6. Special precautions for user

Reference in the Sections 4 to 8.

14.7. Maritime transport in bulk according to IMO instruments

not relevant

Additional information

Hazard identification No.

30

UN number

1263

Classification code

F1

Safety signs

3



Road transport - ADR

Special provisions

163, 367, 650

Limited quantities

5 L

Excepted quantities

E1

Packaging

Packing instructions

P001, IBC03, LP01, R001

Special packing provisions

PP1

Mixed packing provisions

MP19

Portable tanks and bulk containers

Guidelines

T2

Special provisions

TP1, TP29

ADR tank

Tank code

LGBF

Vehicles for tank carriage

FL

Transport category

3

Tunnel restriction code

(D/E)

Special provision for

packages

V12

operation

S2

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date	25th January 2018	Version	6.0
Revision date	03rd February 2025		

Railway transport - RID

Special provisions 163, 367, 650

Packaging

Packing instructions P001, IBC03, LP01, R001

Special packing provisions PP1

Mixed packing provisions MP19

Portable tanks and bulk containers

Guidelines T2

Special provisions TP1, TP29

RID Tanks

Tank code LGBF

Transport category 3

Special provision for

packages W12

Air transport - ICAO/IATA

Packaging instructions for limited amount Y344

Packaging instructions passenger 355

Cargo packaging instructions 366

Marine transport - IMDG

EmS (emergency plan) F-E, S-E

MFAG 310

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Product contains regulated explosives precursor: Making available, introduction, possession and use of those precursors by member of the general public according to Regulation (EU) 2019/1148, Article 5 to 9. Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date 25th January 2018
Revision date 03rd February 2025 Version 6.0

Restrictions pursuant to Annex XVII of Regulation (EC) No. 1907/2006 (REACH), as amended

Dibutyltin dilaurate

Restriction	Conditions of restriction
30	1. Shall not be placed on the market, or used, — as substances, — as constituents of other substances, or, — in mixtures, for supply to the general public when the individual concentration in the substance or mixture is equal to or greater than: — either the relevant specific concentration limit specified in Part 3 of Annex VI to Regulation (EC) No 1272/2008, or, — the relevant generic concentration limit specified in Part 3 of Annex I of Regulation (EC) No 1272/2008. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of substances and mixtures, suppliers shall ensure before the placing on the market that the packaging of such substances and mixtures is marked visibly, legibly and indelibly as follows: “Restricted to professional users”. 2. By way of derogation, paragraph 1 shall not apply to: (a) medicinal or veterinary products as defined by Directive 2001/82/EC and Directive 2001/83/EC; (b) cosmetic products as defined by Directive 76/768/EEC; (c) the following fuels and oil products: — motor fuels which are covered by Directive 98/70/EC, — mineral oil products intended for use as fuel in mobile or fixed combustion plants, — fuels sold in closed systems (e.g. liquid gas bottles); (d) artists’ paints covered by Regulation (EC) No 1272/2008; (e) the substances listed in Appendix 11, column 1, for the applications or uses listed in Appendix 11, column 2. Where a date is specified in column 2 of Appendix 11, the derogation shall apply until the said date. (f) devices covered by Regulation (EU) 2017/745.

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date 25th January 2018
Revision date 03rd February 2025 Version 6.0

formaldehyde ...%

Restriction	Conditions of restriction
28	1. Shall not be placed on the market, or used, — as substances, — as constituents of other substances, or, — in mixtures, for supply to the general public when the individual concentration in the substance or mixture is equal to or greater than: — either the relevant specific concentration limit specified in Part 3 of Annex VI to Regulation (EC) No 1272/2008, or, — the relevant generic concentration limit specified in Part 3 of Annex I of Regulation (EC) No 1272/2008. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of substances and mixtures, suppliers shall ensure before the placing on the market that the packaging of such substances and mixtures is marked visibly, legibly and indelibly as follows: “Restricted to professional users”. 2. By way of derogation, paragraph 1 shall not apply to: (a) medicinal or veterinary products as defined by Directive 2001/82/EC and Directive 2001/83/EC; (b) cosmetic products as defined by Directive 76/768/EEC; (c) the following fuels and oil products: — motor fuels which are covered by Directive 98/70/EC, — mineral oil products intended for use as fuel in mobile or fixed combustion plants, — fuels sold in closed systems (e.g. liquid gas bottles); (d) artists' paints covered by Regulation (EC) No 1272/2008; (e) the substances listed in Appendix 11, column 1, for the applications or uses listed in Appendix 11, column 2. Where a date is specified in column 2 of Appendix 11, the derogation shall apply until the said date. (f) devices covered by Regulation (EU) 2017/745.

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date 25th January 2018
Revision date 03rd February 2025 Version 6.0

formaldehyde ...%

Restriction	Conditions of restriction
72	1. Shall not be placed on the market after 1 November 2020 in any of the following: (a) clothing or related accessories; (b) textiles other than clothing which, under normal or reasonably foreseeable conditions of use, come into contact with human skin to an extent similar to clothing; (c) footwear; if the clothing, related accessory, textile other than clothing or footwear is for use by consumers and the substance is present in a concentration, measured in homogeneous material, equal to or greater than that specified for that substance in Appendix 12. 2. By way of derogation, in relation to the placing on the market of formaldehyde [CAS No 50-00-0] in jackets, coats or upholstery, the relevant concentration for the purposes of paragraph 1 shall be 300 mg/kg during the period between 1 November 2020 and 1 November 2023. The concentration specified in Appendix 12 shall apply thereafter. 3. Paragraph 1 shall not apply to: (a) clothing, related accessories or footwear, or parts of clothing, related accessories or footwear, made exclusively of natural leather, fur or hide; (b) non-textile fasteners and non-textile decorative attachments; (c) second-hand clothing, related accessories, textiles other than clothing or footwear (d) wall-to-wall carpets and textile floor coverings for indoor use, rugs and runners. 4. Paragraph 1 shall not apply to clothing, related accessories, textiles other than clothing, or footwear within the scope of Regulation (EU) 2016/425 of the European Parliament and of the Council (*) or Regulation (EU) 2017/745 of the European Parliament and of the Council (**). 5. Paragraph 1(b) shall not apply to disposable textiles. 'Disposable textiles' means textiles that are designed to be used only once or for a limited time and are not intended for subsequent use for the same or a similar purpose. 6. Paragraphs 1 and 2 shall apply without prejudice to the application of any stricter restrictions set out in this Annex or in other applicable Union legislation. 7. The Commission shall review the exemption in paragraph 3(d) and, if appropriate, modify that point accordingly. (*) Regulation (EU) 2016/425 of the European Parliament and of the Council of 9 March 2016 on personal protective equipment and repealing Council Directive 89/686/EEC (OJ L 81, 31.3.2016, p. 51). (**) Regulation (EU) 2017/745 of the European Parliament and of the Council of 5 April 2017 on medical devices, amending Directive 2001/83/EC, Regulation (EC) No 178/2002 and Regulation (EC) No 1223/2009 and repealing Council Directives 90/385/EEC and 93/42/EEC (OJ L 117, 5.5.2017, p. 1).

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date 25th January 2018
Revision date 03rd February 2025 Version 6.0

formaldehyde ...%

Restriction	Conditions of restriction
77	1. Shall not be placed on the market in articles, after 6 August 2026, if, under the test conditions specified in Appendix 14, the concentration of formaldehyde released from those articles exceeds: (a) 0,062 mg/m³ for furniture and wood-based articles; (b) 0,080 mg/m³ for articles other than furniture and wood-based articles. The first subparagraph shall not apply to: (a) articles in which formaldehyde or formaldehyde releasing substances are exclusively naturally present in the materials from which the articles are produced; (b) articles that are exclusively for outdoor use under foreseeable conditions; (c) articles in constructions, that are exclusively used outside the building shell and vapour barrier and that do not emit formaldehyde into indoor air; (d) articles exclusively for industrial or professional use unless formaldehyde released from them leads to exposure of the general public under foreseeable conditions of use; (e) articles for which the restriction laid down in entry 72 applies; (f) articles that are biocidal products within the scope of Regulation (EU) No 528/2012 of the European Parliament and of the Council; (g) devices within the scope of Regulation (EU) 2017/745; (h) personal protective equipment within the scope of Regulation (EU) 2016/425; (i) articles intended to come into contact directly or indirectly with food within the scope of Regulation (EC) No 1935/2004; (j) second-hand articles. 2. Shall not be placed on the market in road vehicles after 6 August 2027 if, under the test conditions specified in Appendix 14, the concentration of formaldehyde in the interior of those vehicles exceeds 0,062 mg/m³. The first subparagraph shall not apply to: (a) road vehicles exclusively for industrial or professional use unless the concentration of formaldehyde in the interior of those vehicles leads to exposure of the general public under foreseeable conditions of use; (b) second-hand vehicles.

m-tolylidene diisocyanate

Restriction	Conditions of restriction
74	1. Shall not be used as substances on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) after 24 August 2023, unless: (a) the concentration of diisocyanates individually and in combination is less than 0,1 % by weight, or (b) the employer or self-employed ensures that industrial or professional user(s) have successfully completed training on the safe use of diisocyanates prior to the use of the substance(s) or mixture(s). 2. Shall not be placed on the market as substances on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) after 24 February 2022, unless: (a) the concentration of diisocyanates individually and in combination is less than 0,1 % by weight, or (b) the supplier ensures that the recipient of the substance(s) or mixture(s) is provided with information on the requirements referred to in point (b) of paragraph 1 and the following statement is placed on the packaging, in a manner that is visibly distinct from the rest of the label information: "As from 24 August 2023 adequate training is required before industrial or professional use". 3. For the purpose of this entry "industrial and professional user(s)" means any worker or self-employed worker handling diisocyanates on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) or supervising these tasks. 4. The training referred to in point (b) of paragraph 1 shall include the instructions for the control of dermal and inhalation exposure to diisocyanates at the workplace without prejudice to any national occupational exposure limit value or other appropriate risk management measures at national level. Such training shall be conducted by an expert on occupational safety and health with competence acquired by relevant vocational training. That training shall cover as a minimum: (a) the training elements in point (a) of paragraph 5 for all industrial and professional use(s). (b) the training elements in points (a) and (b) of paragraph 5 for the following uses: — handling open mixtures at ambient temperature (including foam tunnels); — spraying in a ventilated booth;

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date	25th January 2018	Version	6.0
Revision date	03rd February 2025		

m-tolyldiene diisocyanate

Restriction	Conditions of restriction
	— application by roller; — application by brush; — application by dipping and pouring; — mechanical post treatment (e.g. cutting) of not fully cured articles which are not warm anymore; — cleaning and waste; — any other uses with similar exposure through the dermal and/or inhalation route; (c) the training elements in points (a), (b) and (c) of paragraph 5 for the following uses: — handling incompletely cured articles (e.g. freshly cured, still warm); — foundry applications; — maintenance and repair that needs access to equipment; — open handling of warm or hot formulations (> 45 °C); — spraying in open air, with limited or only natural ventilation (includes large industry working halls) and spraying with high energy (e.g. foams, elastomers); — and any other uses with similar exposure through the dermal and/or inhalation route. 5. Training elements: (a) general training, including on-line training, on: — chemistry of diisocyanates; — toxicity hazards (including acute toxicity); — exposure to diisocyanates; — occupational exposure limit values; — how sensitisation can develop; — odour as indication of hazard; — importance of volatility for risk; — viscosity, temperature, and molecular weight of diisocyanates; — personal hygiene; — personal protective equipment needed, including practical instructions for its correct use and its limitations; — risk of dermal contact and inhalation exposure; — risk in relation to application process used; — skin and inhalation protection scheme; — ventilation; — cleaning, leakages, maintenance; — discarding empty packaging; — protection of bystanders; — identification of critical handling stages; — specific national code systems (if applicable); — behaviour-based safety; — certification or documented proof that training has been successfully completed (b) intermediate level training, including on-line training, on: — additional behaviour-based aspects; — maintenance; — management of change; — evaluation of existing safety instructions; — risk in relation to application process used; — certification or documented proof that training has been successfully completed (c) advanced training, including on-line training, on: — any additional certification needed for the specific uses covered; — spraying outside a spraying booth; — open handling of hot or warm formulations (> 45 °C); — certification or documented proof that training has been successfully completed 6. The training shall comply with the provisions set by the Member State in which the industrial or professional user(s) operate. Member States may implement or continue to apply their own national requirements for the use of the substance(s) or mixture(s), as long as the minimum requirements set out in paragraphs 4 and 5 are met. 7. The supplier referred to in point (b) of paragraph 2 shall ensure that the recipient is provided with training material and courses pursuant to paragraphs 4 and 5 in the official language(s) of the Member State(s) where the substance(s) or mixture(s) are supplied. The training shall take into consideration the specificity of the products supplied, including composition, packaging, and design. 8. The employer or self-employed shall document the successful completion of the training referred to in paragraphs 4 and 5. The training shall be renewed at least every five years. 9. Member States shall include in their reports pursuant to Article 117(1) the following information:

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date 25th January 2018
Revision date 03rd February 2025 Version 6.0

m-tolylidene diisocyanate

Restriction	Conditions of restriction
	(a) any established training requirements and other risk management measures related to the industrial and professional uses of diisocyanates foreseen in national law; (b) the number of cases of reported and recognised occupational asthma and occupational respiratory and dermal diseases in relation to diisocyanates; (c) national exposure limits for diisocyanates, if there are any; (d) information about enforcement activities related to this restriction. 10. This restriction shall apply without prejudice to other Union legislation on the protection of safety and health of workers at the workplace.

toluene

Restriction	Conditions of restriction
48	Shall not be placed on the market, or used, as a substance or in mixtures in a concentration equal to or greater than 0,1 % by weight where the substance or mixture is used in adhesives or spray paints intended for supply to the general public.

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out (mixture).

More information

REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the placing on the market of explosives precursors and their use - ANNEX II NOTIFIABLE EXPLOSIVES PRECURSORS: Aluminum powder - stabilized (CAS no. 7429-90-5). All suspicious transactions and significant loss or theft should be reported to the appropriate national contact point.

SECTION 16: Other information

A list of standard risk phrases used in the safety data sheet

EUH066	Repeated exposure may cause skin dryness or cracking.
EUH204	Contains isocyanates. May produce an allergic reaction.
EUH208	Contains neodecanoic acid, cobalt salt. May produce an allergic reaction.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H228	Flammable solid.
H261	In contact with water releases flammable gases.
H301+H311	Toxic if swallowed or in contact with skin.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312+H332	Harmful in contact with skin or if inhaled.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H351	Suspected of causing cancer.
H360FD	May damage fertility. May damage the unborn child.
H361d	Suspected of damaging the unborn child.
H370	Causes damage to organs.
H372	Causes damage to organs through prolonged or repeated exposure.
H372	Causes damage to the gastrointestinal tract through prolonged or repeated exposure.

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date	25th January 2018	Version	6.0
Revision date	03rd February 2025		

H372	Causes damage to the central nervous system through prolonged or repeated exposure.
H373	May cause damage to the central nervous system through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H373	May cause damage to hearing organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Guidelines for safe handling used in the safety data sheet

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing vapours/aerosols.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P312	Call a POISON CENTRE/doctor if you feel unwell.
P370+P378	In case of fire: Use foam (alcohol resistant), carbon dioxide, a spray mist, powder to extinguish.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to by handing over to a person authorized to dispose of waste or a site designated by the town.

Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

Key to abbreviations and acronyms used in the safety data sheet

Acute Tox.	Acute toxicity
ADR	Agreement concerning the international carriage of dangerous goods by road
Aquatic Acute	Hazardous to the aquatic environment
Aquatic Chronic	Hazardous to the aquatic environment (chronic)
Asp. Tox.	Aspiration hazard
BCF	Bioconcentration Factor
BOD	Biochemical oxygen demand
Carc.	Carcinogenicity
CAS	Chemical Abstracts Service
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures
COD	Chemical oxygen demand
EC	Identification code for each substance listed in EINECS
EC ₀	Concentration of a substance when it is affected 0 % of the population
EC ₁₀	Concentration of a substance when it is affected 10 % of the population
EC ₅₀	Concentration of a substance when it is affected 50 % of the population
EINECS	European Inventory of Existing Commercial Chemical Substances
EL ₀	Effective Loading for 0 % of the tested organisms
EL ₅₀	Effective Loading for 50 % of the tested organisms
EmS	Emergency plan
EU	European Union
EuPCS	European Product Categorisation System
Eye Dam.	Serious eye damage
Eye Irrit.	Eye irritation
Flam. Liq.	Flammable liquid
Flam. Sol.	Flammable solid

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date	25th January 2018	Version	6.0
Revision date	03rd February 2025		

IATA	International Air Transport Association
IBC	International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals
IC ₅₀	Concentration causing 50% blockade
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
INCI	International Nomenclature of Cosmetic Ingredients
ISO	International Organization for Standardization
IUPAC	International Union of Pure and Applied Chemistry
LC ₀	Lethal concentration of a substance in which it can be expected death of 0% of the population
LC ₅₀	Lethal concentration of a substance in which it can be expected death of 50% of the population
LD ₅₀	Lethal dose of a substance in which it can be expected death of 50% of the population
LL ₀	Lethal Loading for 0 % of tested organisms
LL ₅₀	Lethal Loading for 50 % of tested organisms
LOAEL	Lowest observed adverse effect level
log K _{ow}	Octanol-water partition coefficient
Muta.	Germ cell mutagenicity
NOAEC	No observed adverse effect concentration
NOAEL	No observed adverse effect level
NOEC	No observed effect concentration
NOEL	No observed effect level
NOELR	No Observed Effect Loading Rate
OEL	Occupational Exposure Limits
PBT	Persistent, bioaccumulative and toxic
PMT	Persistent, mobile and toxic
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
Repr.	Reproductive toxicity
Resp. Sens.	Respiratory sensitization
RID	Agreement on the transport of dangerous goods by rail
Skin Corr.	Skin corrosion
Skin Irrit.	Skin irritation
Skin Sens.	Skin sensitization
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure
UN number	Four-figure identification number of the substance or article taken from the UN Model Regulations
UVCB	Substances of unknown or variable composition, complex reaction products or biological materials
VOC	Volatile organic compounds
vPvB	Very persistent and very bioaccumulative
vPvM	Very persistent and very mobile
Water-react.	Substance or mixture which in contact with water emits flammable gas

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

Recommended restrictions of use

not available

Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended.
REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

The changes (which information has been added, deleted or modified)

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended



SU2013 Synthetic top color UNIVERSAL

Creation date	25th January 2018	Version	6.0
Revision date	03rd February 2025		

The version 6.0 replaces the SDS version from 31 October 2023. Changes were made in sections 2, 8, 9, 11, 12, 13, 15 and 16.

More information

Classification procedure - calculation method.

Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.

Příloha bezpečnostního listu pro výrobek: Rozpouštědlová nátěrová hmota

1. Expoziční scénář: Průmyslové použití

Sektor použití : SU3
Kategorie chemických výrobků : PC9a
Dílčí procesy kryté expozičním scénářem : PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC10, PROC13, PROC 15
Uvolňování výrobku do životního prostředí : ERC4

Základní podmínky omezující riziko pro pracovníky:

Trvání pracovních činností : expozice trvající nejvýše 8 hodin / den
Koncentrace : práce s nátěrovou hmotou, popř. naředěnou na aplikační hustotu
Teplota : provádění prací při doporučené teplotě +5 až 25°C
Obecná opatření na omezení rizik : pracovat v ochranném pracovním oděvu, při kontaktu s nátěrovou hmotou používat ochranné rukavice a ochranné brýle, limitní koncentrace látek obsažených ve směsi jsou uvedeny v oddíle 8 bezpečnostního listu a mohou se lišit v závislosti na typu nátěrové hmoty
Při práci dodržovat obecné zásady hygieny a bezpečnosti práce.
Prostředí, kde jsou činnosti prováděny : vnitřní prostředí s odvětráváním.

Doplňující požadavky omezující riziko pro pracovníky vykonávající dílčí pracovní činnosti:

Dílčí pracovní činnost prováděná s výrobkem	Kategorie procesu	Požadované doplňující opatření
Přečerpávání nátěrových hmot z / do zásobníků a zařízení v uzavřeném systému	PROC1 Použití v rámci uzavřeného výrobního procesu	Nevyžadováno
Přečerpávání nátěrových hmot z / do zásobníků a zařízení v nesespecializovaném zařízení s možností expozice osob a životního prostředí	PROC8a přeprava výrobku (napouštění / vypouštění) z / do nádob / kontejnerů v nesespecializovaných zařízeních	Místní odsávání, popř. dobré větrání (3 – 5 výměn vzduchu za hodinu).
Přečerpávání nátěrových hmot z / do zásobníků a zařízení v nesespecializovaném zařízení s možností expozice osob a životního prostředí	PROC8b PROC8a přeprava výrobku (napouštění / vypouštění) z / do nádob / kontejnerů v specializovaných zařízeních	Místní odsávání, popř. dobré větrání (3 – 5 výměn vzduchu za hodinu).
Míchání, směšování, ředění nátěrových hmot v otevřených zařízeních s možností expozice osob a životního prostředí	PROC5 míchání nebo směšování v dávkových procesech při výrobě směsí	Místní odsávání, popř. dobré větrání (3 – 5 výměn vzduchu za hodinu).
Aplikace stříkáním	PROC7 průmyslové nástřikové techniky	Robotický nástřik provádět v uzavřených komorách nebo uzavřených kabinách s odsáváním a zajištěním nezávislého přívodu vzduchu. Ruční nástřik provádějte ve stříkacích kabinách nebo v intenzívně větraných prostorách (5-10 výměn vzduchu za hodinu) za použití polomasky nebo masky s filtrem typu A/P2.
Ruční aplikace nátěrových hmot válečkem, štětkou, stěrkou	PROC10 aplikace válečkem, stěrkou nebo štětkou	Místní odsávání, popř. dobré větrání (3 – 5 výměn vzduchu za hodinu).
Nanášení nátěrových hmot poléváním nebo ponořením	PROC13 úprava předmětů máčením a poléváním	Místní odsávání, popř. dobré větrání (3 – 5 výměn vzduchu za hodinu).
Volné sušení nátěrového filmu při normální teplotě nebo mírně zvýšené teplotě	PROC4 použití v rámci dávkového a jiného procesu s větší možností expozice	Provádět za místního odsávání, popř. dobré větrání (3 – 5 výměn vzduchu za hodinu).
Kontinuální postupy sušení a vytvrzování nátěrových hmot za zvýšené teploty v sušících tunelech s odsáváním par	PROC2 použití v rámci nepřetržitého chemického výrobního procesu s příležitostnou kontrolovanou expozicí (např. odběr	Nevyžaduje další opatření na omezení rizik.

Dílčí pracovní činnost prováděná s výrobkem	Kategorie procesu	Požadované doplňující opatření
	vzorků)	
Násadové postupy sušení a vytvrzování filmu nátěrových hmot za zvýšené teploty v odsávaných komorách.	PROC3 použití v rámci uzavřeného dávkového procesu výroby směsí	Nevyžaduje další opatření na omezení rizik.
Strojní čištění a promývání uzavřených nádrží, zásobníků a zařízení vybavených odsáváním par	PROC3 použití v rámci uzavřeného dávkového procesu výroby směsí	Nevyžaduje další opatření na omezení rizik.
Ruční čištění malých zásobníků, aplikačních zařízení a nářadí	PROC10 aplikace válečkem, stěrkou nebo štětcem	Lokální odsávání v místě potencionálního úniku emisí nebo dobré větrání (3 – 5 výměn vzduchu za hodinu).
Kontrolní činnosti prováděné s nátěrovými hmotami v laboratořích	PROC15 použití jako laboratorního reagentu (práce s výrobkem v laboratořích)	Dobré větrání (3 – 5 výměn vzduchu za hodinu).
Činnosti s odpady výrobku a odpady znečištěnými výrobkem		Při nebezpečí styku s odpady používat rukavice. Odpady ukládat do uzavíratelných obalů uložených v dobře větraných skladech nebo ve venkovním prostředí. Odpady zajistit proti úniku do vody a půdy.

Doplňující požadavky omezující riziko pro životní prostředí

Omezování emisí do ovzduší	Při nanášení barvy stříkáním odstraňovat ze vzduchu odtahovaného z pracovních prostor úlet aerosolu barvy. Při překročení limitů spotřeby rozpouštědel stanovených vyhláškou využívat postupy rekuperace rozpouštědel z odpadního vzduchu nebo jinými postupy zaručujícími dodržení emisních parametrů stanovených předpisy pro ochranu ovzduší.
Omezování emisí do vody	Barvu a odpady znečištěné barvou skladovat v objektech stavebně zajištěných proti úniku úkapů a havarijních úniků do podzemních a povrchových vod. Při vypouštění odpadních vod dodržovat parametry stanovené pro dané zařízení vodohospodářským orgánem.
Odstraňování odpadů	Odpady barvy a materiálů znečištěných barvou odstraňovat ve spolupráci s osobami oprávněnými k nakládání s odpady.

2. Expoziční scénář: profesionální použití

Sektor použití : SU22
Kategorie chemických výrobků : PC9a
Dílčí procesy kryté expozičním scénářem : PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC 15, PROC19
Uvolňování výrobku do životního prostředí : ERC8a, REC8d

Základní podmínky omezující riziko pro pracovníky:

Trvání pracovních činností : expozice trvající nejvýše 8 hodin / den
Koncentrace : práce s nátěrovou hmotou, popř. naředěnou na aplikační hustotu
Teplota : provádění prací při doporučené teplotě +5 až 25°C s výjimkou sušení nebo vytvrzování filmu za zvýšené teploty
Obecná opatření na omezení rizik : pracovat v ochranném pracovním oděvu, při kontaktu s nátěrovou hmotou používat ochranné rukavice a ochranné brýle, limitní koncentrace látek obsažených ve směsi jsou uvedeny v oddíle 8 bezpečnostního listu a mohou se lišit v závislosti na typu nátěrové hmoty
Při práci dodržovat obecné zásady hygieny a bezpečnosti práce.

Prostředí, kde jsou činnosti prováděny : vnitřní prostředí s odvětráváním, popř. venkovní prostředí.

Doplňující požadavky omezující riziko pro pracovníky vykonávající dílčí pracovní činnosti:

Dílčí pracovní činnost prováděná s výrobkem	Kategorie procesu	Požadované doplňující opatření
Přečerpávání nátěrových hmot z / do zásobníků a zařízení v nespécializovaném zařízení s možností expozice osob a životního prostředí	PROC8a přeprava výrobku (napouštění / vypouštění) z / do nádob / kontejnerů v nespécializovaných zařízeních	Uvnitř budov: Místní odsávání, popř. dobré větrání (3 – 5 výměn vzduchu za hodinu). Venku: zajistit úkapy nátěrových hmot.
Míchání, směšování, ředění nátěrových hmot v otevřených zařízeních s možností expozice osob a	PROC5 míchání nebo směšování	Uvnitř: Místní odsávání, popř. dobré větrání (3 – 5 výměn vzduchu za hodinu).

Dílčí pracovní činnost prováděná s výrobkem	Kategorie procesu	Požadované doplňující opatření
životního prostředí	v dávkových procesech při výrobě směsí	Venku: činnosti vykonávat nejdéle 4hod./den bez potřeby dalších opatření, nebo používat ochranu dýchacích orgánů s filtrem typu A.
Aplikace stříkáním	PROC11 neprůmyslové nástřikové techniky	Uvnitř: nástřik provádět v uzavřených komorách nebo uzavřených kabinách s odsáváním a zajištěním nezávislého přívodu vzduchu. Místní odsávání, popř. dobré větrání (3 – 5 výměn vzduchu za hodinu). Ruční nástřik provádějte ve stříkacích kabinách nebo v intenzivně větraných prostorách (5-10 výměn vzduchu za hodinu) za použití polomasky nebo masky s filtrem typu A/P2. Venku: použití polomasky nebo masky s filtrem typu A/P2.
Ruční aplikace nátěrových hmot válečkem, štětcem, stěrkou	PROC10 aplikace válečkem, stěrkou nebo štětcem	Uvnitř: Místní odsávání, popř. dobré větrání (3 – 5 výměn vzduchu za hodinu). Venku: nevyžaduje se další opatření
Nanášení nátěrových hmot poléváním nebo ponořením	PROC13 úprava předmětů máčením a poléváním	Uvnitř: Místní odsávání, popř. dobré větrání (3 – 5 výměn vzduchu za hodinu). Venku: používat ochranu dýchacích orgánů s filtrem typu A.
Násadové postupy sušení a vytvrzování filmu nátěrových hmot za zvýšené teploty v odsávaných komorách.	PROC3 použití v rámci uzavřeného dávkového procesu výroby směsí	Nevyžaduje další opatření na omezení rizik.
Volné sušení nátěrového filmu při normální teplotě nebo mírně zvýšené teplotě	PROC4 použití v rámci dávkového a jiného procesu s větší možností expozice	Uvnitř: Provádět za místního odsávání, popř. dobré větrání (3 – 5 výměn vzduchu za hodinu). Venku: nevyžaduje se další opatření
Ruční čištění malých zásobníků, aplikačních zařízení a nářadí	PROC10 aplikace válečkem, stěrkou nebo štětcem	Uvnitř: Lokální odsávání v místě potencionálního úniku emisí nebo dobré větrání (3 – 5 výměn vzduch za hodinu). Venku: nevyžaduje se další opatření
Činnosti, při kterých dochází k přímému kontaktu s výrobkem bez použití pracovního nástroje	PROC19 ruční mísení s úzkým kontaktem za použití OOPP	Uvnitř: rukavice, místní odsávání nebo dobré větrání Venku: rukavice
Kontrolní činnosti prováděné s nátěrovými hmotami v laboratořích	PROC15 použití jako laboratorního reagentu (práce s výrobkem v laboratořích)	Dobré větrání (3 – 5 výměn vzduch za hodinu).
Činnosti s odpady výrobku a odpady znečištěnými výrobkem		Při nebezpečí styku s odpady používat rukavice. Odpady ukládat do uzavíratelných obalů uložených v dobře větraných skladech nebo ve venkovním prostředí. Odpady zajistit proti úniku do vody a půdy. Uvnitř: dobré větrání (3 – 5 výměn vzduch za hodinu).

Doplňující požadavky omezující riziko pro životní prostředí

Omezování emisí do ovzduší	Nejsou požadována žádná zvláštní opatření
Omezování emisí do vody	Barvu a odpady znečištěné barvou skladovat v objektech stavebně zajištěných proti úniku úkapů a havarijních úniků do podzemních a povrchových vod. Při vypouštění odpadních vod dodržovat parametry stanovené pro dané zařízení vodohospodářským orgánem.
Odstraňování odpadů	Odpady barvy a materiálů znečištěných barvou odstraňovat ve spolupráci s osobami oprávněnými k nakládání s odpady.