

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended



U6000 THINNER for polyurethane coatings

Creation date	27th October 2016	Version	3.0
Revision date	08th September 2022		

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. Product identifier**
Substance / mixture U6000 THINNER for polyurethane coatings
Number mixture
UFI U6000-A-C0000
Other mixture names QUXR-Y76F-A107-QHSC
U6000 ŘEDIDLO do polyuretanových nátěrových hmot
- 1.2. Relevant identified uses of the substance or mixture and uses advised against**
Mixture's intended use
THINNER U6000 is intended for thinning polyurethane paint materials and possibly other paint materials for which this thinner is prescribed.
Main intended use
PC-PNT-7 Paint removers, thinners and related auxiliaries
Mixture uses advised against
The product should not be used in ways other than those referred in Section 1.
- 1.3. Details of the supplier of the safety data sheet**
Manufacturer
Name or trade name COLORLAK, a.s.
Address Tovární 1076, Staré Město, 686 03
Czech Republic
Identification number (CRN) 49444964
VAT Reg No CZ49444964
Phone +420 572527111
E-mail colorlak@colorlak.cz
Web address www.colorlak.cz
- Competent person responsible for the safety data sheet**
Name Ing. Veronika Chytilová
E-mail chytilova@colorlak.cz
- 1.4. Emergency telephone number**
European emergency number: 112

SECTION 2: Hazards identification

- 2.1. Classification of the substance or mixture**
Classification of the mixture in accordance with Regulation (EC) No 1272/2008
The mixture is classified as dangerous.

Flam. Liq. 3, H226
Asp. Tox. 1, H304
Acute Tox. 4, H312+H332
Skin Irrit. 2, H315
Eye Irrit. 2, H319
STOT SE 3, H335, H336
STOT RE 2, H373 (central nervous system)
Aquatic Chronic 3, H412

Full text of all classifications and hazard statements is given in the section 16.

Most serious adverse physico-chemical effects

Flammable liquid and vapour.

Most serious adverse effects on human health and the environment

May cause damage to the central nervous system through prolonged or repeated exposure. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. Harmful in contact with skin or if inhaled. Harmful to aquatic life with long lasting effects.

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended



U6000 THINNER for polyurethane coatings

Creation date	27th October 2016	Version	3.0
Revision date	08th September 2022		

2.2. Label elements

Hazard pictogram



Signal word

Danger

Hazardous substances

Technical xylene (mixed with ethylbenzene)
2-methoxy-1-methylethyl acetate

Hazard statements

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to the central nervous system through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
H312+H332	Harmful in contact with skin or if inhaled.

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P314	Get medical advice/attention if you feel unwell.
P331	Do NOT induce vomiting.
P370+P378	In case of fire: Use foam (alcohol resistant), carbon dioxide, a spray mist, powder to extinguish.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to by handing over to a person authorized to dispose of waste or a site designated by the town.

Requirements for child-resistant fastenings and tactile warning of danger

Container must carry a tactile warning of danger. Container must be fitted with child-resistant fastening.

2.3. Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended.

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended



U6000 THINNER for polyurethane coatings

Creation date 27th October 2016
Revision date 08th September 2022 Version 3.0

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

THINNER U6000 is a mixture of organic solvents. Mixture of substances and additives specified below.

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
EC: 905-588-0 Registration number: 01-2119539452-40	Technical xylene (mixed with ethylbenzene)	65-70	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Acute Tox. 4, H312+H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Specific concentration limit: STOT RE 2, H373 (central nervous system): C ≥ 10 %	1, 2
Index: 607-195-00-7 CAS: 108-65-6 EC: 203-603-9 Registration number: 01-2119475791-29	2-methoxy-1-methylethyl acetate	25-35	Flam. Liq. 3, H226 STOT SE 3, H336	1

Notes

- 1 A substance for which exposure limits are set.
- 2 Substance of unknown or variable composition, complex reaction products or biological materials - UVCB.

Full text of all classifications and hazard statements is given in the section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Do not perform artificial respiration without self-protection (e.g. a mask). Take care of your own safety. If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet. If unconscious, put the person in the stabilized (recovery) position on his side with his head slightly bent backwards and make sure that airways are free; never induce vomiting. If the person vomits by himself, make sure that the vomit is not inhaled. In life threatening conditions first of all provide resuscitation of the affected person and ensure medical assistance. Respiratory arrest - provide artificial respiration immediately. Cardiac arrest - provide indirect cardiac massage immediately.

If inhaled

Take care of your own safety, do not let the affected person walk! Terminate the exposure immediately; move the affected person to fresh air. Beware of the contaminated clothes. Depending on the situation, call the medical rescue service and ensure medical treatment considering the frequent need of further observation for at least 24 hours.

If on skin

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible. Soap, soap solution or shampoo should be used if there is no skin injury. Provide medical treatment if skin irritation persists. Rinse skin with water or shower.

If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. Rinsing should continue at least for 10 minutes. Provide medical treatment, specialized if possible.

If swallowed

If the affected person vomits, make sure to prevent inhalation of the vomit (as there is a danger of lung damage after inhalation of these liquids in the airways also in infinitesimal amount). Ensure medical treatment considering the frequent need of further observation for at least 24 hours. Bring an original container with the label and the Safety Data Sheet of the given substance as appropriate.

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended



U6000 THINNER for polyurethane coatings

Creation date	27th October 2016	Version	3.0
Revision date	08th September 2022		

- 4.2. Most important symptoms and effects, both acute and delayed**
If inhaled
Cough, headache. May cause respiratory irritation. May cause drowsiness or dizziness.
If on skin
Causes skin irritation.
If in eyes
Causes serious eye irritation.
If swallowed
Irritation, nausea.
- 4.3. Indication of any immediate medical attention and special treatment needed**
Symptomatic treatment.

SECTION 5: Firefighting measures

- 5.1. Extinguishing media**
Suitable extinguishing media
Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.
Unsuitable extinguishing media
Water - full jet.
- 5.2. Special hazards arising from the substance or mixture**
In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.
- 5.3. Advice for firefighters**
Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Closed containers with the product near the fire should be cooled with water. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

SECTION 6: Accidental release measures

- 6.1. Personal precautions, protective equipment and emergency procedures**
Provide sufficient ventilation. Flammable liquid and vapour. Remove all ignition sources. Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Do not inhale mist/vapours/spray. Prevent contact with skin and eyes.
- 6.2. Environmental precautions**
Prevent contamination of the soil and entering surface or ground water.
- 6.3. Methods and material for containment and cleaning up**
Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.
- 6.4. Reference to other sections**
See the Section 7, 8 and 13.

SECTION 7: Handling and storage

- 7.1. Precautions for safe handling**
Prevent formation of gases and vapours in flammable or explosive concentrations and concentrations exceeding the occupational exposure limits. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. Use non-sparking tools. Use of antistatic clothes and footwear is recommended. Do not inhale mist/vapours/spray. Prevent contact with skin and eyes. No smoking. Wash hands and exposed parts of the body thoroughly after handling. Use only outdoors or in a well-ventilated area. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Take action to prevent static discharges. Avoid release to the environment.
- 7.2. Conditions for safe storage, including any incompatibilities**
Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Do not expose to sunlight. Store locked up. Keep container tightly closed. Keep cool.

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended



U6000 THINNER for polyurethane coatings

Creation date 27th October 2016
Revision date 08th September 2022 Version 3.0

Content	Packaging type	Material of package
0,42 l	can / tin	
0,7 l	can / tin	
2 l	jerry can	
4 l	jerry can	
9 l	jerry can	
170 l	barrel / drum	

Storage class 3A - Flammable liquids (flash point below 55 °C)
Storage temperature +5 to +25 °C

The specific requirements or rules relating to the substance/mixture

Solvent vapours are heavier than air and accumulate especially near the floor where they may form an explosive mixture with the air.

7.3. Specific end use(s)

not available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

The mixture contains substances for which occupational exposure limits are set.

European Union

Commission Directive 2000/39/EC

Substance name (component)	Type	Value	Note
2-methoxy-1-methylethyl acetate (CAS: 108-65-6)	OEL 8 hours	275 mg/m ³	Skin
	OEL 8 hours	50 ppm	
	OEL 15 minutes	550 mg/m ³	
	OEL 15 minutes	100 ppm	

European Union

Commission Directive 91/322/EEC

Substance name (component)	Type	Value	Note
Technical xylene (mixed with ethylbenzene)	OEL 8 hours	221 mg/m ³	
	OEL 8 hours	50 ppm	
	OEL 15 minutes	442 mg/m ³	
	OEL 15 minutes	100 ppm	

DNEL

2-methoxy-1-methylethyl acetate

Workers / consumers	Route of exposure	Value	Effect	Value determination	Source
Workers	Inhalation	275 mg/m ³	Systemic chronic effects		BL dodavatele
Workers	Dermal	796 mg/kg bw/day	Systemic chronic effects		BL dodavatele
Consumers	Inhalation	33 mg/m ³	Systemic chronic effects		BL dodavatele
Consumers	Dermal	320 mg/kg bw/day	Systemic chronic effects		BL dodavatele
Consumers	Oral	36 mg/kg bw/day	Systemic chronic effects		BL dodavatele

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended



U6000 THINNER for polyurethane coatings

Creation date

27th October 2016

Revision date

08th September 2022

Version

3.0

Technical xylene (mixed with ethylbenzene)

Workers / consumers	Route of exposure	Value	Effect	Value determination	Source
Workers	Inhalation	77 mg/m ³	Systemic chronic effects		ECHA
Workers	Inhalation	289 mg/m ³	Local acute effects		ECHA
Workers	Dermal	180 mg/kg bw/day	Systemic chronic effects		ECHA
Consumers	Inhalation	14.8 mg/m ³	Systemic chronic effects		ECHA
Consumers	Dermal	108 mg/kg bw/day	Systemic chronic effects		ECHA
Consumers	Oral	1.6 mg/kg bw/day	Systemic chronic effects		ECHA

PNEC

2-methoxy-1-methylethyl acetate

Route of exposure	Value	Value determination	Source
Freshwater environment	0.635 mg/l		BL dodavatele
Seawater	0.0635 mg/l		BL dodavatele
Microorganisms in wastewater treatment plants	100 mg/l		BL dodavatele
Freshwater sediment	3.29 mg/kg of dry substance of sediment		BL dodavatele
Sea sediments	0.329 mg/kg of dry substance of sediment		BL dodavatele
Soil (agricultural)	0.29 mg/kg of dry substance of soil		BL dodavatele

Technical xylene (mixed with ethylbenzene)

Route of exposure	Value	Value determination	Source
Freshwater environment	327 µg/l		ECHA
Seawater	327 µg/l		ECHA
Soil (agricultural)	2.31 mg/kg of dry substance of soil		ECHA
Food chain	327 µg/l		ECHA
Microorganisms in wastewater treatment plants	6.58 mg/l		EHCA
Sea sediments	12.46 mg/kg of dry substance of sediment		ECHA
Freshwater sediment	12.46 mg/kg of dry substance of sediment		ECHA

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended



U6000 THINNER for polyurethane coatings

Creation date	27th October 2016	Version	3.0
Revision date	08th September 2022		

8.2. Exposure controls

Follow the usual measures intended for health protection at work and especially for good ventilation. This can be achieved only by local suction or efficient general ventilation. If exposure limits cannot be observed in this mode, suitable protection of airways must be used. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

Eye/face protection

Protective goggles.

Skin protection

Hand protection: Protective gloves resistant to the product. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. Observe other recommendations of the manufacturer. Other protection: protective workwear. Contaminated skin should be washed thoroughly.

Respiratory protection

Mask with a filter against organic vapours in a poorly ventilated environment.

Thermal hazard

Not available.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	liquid
Colour	colourless, clear to slightly opalescent, colorless or slightly yellowish liquid
Odour	after organic solvents
Melting point/freezing point	data not available
2-methoxy-1-methylethyl acetate (CAS: 108-65-6)	-66 °C (BL dodavatele)
Technical xylene (mixed with ethylbenzene)	-94,96-13,2 °C (BL dodavatele)
Boiling point or initial boiling point and boiling range	≤60 °C (estimation)
2-methoxy-1-methylethyl acetate (CAS: 108-65-6)	145,8 °C (BL dodavatele)
Technical xylene (mixed with ethylbenzene)	136,2-144,5 °C (BL dodavatele)
Flammability	Flammable liquid of risk class II (ČSN 65 0201)
Technical xylene (mixed with ethylbenzene)	hořlavý (BL dodavatele)
Lower and upper explosion limit	
bottom	0,8 % (for Technical xylene)
2-methoxy-1-methylethyl acetate (CAS: 108-65-6)	1,5 % (BL dodavatele)
Technical xylene (mixed with ethylbenzene)	0,8 % (BL dodavatele)
upper	7 % (for Technical xylene)
2-methoxy-1-methylethyl acetate (CAS: 108-65-6)	7,0 % (BL dodavatele)
Technical xylene (mixed with ethylbenzene)	7 % (BL dodavatele)
Flash point	28 °C (PND 65 6065)
2-methoxy-1-methylethyl acetate (CAS: 108-65-6)	45 °C (BL dodavatele)
Technical xylene (mixed with ethylbenzene)	18-32 °C (BL dodavatele)
Auto-ignition temperature	data not available
2-methoxy-1-methylethyl acetate (CAS: 108-65-6)	333 °C (BL dodavatele)
Technical xylene (mixed with ethylbenzene)	432-528 °C (BL dodavatele)
Decomposition temperature	data not available
pH	non-soluble (in water)
Kinematic viscosity	<20,5 mm ² /s at 40 °C
Kinematic viscosity	data not available
2-methoxy-1-methylethyl acetate (CAS: 108-65-6)	1,23 mm ² /s at 40 °C (BL dodavatele)
Solubility in water	not miscible
2-methoxy-1-methylethyl acetate (CAS: 108-65-6)	247 g/l (BL dodavatele)
Technical xylene (mixed with ethylbenzene)	146-190,7 mg/l při 25 °C (BL dodavatele)
Partition coefficient n-octanol/water (log value)	log Pow 1,2 till 3,2 (range of substances contained)
Vapour pressure	3,37 - 9,44 hPa at 20 °C (range of substances contained)

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended



U6000 THINNER for polyurethane coatings

Creation date	27th October 2016	Version	3.0
Revision date	08th September 2022		

2-methoxy-1-methylethyl acetate (CAS: 108-65-6)	355 at 20 °C (BL dodavatele)
Technical xylene (mixed with ethylbenzene)	650-944 Pa (BL dodavatele)
Density and/or relative density	
Density	0,880-0,895 g/cm ³ at 23 °C (manufacturer's methodology B5/TD1-5 (ČSN EN ISO 2811-2))
2-methoxy-1-methylethyl acetate (CAS: 108-65-6)	0,964 g/cm ³ at 25 °C (BL dodavatele)
Technical xylene (mixed with ethylbenzene)	0,862-0,88 g/cm ³ at 25 °C (BL dodavatele)
Form	liquid: volatile, liquid without extraneous mechanical impurities
VOC content in product: category and subcategory of products - not classified	

9.2. Other information

Combustion temperature	42 °C (PND 65 6212)
Ignition temperature	430 °C (PND 33 0371)
Vapour density	> 1 (air = 1)
Total organic carbon (TOC)	0,786 kg/kg (calculation)
Solid content (dry matter)	0 % volume (calculation)
Calorific value: 35,52 MJ/kg (PND 65 6169); Heat of combustion: 37,70 MJ/kg (PND 65 6169); Flammability - temperature class: T2 (PND 33 0371).	

SECTION 10: Stability and reactivity

10.1. Reactivity

not available

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Unknown.

10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost.

10.5. Incompatible materials

Protect against strong acids, bases and oxidizing agents.

10.6. Hazardous decomposition products

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Inhalation of solvent vapors above values exceeding exposure limits for working environment may result in acute inhalation poisoning, depending on the level of concentration and exposure time. No toxicological data is available for the mixture.

Acute toxicity

Harmful in contact with skin or if inhaled.

2-methoxy-1-methylethyl acetate

Route of exposure	Parameter	Value	Exposure time	Species	Sex	Source
Oral	LD ₅₀	5000 mg/kg		Rat (Rattus norvegicus)		BL dodavatele
Inhalation	LC 0	>23.5 mg/l	6 hour	Rat (Rattus norvegicus)		BL dodavatele
Dermal	LD ₅₀	5000 mg/kg		Rat (Rattus norvegicus)		BL dodavatele

Technical xylene (mixed with ethylbenzene)

Route of exposure	Parameter	Value	Exposure time	Species	Sex	Source
Oral	LD ₅₀	3523 mg/kg bw		Rat		ECHA

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended



U6000 THINNER for polyurethane coatings

Creation date	27th October 2016	Version	3.0
Revision date	08th September 2022		

Technical xylene (mixed with ethylbenzene)

Route of exposure	Parameter	Value	Exposure time	Species	Sex	Source
Inhalation (vapor)	LD ₅₀	6350 ppm	4 hour	Rat		ECHA
Dermal	LD ₅₀	12126 mg/kg bw		Rabbit		ECHA
Oral	NOAEL	150 mg/kg bw		Rat		ECHA
Oral	LOAEL	150 mg/kg bw		Rat		ECHA

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Based on available data the classification criteria are not met.

Germ cell mutagenicity

Based on available data the classification criteria are not met.

Carcinogenicity

Based on available data the classification criteria are not met.

Reproductive toxicity

Based on available data the classification criteria are not met.

Toxicity for specific target organ - single exposure

May cause respiratory irritation. May cause drowsiness or dizziness.

Toxicity for specific target organ - repeated exposure

May cause damage to the central nervous system through prolonged or repeated exposure.

Repeated dose toxicity

2-methoxy-1-methylethyl acetate

Route of exposure	Parameter	Result	Value	Exposure time	Species	Sex	Source
Inhalation	NOAEL		1000 ppm		Rat		echa
Dermal	NOAEL		1000-1838 mg/kg bw/day		Rabbit		echa

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2. Information on other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 12: Ecological information

12.1. Toxicity

Acute toxicity

Harmful to aquatic life with long lasting effects.

2-methoxy-1-methylethyl acetate

Parameter	Method	Value	Exposure time	Species	Environment	Source
LC ₅₀		134 mg/l	96 hour	Fishes (Oncorhynchus mykiss)		BL dodavatele
EC ₅₀		408 mg/l	48 hour	Daphnia (Daphnia magna)		BL dodavatele
EC ₅₀		500 mg/l	48 hour	Aquatic invertebrates		echa
ErC ₅₀	OECD 201	>1000 mg/l	96 hour	Algae (Selenastrum capricornutum)		BL dodavatele

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended



U6000 THINNER for polyurethane coatings

Creation date 27th October 2016
Revision date 08th September 2022

Version 3.0

2-methoxy-1-methylethyl acetate

Parameter	Method	Value	Exposure time	Species	Environment	Source
EC 10		1 g/l	30 min	Microorganisms (Photobacterium phosphoreum)		ECHA

Technical xylene (mixed with ethylbenzene)

Parameter	Method	Value	Exposure time	Species	Environment	Source
EC ₅₀		96 mg/l	24 hour	Microorganisms (Photobacterium phosphoreum)		ECHA
EC ₅₀		2.2 mg/l	73 hour	Algae (Selenastrum capricornutum)		ECHA
IC ₅₀		1 mg/l	24 hour	Aquatic invertebrates		ECHA
LC ₅₀		2.6 mg/l	4 day	Fishes (Oncorhynchus mykiss)		ECHA

Chronic toxicity

2-methoxy-1-methylethyl acetate

Parameter	Value	Exposure time	Species	Environment	Source
LC ₅₀	63.5 mg/l	14 day	Fishes (Oncorhynchus mykiss)		ECHA

Technical xylene (mixed with ethylbenzene)

Parameter	Value	Exposure time	Species	Environment	Source
NOEC	960 µg/l		Aquatic invertebrates		ECHA
NOEC	1.3 mg/l	56 day	Fishes (Oncorhynchus mykiss)		ECHA

12.2. Persistence and degradability

not available

12.3. Bioaccumulative potential

Not available.

12.4. Mobility in soil

Not available.

12.5. Results of PBT and vPvB assessment

Product does not contain any substance meeting the criteria for PBT or vPvB in accordance with the Annex XIII of Regulation (EC) No 1907/2006 (REACH) as amended.

12.6. Endocrine disrupting properties

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

12.7. Other adverse effects

Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Proceed in accordance with valid regulations on waste disposal. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Empty containers may be used at waste incinerators to produce energy or deposited in a dump with appropriate classification. Perfectly cleaned containers can be submitted for recycling.

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended



U6000 THINNER for polyurethane coatings

Creation date	27th October 2016	Version	3.0
Revision date	08th September 2022		

Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended.
Decision 2000/532/EC establishing a list of wastes, as amended.

Waste type code

07 04 04 other organic solvents, washing liquids and mother liquors *
14 06 03 other solvents and solvent mixtures *
20 01 13 Solvents *

Packaging waste type code

15 01 10 packaging containing residues of or contaminated by hazardous substances *
(*) - Hazardous waste according to Directive 2008/98/EC on hazardous waste

SECTION 14: Transport information

14.1. UN number or ID number

UN 1993

14.2. UN proper shipping name

FLAMMABLE LIQUID, N.O.S. (Technical xylene (mixed with ethylbenzene), 2-methoxy-1-methylethyl acetate)

14.3. Transport hazard class(es)

3 Flammable liquids

14.4. Packing group

III - substances presenting low danger

14.5. Environmental hazards

No.

14.6. Special precautions for user

Reference in the Sections 4 to 8.

14.7. Maritime transport in bulk according to IMO instruments

not relevant

Additional information

Hazard identification No.

30

UN number

1993

Classification code

F1

Safety signs

3



SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended



U6000 THINNER for polyurethane coatings

Creation date	27th October 2016	Version	3.0
Revision date	08th September 2022		

Road transport - ADR

Special provisions	274, 601
Limited quantities	5 L
Excepted quantities	E1

Packaging

Packing instructions	P001, IBC03, LP01, R001
Mixed packing provisions	MP19

Portable tanks and bulk containers

Guidelines	T4
Special provisions	TP1, TP29

ADR tank

Tank code	LGBF
Vehicles for tank carriage	FL
Transport category	3
Tunnel restriction code	(D/E)

Special provision for

packages	V12
operation	S2

Railway transport - RID

Special provisions	274, 601
Excepted quantities	E1

Packaging

Packing instructions	P001, IBC03, LP01, R001
Mixed packing provisions	MP19

Portable tanks and bulk containers

Guidelines	T4
Special provisions	TP1, TP29

RID Tanks

Tank code	LGBF
Transport category	0

Special provision for

packages	W 12
----------	------

Marine transport - IMDG

EmS (emergency plan)	F-E, S-E
MFAG	310

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. Regulation (EC) No. 1272/2008 of the European Parliament and of the Council of 16th December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No. 1907/2006, as amended.

15.2. Chemical safety assessment

not available

SECTION 16: Other information

A list of standard risk phrases used in the safety data sheet

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended



U6000 THINNER for polyurethane coatings

Creation date	27th October 2016	Version	3.0
Revision date	08th September 2022		

H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H373	May cause damage to the central nervous system through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
H312+H332	Harmful in contact with skin or if inhaled.
Guidelines for safe handling used in the safety data sheet	
P501	Dispose of contents/container to by handing over to a person authorized to dispose of waste or a site designated by the town.
P102	Keep out of reach of children.
P101	If medical advice is needed, have product container or label at hand.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P405	Store locked up.
P271	Use only outdoors or in a well-ventilated area.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P403+P235	Store in a well-ventilated place. Keep cool.
P370+P378	In case of fire: Use foam (alcohol resistant), carbon dioxide, a spray mist, powder to extinguish.
P260	Do not breathe vapours/spray.
P314	Get medical advice/attention if you feel unwell.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P103	Read label before use.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

Key to abbreviations and acronyms used in the safety data sheet

ADR	European agreement concerning the international carriage of dangerous goods by road
BCF	Bioconcentration Factor
CAS	Chemical Abstracts Service
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures
DNEL	Derived no-effect level
EC ₅₀	Concentration of a substance when it is affected 50% of the population
EINECS	European Inventory of Existing Commercial Chemical Substances
EmS	Emergency plan
ES	Identification code for each substance listed in EINECS
EU	European Union
EuPCS	European Product Categorisation System
IATA	International Air Transport Association
IBC	International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals
IC ₅₀	Concentration causing 50% blockade
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
INCI	International Nomenclature of Cosmetic Ingredients
ISO	International Organization for Standardization
IUPAC	International Union of Pure and Applied Chemistry
LC ₅₀	Lethal concentration of a substance in which it can be expected death of 50% of the population
LD ₅₀	Lethal dose of a substance in which it can be expected death of 50% of the population
LOAEL	Lowest observed adverse effect level

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended



U6000 THINNER for polyurethane coatings

Creation date	27th October 2016	Version	3.0
Revision date	08th September 2022		

log Kow	Octanol-water partition coefficient
MARPOL	International Convention for the Prevention of Pollution from Ships
NOAEL	No observed adverse effect level
NOEC	No observed effect concentration
OEL	Occupational Exposure Limits
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted no-effect concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Agreement on the transport of dangerous goods by rail
UN	Four-figure identification number of the substance or article taken from the UN Model Regulations
UVCB	Substances of unknown or variable composition, complex reaction products or biological materials
VOC	Volatile organic compounds
vPvB	Very Persistent and very Bioaccumulative
Acute Tox.	Acute toxicity
Aquatic Chronic	Hazardous to the aquatic environment (chronic)
Asp. Tox.	Aspiration hazard
Eye Irrit.	Eye irritation
Flam. Liq.	Flammable liquid
Skin Irrit.	Skin irritation
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

Recommended restrictions of use

not available

Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended.
REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

The changes (which information has been added, deleted or modified)

The version 3.0 replaces the SDS version from 08 November 2018. Changes were made in sections 1, 2, 3, 7, 9, 11, 12, 14 and 16.

More information

Classification procedure - calculation method.

Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.