



C6000 THINNER for nitrocellulose paints

Use:

For thinning nitrocellulose paints if the product's standard does not prescribe another thinner, or for cleaning of application equipment according to customer's needs. The variant C6000/C0000 is intended for thinning the paint C2028 only. C6000 is also used for washing away of residues of resin from branch knots. The thinner C6000 can also be used for thinning synthetic paints applied by brush, roller or spraying if this method of thinning is recommended in the instructions for the particular paint. The variant V0004 of the thinner C6000 is suitable most of all for washing technological and working equipment. It can also be used for thinning nitrocellulose paints for different application methods (e.g. spraying, brush, roller, curtain coating) – should be tested in advance.

Variants: As per the valid price list.

Properties of the thinner:

Density variant A-C, A-V0004, A-V0012	0.82–0.85 g/cm ³
variant A-V0006	0.835–0.855 g/cm ³
variant Z1C0000	0.83–0.85 g/cm ³
variant Z1V0004	0.82–0.85 g/cm ³

Packaging: According to the current offer

Shelf life: At temperature 5-25°C during the warranty period stated on the package.

Disposal: Containers/unused product should be handed over to a person authorised for disposal of wastes or to a hazardous waste collection point established by the local authorities.

Product classification:

Signal word: **Danger**



Hazard statements:

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to the central nervous system through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

For details, see the Safety Data Sheet of this product.

“The user is responsible for the correct use of paints or for the composition and correct application of a paint system, i.e., the user must always consider all circumstances, conditions of application and processing that could affect the final quality of surface treatment.

No claims filed after using up the product will be taken into consideration. COLORLAK, a.s. reserves the right to change data in technical and advertising materials without any prior notice.”

“The technical recommendations contained in this Catalogue Sheet are given based on our experience and best knowledge of the state of the art in science and practice; they are not binding and they do not constitute any obligations unless expressly defined in the purchase contract.”

Marketing, 8/2026

COLORLAK, a.s., Tovární 1076, 686 03 Staré Město, Czech Republic
Phone: +420 572 527 111, Info: +420 800 145 555, www.colorlak.cz