



P7005

BENZINE TECHNICAL CLEANER

Use:

For degreasing and cleaning of surfaces of metal objects before coating and for cleaning of working tools and equipment. The BENZINE TECHNICAL CLEANER cannot be used to thin coating compositions.

Properties of the cleaner:

Density

0.70–0.725 g/cm³**Packaging:**

As per the current price list.

Shelf life:

At temperatures of 5–25°C for the duration of the warranty period stated on the package.

Disposal: Containers/unused product should be handed over to a person authorised for disposal of wastes or to a hazardous waste collection point established by the local authorities.

Product classification:Signal word: **Danger****Hazard statements:**

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H411	Toxic to aquatic life with long-lasting effects.

For details, see the Safety Data Sheet of this product.

“The user is responsible for correct use of paints or for the composition and correct application of a paint system, i.e., the user must always consider all circumstances – conditions of application and processing that could affect the final quality of surface treatment.

No claims filed after using the product will be taken into consideration. COLORLAK, a.s. reserves the right to change data in technical and advertising materials without any prior notice.”

“The technical recommendations contained in this Catalogue Sheet are given based on our experience and best knowledge of the state of the art in science and practice; they are not binding and they do not constitute any obligations unless expressly defined in the purchase contract.”

Marketing, 8/2026