



U6002 THINNER for urethane paints

Use: For thinning of polyurethane and acrylurethane paints (e.g. AXAPUR series) for which this thinner is prescribed.

Properties of the thinner:

Density

0.90–0.92 g/cm³

Packaging: As per the current offer.

Shelf life: At temperatures of 5–25°C for the duration of the warranty period indicated on the package of the coating material.

Disposal: Containers/unused product should be handed over to a person authorised for disposal of wastes or to a hazardous waste collection point established by the local authorities.



Product classification:

Signal word: **Danger**

Hazard statements:

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H373	May cause damage to the central nervous system through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

For details, see the Safety Data Sheet of this product.

“The user is responsible for correct use of paints or for the composition and correct application of a paint system, i.e. the user must always consider all circumstances – conditions of application and processing that could affect the final quality of surface treatment.

No claims filed after using up the product will be taken into consideration. The manufacturer COLORLAK, a.s. reserves the right to change data in technical and advertising materials without any prior notice.”

“Technical recommendations contained in this Catalogue Sheet are given based on our experience and best knowledge of the state of the art in science and practice; they are not bindings and they do not constitute any obligations unless expressly defined in the purchase contract.”

Marketing, 9/2019